

OLT-23-000534
OLT-23-000939
OLT-23-000940

ONTARIO LAND TRIBUNAL

PROCEEDING COMMENCED UNDER subsection 22(7) of the *Planning Act*, R.S.O. 1990, c. P.13, as amended.

Applicant and Appellant: Caivan (Perth GC) Limited
Subject: Request to amend the Official Plan – Failure to adopt the requested amendment
Description: To permit 940 single detached dwellings and townhomes, a nine-hole golf course, park and open space areas
Reference Number: OPA-01-2023
Property Address: 141 Peter Street, Part of Lots 26 & 27, Concession 1, Part Lots 25, 26 & 27, Concession 2, Geographic Township of Bathurst, and Part Lot 1 in Southeast Half Lot 1, Concession 1, Part Lot 1 in Southwest Half Lot 1, Concession 2, Geographic Township of Drummond, now in the Town of Perth, County of Lanark
Municipality/UT: Town of Perth / County of Lanark
OLT Case No.: OLT-23-000939
OLT Lead Case No.: OLT-23-000534

PROCEEDING COMMENCED UNDER subsection 34(11) of the *Planning Act*, R.S.O. 1990, c. P.13, as amended.

Applicant and Appellant: Caivan (Perth GC) Limited
Subject: Application to amend the Zoning By-law – Refusal or neglect to make a decision
Description: To permit 940 single detached dwellings and townhomes, a nine-hole golf course, park and open space areas
Reference Number: ZBL-03-2023
Property Address: 141 Peter Street, Part of Lots 26 & 27, Concession 1, Part Lots 25, 26 & 27, Concession 2, Geographic Township of Bathurst, and Part Lot 1 in Southeast Half Lot 1, Concession 1, Part Lot 1 in Southwest Half Lot 1, Concession 2, Geographic Township of Drummond, now in the Town of Perth, County of Lanark
Municipality/UT: Town of Perth / County of Lanark
OLT Case No.: OLT-23-000940

OLT-23-000534
OLT-23-000939
OLT-23-000940

PROCEEDING COMMENCED UNDER subsection 51(34) of the *Planning Act*, R.S.O. 1990, c. P.13, as amended.

Applicant and Appellant:	Caivan (Perth GC) Limited
Subject:	Proposed Plan of Subdivision – Failure of Approval Authority to make a decision
Description:	To permit 940 single detached dwellings and townhomes, a nine-hole golf course, park and open space areas
Reference Number:	09-T-22001
Property Address:	141 Peter Street, Part of Lots 26 & 27, Concession 1, Part Lots 25, 26 & 27, Concession 2, Geographic Township of Bathurst, and Part Lot 1 in Southeast Half Lot 1, Concession 1, Part Lot 1 in Southwest Half Lot 1, Concession 2, Geographic Township of Drummond, now in the Town of Perth, County of Lanark
Municipality/UT:	Town of Perth / County of Lanark
OLT Case No.:	OLT-23-000534
OLT Lead Case No.:	OLT-23-000534
OLT Case Name:	Caivan (Perth GC) v Lanark County

Witness Statement of Alex Meacoe, P.Eng. – Senior Geotechnical Engineer

Qualifications

1. I am a Professional Geotechnical Engineer (P.Eng.) as designated by Professional Engineers Ontario (PEO) and have more than 15 years of experience as a consulting engineer in the Province of Ontario. I obtained my Bachelor of Applied Science, Civil Engineering, degree from the University of Ottawa.
2. I am Senior Geotechnical Engineer at GEMTEC Consulting Engineers and Scientists Limited (GEMTEC). GEMTEC is a consulting company of engineers and geoscientists providing consulting services to a range of clients in both the private and public sector.
3. My consulting experience includes project management and providing senior geotechnical support for geotechnical investigations of commercial and residential land development projects, buried infrastructure, bridges, pavement design, as well as providing consultation services in support of construction projects.
4. My curriculum vitae is attached to this witness statement as Appendix "A". A copy of my Acknowledgement of Expert Duty is attached as Appendix "B".

Retainer

5. GEMTEC was retained by Caivan (Perth GC) Limited in 2021 to complete geotechnical, environmental, and hydrogeological investigations for the site.
6. As part of this retainer, I prepared a due diligence geotechnical investigation for the proposed residential development at the site. This due diligence geotechnical investigation included advancing boreholes at the site on wide spacings and providing preliminary geotechnical recommendations concerning the proposed development. GEMTEC also assessed any possible geotechnical hazards that may result from the proposed development.
7. Following the due diligence investigation, I prepared a detailed geotechnical investigation for the proposed residential development at the site. The detailed geotechnical investigation included advancing boreholes across the site on approximately 150 metre spacing, including installing monitoring wells, bedrock coring, and a slope assessment. The detailed geotechnical investigation provided further site specific geotechnical

recommendations concerning the proposed development based on the conceptual plans provided by Caivan.

8. GEMTEC produced the following deliverables as part of this project:
 - a. Letter to Caivan (Perth GC) Limited, titled "Slope Stability Assessment, Proposed Residential Development, 141 Peter Street, Perth, Ontario" dated February 17, 2023 (project no. 100737.002), and provided to Lanark County in February 2023.. A copy of this letter is provided in Appendix "C";
 - b. Report to Caivan (Perth GC) Limited, titled "Geotechnical Investigation, Proposed Residential Development, 141 Peter Street, Ottawa, Ontario" dated February 3, 2023 (project no. 100737.002), and provided to Lanark County in February 2023. A copy of this report is provided in Appendix "D";

Documents Reviewed

9. As part of this retainer and in preparation for my evidence, I reviewed the following documents:
 - a. Report prepared by GEMTEC, titled "Hydrogeological Investigation, Proposed Residential Development, 141 Perth Street, Perth, Ontario" dated February 22, 2023; and
 - b. Report prepared by J.F. Sabourin and Associated Inc., GEMTEC, Kilgour & Associates Ltd., and Schaeffer David Engineering Ltd., titled "Grants Creek Wetland Integrated Hydrologic Impact Assessment, Perth Western Annex Lands" dated March, 2023; and
 - c. J.D. Barnes, 2024. Draft Plan of Subdivision (Sheet 1, 2 and 3 of 3). Dated June 12, 2024. A copy of these plans are provided in Appendix "E".

Geotechnical Investigation

10. The purpose of the geotechnical investigation was to identify the general subsurface and groundwater conditions at the site by means of a limited number of boreholes and monitoring wells, and based on the factual information obtained, to provide geotechnical

engineering guidelines on the geotechnical design aspects of the project, including construction considerations that could influence design decisions.

11. Based on the results of the boreholes advanced at the site, the general subsurface conditions on the site consist of topsoil or peat (located within the wetland), silty clay, overlying glacial till, and bedrock. Surficial soil thicknesses are variable across the site with exposed bedrock forming high points and 1 to 3 metres of overburden in the low areas between bedrock knolls. The surface of the bedrock drops off to the northwest towards the Tay River where the overburden thickness exceeds 7 metres.
12. The results of the geotechnical investigation indicate that the proposed residential houses at the site could be founded on spread footings bearing on or within the undisturbed native overburden deposits or bedrock, or on engineered fill above the native overburden deposits or bedrock. There is no restriction on the amount of grade raise filling at the site, from a geotechnical perspective. The overburden excavations and any site preparation works required for the proposed residential development can be carried out using standard construction practices, from a geotechnical perspective.

Slope Stability Assessment

13. The purpose of this slope stability assessment was to establish the 'Erosion Hazard Limit' for the site along the Tay River at the northwest corner of the site. This limit constitutes a safe setback for any proposed development at the site with respect to slope stability. The Erosion Hazard Limit was determined based on the Natural Hazard Policies set forth in Section 3.1 of the Provincial Policy Statement. Current regulations restrict development within the Erosion Hazard Limit.
14. The Erosion Hazard Limit as per the Ministry of Natural Resources Technical Guide, consists of the stable slope allowance, the toe erosion allowance, and the erosion access allowance. The results of the slope stability assessment show that the slopes are considered stable from a geotechnical point of view, and therefore the stable slope allowance is not required. Since erosion was noted along the shoreline, a toe erosion allowance of 8 metres was applied to the crest of the slope. An erosion access allowance of 6 metres was included to allow construction equipment to access the site to repair a possible failed slope, as shown in the Slope Stability Assessment letter in Appendix D.

Summary Intended Expert Evidence

15. There are no constraints on the proposed development from a geotechnical perspective.

Conclusion and Recommendation to the Tribunal

16. In my professional opinion, the site is suitable for the proposed residential development, consisting of residential housing and service construction, from a geotechnical perspective.

17. A revised Draft Plan of Subdivision (refer to attached Appendix "E"), prepared by J.D. Barnes was provided to GEMTEC following completion of the geotechnical report. The revised Draft Plan of Subdivision includes updated wetland limits and proposed bridge crossing, which do not change the conclusions or recommendations provided in the geotechnical report.

18. I will be in attendance before the Tribunal to answer any relevant questions concerning the attached reports (Appendix C and D), the contents of this WS and the contents of any WS or other evidence filed by parties opposite.

Alex Meacoe, P.Eng.

June 12, 2024

APPENDIX A

Senior Geotechnical Engineer

EDUCATION

Bachelor of Applied Science in Civil Engineering, University of Ottawa, 2007

LICENCES & REGISTRATIONS

Registered Professional Engineer of Ontario, 2014

Alex is a Geotechnical Engineer with 15 years of experience working in Ottawa, Ontario. He has been involved in numerous transportation and development projects in Eastern Ontario and the Ottawa area. Alex has experience as a project manager and as a project engineer on a large variety of projects, including building and bridge foundations, settlement analysis, stability of slopes, embankment design, excavations, culverts, retaining walls, residential developments, sewers and watermains.

PROJECT EXPERIENCE

Highway 417 Widening, Maitland Avenue to Island Park Drive, Ottawa, Ontario – Geotechnical Investigation and foundation design recommendations for the overpass structures at Maitland Avenue, Woodroffe Avenue, and Pinecrest Street as well as several trenchless crossings, noise walls, overhead signs, and retaining walls along the widened alignment of Highway 417 from Maitland Avenue to Island Park Drive in Ottawa, Ontario. Bridge replacements and widening over busy 400 series highway in urban area. Rapid replacement methods were used.

Highway 7 Ouse River Bridge Replacement, Peterborough, Ontario – Geotechnical investigation and foundation design recommendations for replacement of Ouse River Bridge on Highway 7 in Peterborough County, Ontario. The Existing bridge structure over Ouse River was to be replaced with a structural culvert. Subsurface conditions consisting of a thick deposit of sensitive silty clay over glacial till.

Highway 35 Stoney Creek Bridge Replacement, Lindsay, Ontario – Geotechnical investigation and foundation design recommendations for the replacement of the Stoney Creek Bridge Culvert along Highway 35 south of Lindsay, Ontario. The two existing bridge culverts over Stoney Creek were to be replaced with a structural culvert. Subsurface conditions consisting of a deposit of organic soils over sensitive silty clay over glacial till.

Bridge and Culvert Replacements, Aviation Parkway to Ramsayville Road, Ottawa, Ontario – Geotechnical investigation and foundation design recommendations for replacement of bridges and culverts, as well as tunnel and trenchless installations, noise barrier walls, high mast lighting

PROJECT EXPERIENCE *(continued)*

and overhead signs along Highway 417 from Aviation Parkway to Ramsayville Road in Ottawa, Ontario. Subsurface conditions consisting of a thick deposit of sensitive silty clay over glacial till to shallow bedrock.

Proposed New Overpass Structure and Intersection Upgrades, Highway 17 at 504, West of Arnprior, Ontario –

Geotechnical Investigation and foundation design services for proposed new overpass structure and intersection improvements over the future widened Highway 17 at Highway 508/54 west of Arnprior, Ontario. New structure included large embankments founded on thick deposits of sensitive silty clay over glacial till.

Replacement of County Road 43 Bridge over Kemptville Creek, Kemptville, Ontario – geotechnical and hydrogeological investigation for the proposed replacement of the County Road 43 Bridge over Kemptville Creek in Kemptville, Ontario. The investigation included advancing boreholes and completing multi-channel analysis of surface waves (MASW) testing to determine the shear wave velocity. The bridge replacement included recommendations for temporary access roadways adjacent to the existing bridge for the construction of the new bridge. The bridge replacement included recommendations for seismic site class, overburden and bedrock excavations, temporary shoring, bridge foundations options of shallow foundations and caissons, backfill and lateral earth pressures, and approach embankment widening and construction.

Sylvester Powers Bridge Replacement, Kennelly Road, County of Renfrew, Ontario – geotechnical investigation for the proposed replacement of the Sylvester Power Bridge in the County of Renfrew, Ontario. The subsurface conditions at the bridge consists of a thick deposit of sensitive silty clay. The bridge replacement included recommendations for excavations, foundation design alternatives for twin box culverts, corrugated steel pipe low profile arch culvert, and replacing the existing bridge deck, seismic design, and detailed settlement analysis for the proposed widening of the approach embankments.

St Andre Road Bridge Rehabilitation, Township of Embrun, Ontario – geotechnical investigation for the proposed replacement of the St Andre Road Bridge in the Township of Embrun, Ontario. The subsurface conditions at the bridge consists of a thick deposit of sensitive silty clay. The investigation included advancing boreholes and completing multi-channel analysis of surface waves (MASW) testing to determine the shear wave velocity. The bridge replacement included recommendations for excavations, seismic site class, backfill, and pavement design for roadway construction.

Replacement of two Pedestrian Bridges, Terry Fox Participark, Ottawa, Ontario – geotechnical investigation for the proposed replacement of pedestrian bridges located in a City of Ottawa park. The pedestrian bridge replacements included recommendations for excavations, bearing capacities, seismic design, frost protection, foundation backfill and lateral earth pressures, and slope stability analysis of the existing and proposed embankments.

Rehabilitation of Waters Bridge and Dalmac Road Bridge in Ottawa, Ontario – geotechnical desktop assessment for the proposed rehabilitation of Waters Bridge and Dalmac Road Bridge located within the City of Ottawa. The bridge rehabilitations included recommendations for excavations, bearing capacities, frost protection, foundation backfill and lateral earth pressures.

Nation Valley Road Bridge and Cayer Road Bridge Replacement, Township of North Dundas, Ontario – geotechnical investigation for the proposed replacement of two bridge culverts within the Township of North Dundas, Ontario. The culvert replacements included recommendations for both reinforced concrete pipe and reinforced concrete box culverts, trench backfill, and pavement reinstatement.

PROJECT EXPERIENCE *(continued)*

2021 Renewal of 4 Culverts, Springhill Road, Huismans Road, Dunning Road, and Devine Road, Ottawa, Ontario – geotechnical investigation for the proposed replacement of four culverts within the City of Ottawa. The culvert will be replaced with precast reinforced concrete box culverts and included recommendations for excavations, groundwater taking, trench backfill, bearing capacities, and pavement design for roadway reinstatement.

Indian Creek Road Twin Culvert Replacement, Ottawa, Ontario – geotechnical investigation for the proposed replacement of Indian Creek Road Culvert within the City of Ottawa. The subsurface conditions at the culvert consists of a tall embankment overlying a thick deposit of sensitive silty clay. The culvert replacement included recommendations for excavations, material reuse, bedding and backfill, headwall recommendations, and pavement design for roadway reinstatement.

McNeely Road Drainage Improvements, Ottawa, Ontario – geotechnical investigation for the proposed drainage improvements along McNeely Road north of Whispering Willow Drive within the City of Ottawa. The drainage improvements included installing a new storm sewer and outlet to the existing Bear Creek, as well as a new ditch along McNeely Road. The recommendations for the proposed service installation included excavations, bedding and backfill, groundwater management, and a slope stability assessment of the proposed outfall construction at the existing creek.

Herzberg Road Storm Sewer Replacement, Ottawa, Ontario – geotechnical investigation for the proposed storm sewer replacement along Herzberg Road north of March Road within the City of Ottawa. The sewer replacement included installing a new storm sewer and headwall at the outlet location. The recommendations for the proposed service installation included excavations, bedding and backfill, groundwater management, and headwall construction recommendations.

Storm Sewer Rehabilitation, Blackburn Hamlet Bypass and Renaud Road, Ottawa, Ontario – geotechnical investigation for the proposed storm sewer replacement along the Blackburn Hamlet Bypass and Renaud Road within the City of Ottawa. The sewer replacement included replacing the existing storm sewer and headwall as well as a new run off channel. The recommendations for the proposed storm sewer replacement included excavations, bedding and backfill, groundwater management, headwall construction, retaining wall and embankment construction, and pavement design for roadway reconstruction.

Bilberry Creek Bank Remediation, Bilberry Creek, Ottawa, Ontario – slope stability assessment for the existing Bilberry Creek in Ottawa, Ontario. The investigation provided an assessment of the potential for slope failure as well as recommendations for the future remediation of the Bilberry Creek slopes including toe remediation, slope regrading, culvert installation, and slope reinforcement.

Hamlet Road Integrated Road, Sewer, and Watermain Reconstruction Project, Ottawa, Ontario – geotechnical investigation for the proposed replacement of the sanitary sewer, watermain, storm sewer, and full depth road reconstruction of Hamlet Road within Ottawa, Ontario.

Huron Avenue North Integrated Road, Sewer, and Watermain Reconstruction Project, Ottawa, Ontario – geotechnical investigation for the proposed replacement of the sanitary sewer, watermain, storm sewer, and full depth road reconstruction of Hamlet Road within Ottawa, Ontario.

PROJECT EXPERIENCE *(continued)*

Bel-Air Drive, Iris Street, Field Street, and Bedbrooke Street Integrated Road, Sewer, and Watermain Reconstruction Project, Ottawa, Ontario– geotechnical investigation for the proposed replacement of the sanitary sewer, watermain, storm sewer, and full depth road reconstruction of Bel-Air Drive, Iris Street, Field Street, and Bedbrooke Street within Ottawa, Ontario.


Argyle Street, Lochiel Street, Opeongo Road, and Hall Avenue Reconstruction, Renfrew, Ontario – geotechnical investigation for the proposed replacement of the watermain, localized repairs to the sanitary sewer, roadway trench reinstatement and rehabilitation of the remainder of the roadway of Argyle Street, Lochiel Street, Opeongo Road, and Hall Avenue in Renfrew, Ontario.

Sidewalk and Traffic Calming Measures, Halton Terrace, Ottawa, Ontario – geotechnical investigation for the proposed roadway improvements along Halton Terrace within Ottawa, Ontario.

Munroe Avenue East and Harry Street Reconstruction, Renfrew, Ontario– geotechnical investigation and slope stability assessment for the proposed replacement of the watermain, construction of a new storm sewer, localized repairs to the sanitary sewer, roadway trench reinstatement and rehabilitation of the remainder of the roadway of Munroe Avenue East and Harry Street in Renfrew, Ontario. A slope stability assessment was also carried out at the proposed location of the outfall location.

Stanley Avenue Watermain Renewal and Resurfacing, Ottawa, Ontario – geotechnical investigation for the proposed replacement of the watermain and roadway reconstruction on Stanley Avenue from Sussex Drive to Union Street within Ottawa, Ontario.

APPENDIX B



Ontario
 Ontario Land Tribunal
 Tribunal ontarien de l'aménagement du territoire

Acknowledgment Of Expert's Duty

OLT Case Number	Municipality
OLT-23-000534	Town of Perth / County of Lanark

1. My name is.....Alex Meacoe
 I live at the City of Gatineau
 in the Outaouais Region
 in the Province of Quebec

2. I have been engaged by or on behalf of Caivan (Perth GC) to provide evidence in relation to the above-noted Ontario Land Tribunal (`Tribunal`) proceeding.

3. I acknowledge that it is my duty to provide evidence in relation to this proceeding as follows:
 - a. to provide opinion evidence that is fair, objective and non-partisan;
 - b. to provide opinion evidence that is related only to matters that are within my area of expertise;
 - c. to provide such additional assistance as the Tribunal may reasonably require, to determine a matter in issue; and
 - d. not to seek or receive assistance or communication, except technical support, while under cross examination, through any means including any electronic means, from any third party, including but not limited to legal counsel or client.

4. I acknowledge that the duty referred to above prevails over any obligation which I may owe to any party by whom or on whose behalf I am engaged.

Date June 10, 2024

.....

Signature

APPENDIX C

February 17, 2023

File: 100737.002

Caivan (Perth GC) Limited
2934 Baseline Road, Suite 302
Ottawa, Ontario
K2H 1B2

Attention: Hugo Lalonde – Director, Land Development

**Re: Slope Stability Assessment
Proposed Residential Development
141 Peter Street
Perth, Ontario**

This letter presents the results of a slope stability assessment carried out for the proposed residential development located at 141 Peter Street in Perth, Ontario. The purpose of this slope stability assessment is to establish the 'Erosion Hazard Limit' for the site along the Tay River. This limit constitutes a safe setback for any proposed development at the site with respect to slope stability. The Erosion Hazard Limit was determined based on the Natural Hazard Policies set forth in Section 3.1 of the Provincial Policy Statements of the Planning Act of Ontario. Current regulations restrict development within the Erosion Hazard Limit.

BACKGROUND

It is understood that plans are being prepared for a new residential development at the Perth Golf Course located at 141 Peter Street.

GEMTEC Consulting Engineers and Scientists (GEMTEC) carried out a geotechnical investigation for the proposed development, the results of that investigation are provided in the following report:

- Report to Caivan (Perth GC) Limited, titled "Geotechnical Investigation, Proposed Residential Development, 141 Perth Street, Perth, Ontario" dated February 3, 2022 (Project No. 100737.002)

Based on the results of the previous investigation, the site is generally underlain by deposits of weathered silty clay crust and/or glacial till over shallow bedrock. The overburden deposits at the site are underlain by Precambrian bedrock at depths of up to about 3 metres below the existing ground surface, with some localized areas of up to about 8 metres. Several areas of outcropping bedrock were observed within the proposed development during the investigation.

DESCRIPTION OF SITE AND SLOPE

A site reconnaissance was carried out on May 12, 2022 by a member of our engineering staff. At that time, the geometry of the full height of the slope along the Tay River at the site was surveyed at seven locations using hand surveying equipment. The cross sections were positioned in the field by GEMTEC personnel. The locations of the cross sections are provided on Figure 1. Cross sections of the slopes are provided in the attached.

The geometries of the cross sections considered are summarized in Table 3.1:

Table 2.1 – Slope Cross Section Height and Slope Inclination

Cross Section	Slope Height (metres)	Approximate inclination from horizontal (degrees)
A-A	2.7	18
B-B	1.1	18
C-C	1.5	18
D-D	0.9	35
E-E	1.0	18
F-F	1.0	18
G-G	1.0	18

Based on our previous geotechnical investigation, the site is generally underlain by stiff to very stiff weathered silty clay crust and/or compact to dense glacial till over Precambrian bedrock. The slopes along the Tay River have an overall slope height of up to about 2.7 metres, but generally less than about 1.5 metres with inclinations generally about 18 and 35 degrees from the horizontal along the natural slope.

The site is vegetated with small to large trees and grass. No signs of slope instability (e.g., tension cracks) was observed at the site during our site reconnaissance. Signs of minor erosion was observed at the site during our site reconnaissance.

SLOPE STABILITY ASSESSMENT

For unstable slopes, the distance from the unstable slope to the safe setback line is called ‘Erosion Hazard Limit’. In accordance with the Ministry of Natural Resources (MNR) Technical Guide “Understanding Natural Hazards” dated 2001, the Erosion Hazard Limit consists of three

components: (1) Stable Slope Allowance, (2) Toe Erosion Allowance, and (3) Erosion Access Allowance.

The Stable Slope Allowance, as described in the MNR procedures, encompasses the area where a minimum slope inclination of 3 horizontal to 1 vertical is achieved (i.e., a slope angle of about 18 degrees from horizontal). Since the slopes along the Tay River are generally sloped at about 3 horizontal to 1 vertical, with the exception of cross section D-D which has a slope height of about 0.9 metres, the Stable Slope Allowance described in the MNR procedures is not required.

Given that minor erosion was observed along the slope, a Toe Erosion Allowance of 8 metres is required for stiff clay soils/glacial tills. The Toe Erosion Allowance is applied at the crest of the slope.

The MNR procedures also include the application of a 6 metre wide Erosion Access Allowance beyond the Toe Erosion Allowance to allow for access by equipment to repair a possible failed slope.

Based on the above information, the Erosion Hazard Limit for the slopes along the Tay River will be 14 metres, as measured from the crest of the slope.


CLOSURE

We trust that this letter is sufficient for your purposes. If you have any questions or require additional information, please call.



Alex Meacoe, P.Eng.
Senior Geotechnical Engineer

PS/WAM/BC



Bill Cavers, P.Eng.
Principal Geotechnical Engineer



Enclosures

N:\Projects\100700\100737.002\Deliverables\Slope Stability\100737.002_LET.02_Slope_V.02_2023-02-17.docx98



ATTACHMENTS

Figure 1 – Site Plan
Figure 2 to 8 – Slope Cross Sections




LEGEND

BH/ PH/ HA # ← BOREHOLE/ PROBEHOLE/ HAND AUGERHOLE ID
 XX.XX ← GROUND SURFACE ELEVATION, IN METRES GEODETIC DATUM

- BOREHOLE (current investigation by GEMTEC)
- BOREHOLE (previous investigation by GEMTEC)
- PROBEHOLE (current investigation by GEMTEC)
- PROBEHOLE (previous investigation by GEMTEC)
- HAND AUGERHOLE (previous investigation by GEMTEC)
- HAND AUGER HOLE (previous investigation by GEMTEC, 2018)
- HAND AUGER HOLE (current investigation by GEMTEC)
- HAND AUGER HOLE (current investigation by GEMTEC, elevations are based on DEM (not surveyed data))
- MONITORING WELL (current investigation by GEMTEC)

— APPROXIMATE DEVELOPMENT BOUNDARY
 - - - EROSION ACCESS ALLOWANCE
 - - - TOE EROSION ALLOWANCE

A A' SLOPE CROSS SECTION LOCATION




GEMTEC
 CONSULTING ENGINEERS AND SCIENTISTS

32 Steacie Drive
 Ottawa, ON K2K 2A9
 Tel: (613) 836-1422
 www.gemtec.ca
 ottawa@gemtec.ca

Client		Project	
CAIVAN (PERTH GC) LIMITED		100737.002	
Location			
SLOPE STABILITY ASSESSMENT PERTH GOLF COURSE 151 PETER STREET PERTH, ONTARIO			
Drwn by	Chkd by	SITE PLAN	
S.L.	W.A.M.		
Date	Rev.	FIGURE 1	
FEBRUARY 2023	1		


N:\Projects\100737\100737_002\Drafting\1.Drafting\100737_002_SlopeStability_R1_2023-02.dwg



Slope Cross Section AA
Perth Golf Development
Perth, Ontario

Project No.	100737.002
Drawn:	WAM
Date:	02/02/2023


Figure 2



Slope Cross Section BB
Perth Golf Development
Perth, Ontario

Project No.	100737.002
Drawn:	WAM
Date:	02/02/2023


Figure 3



Slope Cross Section CC
Perth Golf Development
Perth, Ontario

Project No.	100737.002
Drawn:	WAM
Date:	02/02/2023


Figure 4



Slope Cross Section DD
Perth Golf Development
Perth, Ontario

Project No.	100737.002
Drawn:	WAM
Date:	02/02/2023


Figure 5



Slope Cross Section EE
Perth Golf Development
Perth, Ontario

Project No.	100737.002
Drawn:	WAM
Date:	02/02/2023


Figure 6



Slope Cross Section FF
Perth Golf Development
Perth, Ontario

Project No.	100737.002
Drawn:	WAM
Date:	02/02/2023

Figure 7



Slope Cross Section GG
Perth Golf Development
Perth, Ontario

Project No.	100737.002
Drawn:	WAM
Date:	02/02/2023

Figure 8

APPENDIX D



GEMTEC


www.gemtec.ca

**Geotechnical Investigation
Proposed Residential Development
141 Peter Street
Ottawa, Ontario**

experience • knowledge • integrity



expérience • connaissance • intégrité



GEMTEC

www.gemtec.ca

Submitted to:

Caivan (Perth GC) Limited
2934 Baseline Road, Suite 302
Ottawa, Ontario
K2H 1B2

**Geotechnical Investigation
Proposed Residential Development
141 Peter Street
Ottawa, Ontario**

February 3, 2023
Project: 100737.002

GEMTEC Consulting Engineers and Scientists Limited
32 Steacie Drive
Ottawa, ON, Canada
K2K 2A9

February 3, 2023

File: 100737.002

Caivan (Perth GC) Limited
2934 Baseline Road, Suite 302
Ottawa, Ontario
K2H 1B2

Attention: Hugo Lalonde – Director, Land Development

**Re: Geotechnical Investigation
Proposed Residential Development
141 Peter Street
Perth, Ontario**

Enclosed is our geotechnical investigation report for the above noted project, in accordance with our proposal dated April 12, 2021. This report was prepared by Alex Meacoe, P.Eng. and reviewed by Brent Wiebe, P.Eng.



Alex Meacoe, P.Eng.



Brent Wiebe, P.Eng.

WAM/BC/BW

Enclosures

N:\Projects\100700\100737.002\Deliverables\Geotechnical\100737.002_RPT.01_GEOT_V.04_2023-02-03.docx

TABLE OF CONTENTS

1.0	INTRODUCTION.....	1
2.0	PROJECT DESCRIPTION AND SITE GEOLOGY	1
2.1	Project Description.....	1
2.2	Site Geology	1
3.0	METHODOLOGY	2
3.1	Geotechnical Investigation	2
3.2	Preliminary Geotechnical Investigation	3
4.0	SUBSURFACE CONDITIONS.....	4
4.1	General.....	4
4.2	Topsoil.....	5
4.3	Peat	5
4.4	Fill Material	5
4.5	Silty Sand	5
4.6	Silty Clay.....	6
4.7	Glacial Till	6
4.8	Auger Refusal and Bedrock	7
4.9	Groundwater Levels.....	10
4.10	Hydraulic Conductivity Results.....	12
4.11	Chemistry Relating to Corrosion	12
5.0	GEOTECHNICAL RECOMMENDATIONS AND GUIDELINES.....	13
5.1	General.....	13
5.2	Grade Raise Restrictions	13
5.3	Proposed Houses	13
5.3.1	Overburden Excavation	13
5.3.2	Bedrock Excavation	14
5.3.3	Groundwater Pumping	14
5.3.4	Placement of Engineered Fill	15
5.3.5	Spread Footing Design	15
5.3.6	Frost Protection of Foundations	16
5.3.7	Basement Foundation Wall Backfill and Drainage.....	16
5.3.8	Garage Foundation and Pier Backfill.....	17
5.3.9	Lateral Earth Pressures	17
5.3.10	Basement Concrete Slab Support.....	19
5.3.11	Swimming Pools	20
5.3.12	Seismic Site Classification and Liquefaction Potential.....	20
5.4	Site Services.....	20

5.4.1	Overburden Excavation	20
5.4.2	Bedrock Excavation	21
5.4.3	Permit to Take Water (PTTW).....	22
5.4.4	Bedding and Cover	22
5.4.5	Trench Backfill	23
5.4.6	Seepage Barriers.....	24
5.5	Internal Roadways	24
5.5.1	Subgrade Preparation.....	24
5.5.2	Pavement Design	24
5.5.3	Effects of Soil Disturbance	25
5.5.4	Granular Material Compaction	25
5.5.5	Asphaltic Cement.....	25
5.5.6	Transition Treatments.....	26
5.5.7	Pavement Drainage	26
5.6	Corrosion of Buried Concrete and Steel.....	26
6.0	ADDITIONAL CONSIDERATIONS	26
6.1	Winter Construction	26
6.2	Effects of Construction Induced Vibration	27
6.3	Disposal of Excess Soil.....	27
6.4	Design Review and Construction Observation.....	27
7.0	CLOSURE.....	28

LIST OF TABLES

Table 4.1 – Summary of Grain Size Distribution Testing (Glacial Till).....	6
Table 4.2 – Summary of Auger Refusal and Bedrock Depths and Elevations	7
Table 4.4 – Summary of Groundwater Levels	11
Table 4.5 – Summary of Corrosion Testing	12
Table 5.1 – Allowable Bearing Pressures for Foundations	15
Table 5.2 – Summary of Design Parameters (Building Foundation Walls).....	18
Table 5.2 – Peak Vibration Limits.....	21

LIST OF FIGURES

Figure 1 – Site Plan

Figure 2 – Bedrock Contour Plan

Figure 3 – Groundwater Elevation Contour Plan

LIST OF APPENDICES

Appendix A	Record of Borehole Logs – Current Investigation
Appendix B	Laboratory Test Results
Appendix C	Bedrock Core Photographs
Appendix D	Borehole Records – Previous Investigation
Appendix E	Chemical Analysis of Soil Samples

1.0 INTRODUCTION

This report presents the results of a geotechnical investigation carried out for the proposed residential development located at 141 Peter Street in Perth, Ontario. The purpose of the investigation was to identify the general subsurface conditions at the site by means of a limited number of boreholes and, based on the factual information obtained, to provide preliminary engineering guidelines on the geotechnical design aspects of the project, including construction considerations that could influence design decisions.

2.0 PROJECT DESCRIPTION AND SITE GEOLOGY

2.1 Project Description

Plans are being prepared for a new residential development at the Perth Golf Course located at 141 Peter Street, and a new sanitary sewer connecting the new development to the existing Cockburn Pumping Station located on Big Ben Trail or possibly connecting to the existing sanitary sewer on Rogers Road, south of South Street in Perth, Ontario

The following is known about the site and project:

- The site is located south of the Tay River and west of Peter Street in Perth, Ontario;
- The site is currently a recreational development (the Perth Golf Club); and,
- Based on the plans provided by Caivan Communities, the proposed development will consist of single detached houses, townhouses, stormwater management ponds, a new pumping station, and new community parks.

GEMTEC completed previous geotechnical investigations at this site for Jp2g Consultants Inc. and Caivan Communities. The results are provided in the following reports:

- Report to Jp2g Consultants Inc. titled “Preliminary Geotechnical Investigation, Proposed Residential Development, Perth West Annex, Perth, Ontario” dated July 24, 2019 (Project No. 63988.75).
- Report to Caivan Communities titled “Preliminary Geotechnical Investigation, Proposed Residential Development, Perth West Annex, 141 Peter Street, Perth, Ontario” dated May 21, 2021 (Project No. 100737.001).

2.2 Site Geology

A review of surficial geology maps, and previous geotechnical investigations at the location of the proposed development and along the proposed sanitary sewer alignment indicate that the site is underlain by organic deposits over shallow bedrock. Bedrock geology maps in the area of the site indicate the overburden is underlain by Precambrian bedrock at depths ranging from about

0 to 3 metres. Several areas of outcropping bedrock were observed within the proposed development during the previous investigation.

3.0 METHODOLOGY

3.1 Geotechnical Investigation

The fieldwork for this investigation was carried out between January 4 and February 2, March 15 and 25, and October 5 and 6, 2022. During those time periods, 37 boreholes (numbered 22-201, 22-202, 22-203, 22-203A, 22-205 to 22-214, 22-214A, 22-214B, 22-215, 22-216, 22-218, 22-219, 22-220, 22-221, 22-221A, 22-222, 22-222A, 22-223, 22-224, 22-225, 22-225A, 22-226, 22-227, 22-228, 22-228A, 22-229, and 22-230, 22-233A, 22-233B, 22-234, and 22-235) and three probeholes (numbered 22-106, 22-107, and 22-108) were advanced at the site for the proposed development, and four boreholes were advanced for installation of monitoring wells within the wetlands (boreholes 22-231, 22-231A, 22-232, and 22-232A). Boreholes 22-204 and 22-217 and probehole 22-105 were deleted from the initially planned program.

Details on the boreholes are provided below.

- The boreholes were advanced, within the overburden, to depths ranging from about 0.3 to 8.0 metres below ground surface. Upon reaching practical auger refusal in boreholes 22-201, 22-203A, 22-208, 22-214, 22-216, 22-221, 22-222 to 22-225, and 22-228, the boreholes were then advanced into the bedrock using rotary diamond drilling techniques while retrieving HQ sized bedrock core. These boreholes were advanced to total depths ranging from about 5.8 to 12.3 metres below ground surface.
- Boreholes 22-214A, 22-214B, 22-221A, 22-225A, and 22-228A were advanced adjacent to boreholes 22-214, 22-221, 22-225, and 22-228, respectively, for the installation of monitoring wells.
- Boreholes 22-233A, 22-233B, 22-234, and 22-235 were advanced, without sampling, using hollow stem augers and tricone advancement, to depths ranging from about 2.9 to 6.9 metres for the installation of monitoring wells.
- Boreholes 22-231, 22-231A, 22-232, and 22-232A were advanced in the wetlands to install monitoring wells. The boreholes were advanced using portable drilling equipment. The boreholes were advanced to depths ranging from about 1.6 to 7.1 metres below the ground surface. Upon reaching the bedrock surface in boreholes 22-231A and 22-232A were advanced into the bedrock using rotary diamond drilling techniques while retrieving NQ sized bedrock core. The coring in boreholes 22-231A and 22-232A was advanced to total depths of about 10.4 and 4.7 metres below the existing ground surface, respectively.
- Probeholes 22-106, 22-107, and 22-108 were advanced, without sampling, to practical auger refusal at depths ranging from about 0.4 to 3.2 metres below ground surface.

The boreholes were advanced using a track mounted hollow stem auger drill rig or portable drilling equipment supplied and operated by CCC Geotechnical and Environmental Drilling of Ottawa, Ontario.

Standard penetration tests, where required, were carried out in the boreholes and samples of the soils encountered were recovered using a 50 millimetre diameter split barrel sampler.

Monitoring wells were installed in boreholes 22-201, 22-203A, 22-205, 22-208, 22-214, 22-214B, 22-216, 22-221, 22-221A, 22-222, 22-222A, 22-223, 22-224, 22-225, 22-225A, 22-228, 22-228A, 22-231, 22-231A, 22-232, 22-232A, 22-233B, 22-234, and 22-235 for subsequent measurement of the groundwater level and hydraulic conductivity testing.

One soil sample from each of boreholes 22-212 and 22-226 was sent to Paracel Laboratories Ltd. for basic chemical testing relating to corrosion of buried concrete and steel.

The fieldwork was supervised throughout by a member of our engineering staff who directed the drilling operations, logged the samples and carried out the in-situ testing. Following the fieldwork, the soil and bedrock samples were returned to our laboratory for examination by a geotechnical engineer. Selected samples of the soil were tested for water content, and grain size distribution testing. Selected samples of the bedrock were tested for unconfined compressive strength testing.

The borehole locations were selected by GEMTEC and positioned on site relative to existing features. The ground surface elevations at the borehole locations were determined using precision GPS survey equipment. The elevations are referenced to geodetic datum NAD83 (CSRS) Epoch 2010, vertical network CGVD1928.

Descriptions of the subsurface conditions logged in the boreholes from the current investigation are provided on the Record of Borehole Sheets in Appendix A. The results of the laboratory tests are provided on the borehole logs and in Appendix B. Photographs of the bedrock core are provided in Appendix C. The test hole logs from the previous investigation are provided in Appendix D. The results of chemical testing completed on two soil samples related to corrosion potential are provided in Appendix E. The results of the hydraulic conductivity testing are provided in Appendix F. The approximate locations of the boreholes are shown on the Site Plan, Figure 1.

3.2 Preliminary Geotechnical Investigation

The fieldwork for the previous investigation was carried out between May 3 and 5, 2021. During that time, four boreholes (numbered 21-01 to 21-04, inclusive), four probeholes (numbered 21-101 to 21-104, inclusive), and two hand augerholes (numbered 21-201 and 21-202) were advanced at the site. Details on the test holes are provided below.

- The boreholes were advanced to depths ranging from about 0.4 to 6.7 metres below ground surface. Upon reaching practical auger refusal in boreholes 21-02, 21-03, and

21-04, the boreholes were then advanced into the bedrock using rotary diamond drilling techniques while retrieving HQ sized bedrock core. These boreholes were advanced to total depths of about 3.3 to 5.1 metres below ground surface.

- The probeholes were advanced, without sampling, to practical auger refusal at depths ranging from about 0.2 to 2.1 metres below ground surface.
- The hand augerholes were advanced to refusal at depths of about 1.1 and 0.9 metres below ground surface in hand augerholes 21-201 and 21-202, respectively.

The boreholes and probeholes were advanced using a track mounted hollow stem auger drill rig supplied and operated by CCC Geotechnical and Environmental Drilling of Ottawa, Ontario.

Standard penetration tests were carried out in the boreholes and samples of the soils encountered were recovered using a 50 millimetre diameter split barrel sampler.

The subsurface conditions encountered in the hand augerholes were determined based on visual and tactile examination of the material recovered on the flights of the augers.

The fieldwork was supervised throughout by a member of our engineering staff who directed the drilling operations, logged the samples and carried out the in-situ testing. Following the fieldwork, the soil and bedrock samples were returned to our laboratory for examination by a geotechnical engineer. Selected samples of the soil were tested for water content, and grain size distribution testing. Select samples of the bedrock were tested for unconfined compressive strength testing.

The test hole locations were positioned in the field and subsequently surveyed by GEMTEC personnel using our Trimble R10 GPS survey instrument. The elevations are referenced to geodetic datum.

4.0 SUBSURFACE CONDITIONS

4.1 General

As previously indicated, the soil and groundwater conditions identified in the test holes are given on the Record of Test Hole sheets in Appendix A. The logs indicate the subsurface conditions at the specific test locations only. Boundaries between zones on the logs are often not distinct, but rather are transitional and have been interpreted. The precision with which subsurface conditions are indicated depends on the method of excavation, the frequency and recovery of samples, the method of sampling, and the uniformity of the subsurface conditions. Subsurface conditions at other than the test locations may vary from the conditions encountered in the test holes. In addition to soil variability, fill of variable physical and chemical composition can be present over portions of the site or on adjacent properties.

The soil descriptions in this report are based on commonly accepted methods of classification and identification employed in geotechnical practice. Classification and identification of soil

involves judgement and GEMTEC does not guarantee descriptions as exact, but infers accuracy to the extent that is common in current geotechnical practice.

The groundwater conditions described in this report refer only to those observed at the place and time of observation noted in the report. Groundwater conditions may vary seasonally or as a consequence of construction activities in the area.

The following presents an overview of the subsurface conditions encountered in the test holes advanced during the current and previous investigation.

4.2 Topsoil

A surficial layer of topsoil was encountered at ground surface at hand augerholes 21-201 and 21-202 and boreholes 22-201 to 22-230 and 22-231, except 22-206. The thickness of the topsoil ranges from about 30 to 280 millimetres.

4.3 Peat

Deposits of peat were encountered extending from the ground surface at boreholes 22-231, 22-231A, 22-232 and 22-232A with thicknesses from about 70 to 560 millimetres.

4.4 Fill Material

Boreholes 21-01 to 21-04 were advanced through the golf course pathway and encountered about 80 to 200 millimetres of silty sand and gravel base material.

A layer of fill material was encountered below the pathway base material in boreholes 21-01 and 21-02, at the ground surface at borehole 22-206, and below the topsoil in boreholes 22-229 and 22-230. The fill material generally consists of silty sand with trace gravel and organic material. The fill material extends to depth ranging from about 0.8 to 2.3 metres below the ground surface.

Standard penetration tests carried out in the fill material gave N values of 4 to greater than 50 blows per less than 0.3 metres of penetration. The results of the in situ testing reflect a very loose to very dense relative density. The higher blow counts likely reflect the presence of the bedrock surface rather than the state of packing of the soil matrix.

The water content measured on three samples of the fill material is about 19 to 48 percent.

4.5 Silty Sand

Native deposits of silty sand with varying amounts of gravel were encountered below the topsoil and fill material, where encountered, in boreholes 22-201, 22-208, and, 22-214. The silty sand deposits extend to depths ranging from about 0.3 to 0.8 metres below existing grade.

Standard penetration tests carried out in the silty sand gave N values of 5 to greater than 50 blows per less than 0.3 metres of penetration. The results of the in situ testing reflect a loose to very

dense relative density. The higher blow counts likely reflect the presence of the bedrock surface rather than the state of packing of the soil matrix.

The water content measured on one sample of the silty sand is about 43 percent.

4.6 Silty Clay

Native deposits of weathered silty clay were encountered below the topsoil in hand augerhole 21-201 and boreholes 22-205, 22-207, 22-215, 22-216, 22-218, 22-221, 22-223, 22-226, 22-231, 22-231A, 22-232 and 22-232A. The weathered silty clay crust extends to depths ranging from about 0.6 to 2.3 metres below the existing ground surface.

Standard penetration tests carried out in the weathered silty clay gave N values of 2 to 23 blows per 0.3 metres of penetration. The results of the in situ testing indicate a stiff to very stiff consistency.

4.7 Glacial Till

Native deposits of glacial till were encountered below the topsoil, fill material, silty sand, and silty clay, where encountered, in all the borehole and hand augerhole locations, except boreholes 22-208, 22-218, 22-223, 22-229, 22-232 and 22-232A at depths ranging from about 0.1 to 2.4 metres below existing grade. Glacial till is a heterogeneous mixture of all grain sizes; however, at this site, the glacial till can be described as brown to grey silty sand to silty, clayey sand with varying amounts of gravel, cobbles and boulders. The glacial till was not fully penetrated in all the test holes, but was proven to depths ranging from about 0.4 to 8.0 metres below existing grade.

The results of grain size distribution testing on six samples of the glacial till are provided on the Soils Grading Chart in Appendix B and summarized in Table 4.1.

Table 4.1 – Summary of Grain Size Distribution Testing (Glacial Till)

Location	Sample Number	Sample Depth (metres)	Gravel (%)	Sand (%)	Silt (%)	Clay (%)
21-02	3	1.5 – 2.1	20	50	24	6
22-202	5	3.0 – 3.5	5	56	28	11
22-207	3	1.5 – 2.1	10	53	25	12
22-220	3	1.5 – 2.1	8	38	27	27
22-224	4	2.3 – 2.9	17	51	22	10

Location	Sample Number	Sample Depth (metres)	Gravel (%)	Sand (%)	Silt (%)	Clay (%)
22-230	4	2.3 – 2.9	6	56	27	11

Moisture content testing carried out on 29 samples of the glacial till indicates moisture contents ranging from about 7 to 37 percent.

4.8 Auger Refusal and Bedrock

Practical auger refusal occurred in probeholes 21-101 to 21-104, 22-106, 22-107, and 22-108, hand augerholes 21-201 and 21-202 and boreholes 22-202, 22-203, 22-205, 22-207, 22-209, 22-210, 22-211, 22-212, 22-213, 22-215, 22-218, 22-219, 22-220, 22-221, 22-222, 22-226, 22-227, 22-229, and 22-230 at depths ranging from about 0.2 to 7.5 metres below ground surface.

Precambrian bedrock was encountered and cored at boreholes 21-02, 21-03, 21-04, 22-201, 22-203A, 22-208, 22-214, 22-216, 22-221, 22-222, 22-223, 22-224, 22-225, 22-228, 22-231A and 22-232A at depths ranging from about 0.3 to 7.1 metres below existing grade.

Bedrock was encountered in boreholes 22-234 and 22-235 at depths of about 2.3 and 1.3 metres below the existing ground surface, respectively. The bedrock depths in these two boreholes were estimated based on the tricone drilling resistance and the drill cuttings and should be taken as approximate (i.e., no samples were recovered).

Auger refusal was encountered in probeholes 22-106, 22-107, and 22-108 at depths ranging from about 0.4 to 3.2 metres below the existing ground surface. Auger refusal may indicate the surface of the bedrock or boulders within the glacial till.

The bedrock surface and refusal depths are summarized in Table 4.2.

Table 4.2 – Summary of Auger Refusal and Bedrock Depths and Elevations

Test Hole Number	Ground Surface Elevation (metres)	Depth to Bedrock Surface (metres)	Bedrock Surface Elevation (metres)
21-01	135.1	> 6.7	< 128.4 ²
21-02	136.3	3.3	133.0
21-03	138.5	0.4	138.1
21-04	134.7	1.1	133.6

Test Hole Number	Ground Surface Elevation (metres)	Depth to Bedrock Surface (metres)	Bedrock Surface Elevation (metres)
21-101	135.3	2.0	133.3 ¹
21-102	135.3	2.1	133.2 ¹
21-103	134.9	0.6	134.3 ¹
21-104	134.9	0.2	134.7 ¹
22-106	136.5	0.4	136.1 ¹
22-107	135.4	2.7	132.7 ¹
22-108	137.4	3.2	134.2 ¹
21-201	134.7	1.1	133.6 ¹
21-202	135.4	0.9	134.4 ¹
22-201	136.0	6.4	129.6
22-202	135.6	7.5	128.2 ¹
22-203	135.9	1.0	134.9 ¹
22-203A	135.9	0.8	135.2
22-205	135.3	6.1	129.2 ¹
22-206	136.3	> 8.0	< 128.3 ²
22-207	135.0	3.4	131.7 ¹
22-208	137.5	0.3	137.2
22-209	137.2	1.3	136.0 ¹
22-210	135.7	3.2	132.5 ¹
22-211	134.8	0.9	133.9 ¹
22-212	136.6	2.0	134.6 ¹
22-213	137.2	2.2	135.0 ¹
22-214	137.9	4.7	133.3

Test Hole Number	Ground Surface Elevation (metres)	Depth to Bedrock Surface (metres)	Bedrock Surface Elevation (metres)
22-214A/B	137.8	4.6	132.9 ¹
22-215	135.3	2.4	132.8 ¹
22-216	134.6	1.0	133.6
22-218	136.0	0.6	135.4 ¹
22-219	136.8	3.5	133.3 ¹
22-220	137.5	2.6	135.0 ¹
22-221	134.6	1.2	133.4
22-221A	134.7	1.4	133.3 ¹
22-222	135.6	1.2	134.5
22-222A	135.7	1.2	134.6
22-223	134.6	1.3	133.3
22-224	135.6	4.5	131.2
22-225	134.9	1.2	133.7
22-225A	135.0	1.4	133.6 ¹
22-226	135.6	3.4	132.2 ¹
22-227	137.6	1.0	136.6 ¹
22-228	138.5	0.9	137.5
22-228A	138.5	0.9	137.5
22-229	135.6	2.1	133.5 ¹
22-230	135.0	4.0	130.9 ¹
22-231A	136.0	7.1	129.0
22-232A	139.3	1.6	137.7
22-233A	134.9	2.9	132.0 ¹

Test Hole Number	Ground Surface Elevation (metres)	Depth to Bedrock Surface (metres)	Bedrock Surface Elevation (metres)
22-233B	134.9	5.9	129.1 ¹
22-234	134.4	2.3	132.1 ³
22-235	134.3	1.3	132.9 ³

Notes:

1. Bedrock depth and elevation inferred from practical auger refusal. Auger refusal could occur on boulders within the glacial till or on the bedrock surface.
2. The bedrock surface was not encountered in boreholes 21-01 and 22-206.
3. the bedrock depths were recorded based on the tricone drilling resistance and the drill cuttings and should be taken as approximate (i.e., no samples were recovered).

Precambrian bedrock was encountered at boreholes 21-02, 21-03, 21-04, 22-201, 22-203A, 22-208, 22-214, 22-216, 22-221A, 22-222, 22-222, 22-223, 22-224, 22-225, 22-228, 22-228A, 22-231A, and 22-232A at depths ranging from about 0.3 to 7.1 metres below surface grade and cored using rotary diamond drilling techniques while retrieving HQ and NQ sized bedrock core. The bedrock was cored to depths ranging from about 3.3 to 12.3 metres below surface grade. The recovered bedrock core samples had total core recoveries (TCR's) of about 43 to 100 percent, solid core recovery (SCR) values of about 0 to 100 percent, and rock quality designation (RQD) values of about 0 to 100 percent. Based on these values, the bedrock quality is considered to range from very poor to excellent.

Photographs of the bedrock core are provided on Figures C1 to C12 in Appendix C.

The results of testing carried out on 11 samples of the recovered bedrock core indicate unconfined compressive strengths ranging from about 33 to 231 megapascals, but more generally between 115 and 230 megapascals, which indicates a strong to very strong classification. The two unconfined compressive strength results of 33 and 42 megapascals were likely the result of breakage along existing cracks within the bedrock core.

4.9 Groundwater Levels

Well screens were sealed in the overburden at boreholes 22-201, 22-205, 22-214B, 22-221A, 22-224, 22-225A, 22-231, 22-232, 22-233B, 22-234, and in the bedrock at boreholes 22-203A, 22-208, 22-214, 22-216, 22-221, 22-222, 22-222A, 22-223, 22-225, 22-228, 22-228A, 22-231A, 22-232A, and 22-235 for measurement of the groundwater levels. The groundwater levels in the monitoring wells were measured on February 9, 2022, and October 14, 15, and 17, 2022. The groundwater level depth and elevations are summarized in Table 4.4.

Table 4.4 – Summary of Groundwater Levels

Borehole/Test Pit Number	Groundwater Depth (metres)	Groundwater Elevation (metres)	Date
22-201	0.9	135.1	February 9, 2022
22-203A	1.2	134.7	February 9, 2022
22-205	0.5	134.9	February 9, 2022
22-208	2.7	134.8	February 9, 2022
22-214	2.0	136.0	February 9, 2022
22-214B	1.7	136.1	February 9, 2022
22-216	0.7	133.9	February 9, 2022
22-221	0.5	134.2	February 9, 2022
22-221A	0.6	134.1	February 9, 2022
22-222	1.1	134.5	February 9, 2022
22-222A	1.3	134.4	February 9, 2022
22-223	0.3	134.3	February 9, 2022
22-224	0.5	135.1	February 9, 2022
22-225	0.8	134.1	February 9, 2022
22-225A	0.9	134.1	February 9, 2022
22-228	4.1	134.3	February 9, 2022
22-228A	4.0	134.4	February 9, 2022
22-231	0.7	135.8	October 15, 2022
22-231A	0.8	135.3	October 15, 2022

Borehole/Test Pit Number	Groundwater Depth (metres)	Groundwater Elevation (metres)	Date
22-232	1.4	137.1	October 17, 2022
22-232A	1.3	138.1	October 17, 2022
22-233B	1.0	133.9	October 14, 2022
22-234	1.1	133.3	October 14, 2022
22-235	1.0	133.3	October 14, 2022

The groundwater levels may be higher during wet periods of the year such as the early spring or following periods of precipitation.

4.10 Hydraulic Conductivity Results

Hydraulic conductivity testing was completed in all monitoring wells as part of the hydrogeological investigation and is reported under separate cover.

4.11 Chemistry Relating to Corrosion

Soil samples obtained from boreholes 22-212 and 22-216 were sent to Paracel Laboratories for basic chemical testing relating to corrosion of buried concrete and steel. The results of chemical testing are provided in Appendix E and summarized in Table 4.5 below.

Table 4.5 – Summary of Corrosion Testing

Parameter	Borehole 22-212 Sample 3	Borehole 22-226 Sample 3
Chloride Content (µg/g)	< 5	< 5
Resistivity (Ohm.m)	96.4	49.7
Conductivity (µs/cm)	104	201
pH	7.26	7.53
Sulphate Content (µg/g)	< 5	16

5.0 GEOTECHNICAL RECOMMENDATIONS AND GUIDELINES

5.1 General

The information in the following sections is provided for the guidance of the design engineers and is intended for the design of this project only. As such, lot specific subgrade evaluations should be carried out by experienced geotechnical personnel to support the lot development plans and to confirm the recommendations presented in this report. Contractors bidding on or undertaking the works should examine the factual results of the investigation, satisfy themselves as to the adequacy of the information for construction, and make their own interpretation of the factual data as it affects their construction techniques, schedule, safety and equipment capabilities.

The professional services retained for this project include only the geotechnical aspects of the subsurface conditions at this site. The presence or implications of possible surface and/or subsurface contamination resulting from previous uses or activities of this site or adjacent properties, and/or resulting from the introduction onto the site from materials from off-site sources are outside the terms of reference for this report.

A Phase One and Two Environmental Site Assessment for this property was prepared by GEMTEC and submitted under a separate report.

5.2 Grade Raise Restrictions

The site is underlain by native deposits of weathered silty clay crust, silty sand, and glacial till.

Based on the borehole information, there are no grade raise restrictions at the site, from a geotechnical perspective. The settlement due to compression of the native soils as a result of fill placement should be relatively small and should occur during or shortly after the fill placement.

5.3 Proposed Houses

5.3.1 Overburden Excavation

The excavations for the foundations should be taken through any surficial topsoil, fill material, and into the native overburden deposits. The sides of the excavations should be sloped in accordance with the requirements in Ontario Regulation 213/91 under the Occupational Health and Safety Act. According to the Act, the shallow native overburden deposits can be classified as Type 3 and, accordingly, allowance should be made for excavation side slopes of 1 horizontal to 1 vertical extending upwards from the base of the excavation.

Excavation of the native soils above the groundwater should not present any excavation constraints. In contrast, excavation in the native sandy deposits below the groundwater level could present constraints. Groundwater inflow from the sandy deposits could cause sloughing of the sides of the excavation and disturbance to the soils at the bottom of the excavation. Flatter

side slopes of 3 horizontal to 1 vertical will be required if excavation is required below the groundwater level in sandy deposits.

Based on our observations on site, groundwater inflow from the overburden deposits into the excavations should be controlled by pumping from filtered sumps within the excavations. It is not expected that short term pumping during excavation will have any significant affect on nearby structures and services.

The silty clay deposits are sensitive to disturbance from ponded water, vibration and construction traffic. As such, care should be taken when excavating to avoid disturbance to the silty clay deposits, and it is suggested that final trimming to subgrade level be carried out using a hydraulic shovel equipped with a flat blade bucket. Allowance should be made to remove and replace any disturbed silty clay with compacted sand and gravel, such as that meeting OPSS Granular A or Granular B Type II, where required.

5.3.2 Bedrock Excavation

Localized removal of competent bedrock at this site, if required, could be carried out using hoe ramming techniques in conjunction with line drilling on close centres.

Line drilling on close centres could be used to reduce, not prevent, over break and under break of the bedrock excavation and to define the limit of excavation next to existing structures and services. For the bedrock at this site, it is suggested that allowance be made for line drilling 75 to 100 millimetre diameter holes on 200 to 300 millimetre centres. The vibration effects of hoe ramming are usually minor and localized.

Provided that good bedrock excavation techniques are used, the bedrock could be excavated using vertical side walls. Any loose rock should be scaled from the sides of the excavation.

If significant bedrock removal is required for the site development, blasting may be required. Guidelines on blasting are provided in Section 5.4.2.

5.3.3 Groundwater Pumping

The groundwater levels measured on February 9, 2022 range from about 0.3 to 4.0 metres below existing ground surface.

Any groundwater inflow into the excavations should be handled from within the excavations by pumping from filtered sumps. It is not expected that short term pumping during excavation will have a significant effect on nearby structures.

Suitable detention and filtration will be required before discharging the water to ground surface or sewer. Given the high groundwater table and the likelihood for multiple excavations open simultaneously for the construction of houses or building foundations, the water taking at this site

may exceed 400,000 litres per day and, therefore, a Category 3 Permit to Take Water (PTTW) will be required.

In order to reduce, not eliminate, the requirement for long term pumping from basement sump pumps it is recommended that the underside of footing elevations be set a minimum of 0.3 metres above the seasonally high groundwater level. Where possible, the perimeter foundation drainage should outlet by gravity to the storm sewer and the drains should be equipped with suitable backflow prevention. Further comments on underside of footing elevations could be provided as the design progresses.

5.3.4 Placement of Engineered Fill

Imported granular material (engineered fill) should be used to raise the grade in areas where the proposed founding level is above the level of the native soil, or where subexcavation of disturbed material is required below proposed founding level. The engineered fill should consist of granular material meeting Ontario Provincial Standard Specifications (OPSS) requirements for Granular B Type II and should be compacted in maximum 200 millimetre thick lifts to at least 95 percent of the standard Proctor maximum dry density. To allow spread of load beneath the footings, the engineered fill should extend horizontally at least 0.3 metres beyond the footings and then down and out from the edges of the footings at 1 horizontal to 1 vertical, or flatter. The excavations should be sized to accommodate this fill placement.

In areas where wet sandy soils are encountered at subgrade level, it may be necessary to place a non-woven geotextile meeting the requirements of OPSS 1860 Class I below the engineered fill and to statically compact the first lift of granular material to prevent subgrade disturbance. All seams in the geotextile should overlap at least 0.5 metres.

5.3.5 Spread Footing Design

The proposed houses could be founded on spread footings bearing on or within the native soil or bedrock, or on engineered fill above the native deposits or bedrock. The topsoil and fill material are not considered suitable for the support of the proposed houses, buildings or concrete floor slabs and should be removed from the proposed building areas.

Based on the results of the borehole investigation, the following allowable bearing pressures should be used to size the spread footing foundations:

Table 5.1 – Allowable Bearing Pressures for Foundations

Subgrade Material	Allowable Bearing Pressure for Foundations (kilopascals)
Silty clay, silty sand and sand	100
Glacial till	150

Subgrade Material	Allowable Bearing Pressure for Foundations (kilopascals)
Engineered fill material, over undisturbed, native deposits (minimum thickness of 0.6 metres of engineered fill)	150
Bedrock	250

It is pointed out that the deposits of silty sand near or below the groundwater level may become disturbed following excavation. If disturbance to the sandy deposits occurs, one solution would be to wait several days to allow the porewater pressures to dissipate. Alternatively, the groundwater level could be lowered in advance of excavation by pumping from sump pits, possibly combined with ditching around the perimeter of the excavations.

The native soils at this site are sensitive to construction operations, from ponded water and frost action. The construction operations should therefore be carried out in a manner that minimizes disturbance of the subgrade surfaces.

The post construction total and differential settlement of footings should be less than 25 and 15 millimetres, respectively, provided that all loose or disturbed soil is removed from the bearing surfaces and provided that any engineered fill material is compacted to the required density.

The foundation walls for the houses should be reinforced, both top and bottom, in areas where the footings transition from overburden to bedrock. The reinforcing steel should extend at least 3 metres on both sides of the transition zone.

As indicated above, the underside of footing level should be set a minimum of 0.3 metres above the seasonally high groundwater level.

5.3.6 Frost Protection of Foundations

All exterior footings should be provided with at least 1.5 metres of earth cover for frost protection purposes. Isolated, unheated exterior footings adjacent to surfaces which are cleaned of snow cover during the winter months should be provided with a minimum of 1.8 metres of earth cover. Alternatively, the required frost protection could be provided by means of a combination of earth cover and extruded polystyrene insulation. Further details regarding the insulation of foundations could be provided at the detailed design stage, if necessary.

5.3.7 Basement Foundation Wall Backfill and Drainage

In accordance with the Ontario Building Code, the following alternatives could be considered for drainage of the basement foundation walls:

- Damp proof the exterior of the foundation walls and backfill the walls with free draining, non-frost susceptible sand or sand and gravel such as that meeting OPSS requirements for Granular B Type I or II; or,
- Damp proof the exterior of the foundation walls and install an approved proprietary drainage system on the exterior of the foundation walls and backfill the walls with native material or imported soil.

A perforated plastic foundation drain with a surround of clear crushed stone should be installed on the exterior of the foundation walls at the underside of footing level. A nonwoven geotextile should be placed between the top of the clear stone and any sandy foundation wall backfill material to avoid loss of sand backfill into the voids in the clear stone (and possible post construction settlement of the ground around the houses). The top of the drain should be located below the bottom of the floor slab. The drain should outlet to a sump from which the water is pumped or should drain by gravity to the storm sewer system.

5.3.8 Garage Foundation and Pier Backfill

To avoid adfreeze between the unheated garage foundation walls and the wall backfill and possible jacking (heaving) of the foundation walls, the interior and exterior of the garage foundation walls should be backfilled with free draining, non-frost susceptible sand or sand and gravel such as that meeting OPSS requirements for Granular B Type I or II. The backfill within the garage should be compacted in maximum 300 millimetres thick lifts to at least 95 percent of the standard Proctor dry density value using suitable vibratory compaction equipment.

Alternatively, the interior of the garages could be filled with 19 millimetre clear crushed stone. A suitable nonwoven geotextile should be placed over the subgrade prior to the placement of clear stone to prevent ingress of fines into voids in the clear stone and possible settlement/cracking of the slab. Clear, crushed stone should be nominally compacted (at least 2 passes of a diesel plate compactor) in maximum 300 millimetre thick lifts to reduce the potential for post construction densification of the material.

The backfill against isolated (unheated) walls or piers should consist of free draining, non-frost susceptible material, such as sand or sand and gravel meeting OPSS Granular B Type I or II requirements. Other measures to prevent frost jacking of these foundation elements could be provided, if required.

5.3.9 Lateral Earth Pressures

Foundation walls that are backfilled with granular material such as that meeting OPSS Granular B Type I or II requirements should be designed to resist “at rest” earth pressures calculated using the following formula:

$$P_o = 0.5 K_o \gamma H^2$$

where;

- P_o : Static “At Rest” thrust (kilonewtons per metre);
- γ : Moist material unit weight (kilonewtons per cubic metre);
- K_o : “At Rest” earth pressure coefficient;
- H : Wall height (metre).

Seismic shaking can increase the forces on the retaining wall. The total “At Rest” thrust acting on the walls (P_{oe}) during a seismic event is composed of a static component (P_o) and a dynamic component (P_e), that is:

$$P_{oe} = P_o + P_e$$

The dynamic at rest thrust component (P_e), which acts only during seismic loading conditions, should be calculated using the following formula:

$$P_e = 0.5 (K_{oe} - K_o) \gamma H^2$$

where;

- P_e : Total “At Rest” thrust (kilonewtons per metre);
- γ : Moist material unit weight (kilonewtons per cubic metre);
- K_o : “At Rest” earth pressure coefficient
- K_{oe} : Dynamic “At Rest” earth pressure coefficient;
- H : Wall height (metre).

The static thrust component (P_o) acts at a point located $H/3$ above the base of the wall. During seismic shaking, the dynamic at rest thrust component (P_o) acts at a point located about $0.6H$ above the base of the wall.

For design purposes, the parameters provided in Table 5.2 can be used to calculate the thrust acting on the walls during static and seismic loading conditions.

Table 5.2 – Summary of Design Parameters (Building Foundation Walls)

Parameter	OPSS Granular B Type I	OPSS Granular B Type II
Material Unit Weight, γ (kilonewtons per cubic metre)	22	22

Parameter	OPSS Granular B Type I	OPSS Granular B Type II
Estimated Friction Angle (degrees)	34	38
“At Rest” Earth Pressure Coefficient, K_o , assuming horizontal backfill behind the structure	0.44	0.38
Dynamic “At Rest” Earth Pressure Coefficient, K_{oe} , assuming horizontal backfill behind the structure	0.34 ¹	0.29 ¹

Notes:

- 1) According to the 2015 National Building Code of Canada, the peak ground acceleration (PGA) for this site is 0.10 for Site Class C. The dynamic at rest earth pressure coefficient was calculated using the method suggested by Mononobe and Okabe, assuming a horizontal seismic coefficient, k_h , of 0.05 and assuming that the vertical seismic coefficient, k_v , is zero.

Heavy construction traffic should not be allowed to operate adjacent to foundation walls for the proposed houses and buildings (within about 2 metres horizontal) during construction, without the approval of the designers.

5.3.10 Basement Concrete Slab Support

To provide predictable settlement performance of the basement slab, all topsoil, fill material, disturbed soil, and other deleterious materials should be removed from the slab area.

The base for the floor slab should consist of 19 millimetre clear crushed stone. Allowance should be made for between 150 and 200 millimetres of granular base material.

The clear crushed stone should be nominally compacted in maximum 300 millimetre thick lifts with at least 2 passes of a diesel plate compactor. A suitable nonwoven geotextile should be placed over the subgrade prior to the placement of clear stone to prevent ingress of fines into voids in the clear stone and possible settlement/cracking of the slab.

Underfloor drainage should be provided below the floor slab. If clear crushed stone is used below the floor slab, underfloor drains are not considered essential provided that stub drains are installed to link any hydraulically isolated areas in the basement. The clear stone below the floor slab should be hydraulically connected to the sump pit or to the perimeter drain if drainage to the storm sewer system is possible.

Basement floor slabs should be constructed in accordance with guidelines provided in ACI 302.1R-04 “Guide for Concrete Floor and Slab Construction”.

A polyethylene vapour barrier should be installed below the basement floor slabs.

5.3.11 Swimming Pools

With the exception of shallow bedrock in some areas, we do not anticipate any geotechnical concerns with swimming pool construction in the residential development.

5.3.12 Seismic Site Classification and Liquefaction Potential

Based on the results of the standard penetration carried out as part of this investigation, it is recommended that seismic Site Class C be used for the design of residential structures in the residential development.

Also, based on the results of the standard penetration testing, in our opinion, the native overburden deposits, which are composed of silty sand, silty clay, and glacial till are not prone to liquefaction.

5.4 Site Services

5.4.1 Overburden Excavation

The overburden excavations for the site services will be carried out through topsoil, fill material, silty sand, and glacial till.

In the overburden, the excavation for flexible service pipes should be in accordance with Ontario Provincial Standard Drawing (OPSD) 802.010 for Type 3 Soil. The excavation for rigid service pipes should be in accordance with OPSD 802.031 for Type 3 soil.

The sides of the excavations within overburden soils should be sloped in accordance with the requirements in Ontario Regulation 213/91 under the Occupational Health and Safety Act. According to the Act, most of the soils at this site can be classified as Type 3 soils. Therefore, for design purposes, allowance should be made for 1 horizontal to 1 vertical, or flatter, excavation slopes.

Excavation of the native soils above the groundwater should not present any excavation constraints. In contrast, excavation in the native silty sand and sand below the groundwater level could present constraints. Groundwater inflow from the silty sand and sand deposits could cause sloughing of the sides of the excavation and disturbance to the soils at the bottom of the excavation. Flatter side slopes may be required if excavation is required below the groundwater level in sand and silty sand deposits.

As an alternative or where space constraints dictate, the service installations could be carried out within a tightly fitting, braced steel trench box, which is specifically designed for this purpose.

Based on our observations on site, groundwater inflow from the overburden deposits into the excavations should be controlled by pumping from filtered sumps within the excavations. It is not expected that short term pumping during excavation will have any significant affect on nearby structures and services.

5.4.2 Bedrock Excavation

In bedrock, the excavation for flexible service pipes should be in accordance with OPSD 802.013 for bedrock. The excavation for rigid service pipes should be in accordance with OPSD 802.033 for bedrock.

Localized removal of competent bedrock at this site could be carried out using (a) drill and blasting, (b) hoe ramming techniques in conjunction with line drilling on close centres or (c) a combination of both. Provided that good bedrock excavation techniques are used, the competent bedrock could be excavated using vertical side walls.

Any blasting should be carried out under the supervision of a blasting specialist engineer. As a guideline for blasting, the suggested peak vibration limits at the nearest structure or service are provided in Table 5.2.

Table 5.2 – Peak Vibration Limits

Frequency of Vibration (Hz)	Vibration Limits (millimetres/second)
<10	5
10 to 40	5 to 50 (interpolated)
>40	50

It is pointed out that these criteria, although conservative, were established to prevent damage to existing buildings and services that are in good condition; more stringent criteria may be required to prevent damage to freshly placed (uncured) concrete or vibration sensitive equipment or utilities. Monitoring of the blasting should be carried out to ensure that the blasting meets the limiting vibration criteria. Pre-construction condition surveys of nearby structures, water supply wells, and existing buried services are considered essential. The effects due to vibration from blasting can be controlled by limiting the size and amount of charge, using delayed detonation techniques, and the like. To reduce the effects of vibration on nearby services, we suggest that the separation distance between any blasting and existing underground services be at least 3 metres. Any bedrock removal within these limits could be carried out using hoe ramming techniques in conjunction with line drilling on close centres. It is noted that the cost of bedrock removal generally increases the closer the bedrock removal is to any existing structures or services.

As an alternative to blasting, bedrock removal could be carried out using large hydraulic excavation equipment in combination with hoe ramming. Line drilling on close centres could be used to reduce, not prevent, over break and under break of the bedrock excavation and to define the limit of excavation next to existing structures and services. For the bedrock at this site, it is suggested that allowance be made for line drilling 75 to 100 millimetre diameter holes on 200 to

300 millimetre centres. The vibration effects of hoe ramming are usually minor and localized. Monitoring of the hoe ramming could be carried out, at least initially, to measure the vibrations to ensure that they are below the acceptable threshold value.

Provided that good bedrock excavation techniques are used, the bedrock could be excavated using vertical side walls. Any loose rock should be scaled from the sides of the excavation.

The bedrock at this site has near horizontal bedding planes. Therefore, some over break of the bedrock should be expected. Bedrock over breaks will naturally occur along the bedding planes; as such, additional granular bedding material should be expected for the site services and additional granular fill/concrete should be expected for the house foundations.

5.4.3 Permit to Take Water (PTTW)

The groundwater levels measured on February 9, 2022 range from about 0.3 to 4.0 metres below existing ground surface.

It is expected that any groundwater inflow into the excavations can be handled from within the excavations by pumping from filtered sumps; although, it is noted that if significant bedrock removal or deep excavations are required (e.g. pump station or stormwater management pond), groundwater lowering in advance of construction may be required. It is not expected that short term pumping during excavation will have a significant effect on nearby structures.

Given the high groundwater table, proximity to the Tay River, anticipated excavation depths of four to five metres for the installation of municipal series and the likelihood for multiple excavations open simultaneously (i.e., multiple crews), the water taking at this site is expected to exceed 400,000 litres per day and, therefore, a Category 3 Permit to Take Water (PTTW) will be required. A hydrogeological investigation in support of a Category 3 PTTW is provided under a separate cover.

5.4.4 Bedding and Cover

The bedding and cover for the proposed utilities should consist of least 150 millimetres of OPSS Granular A backfill placed in accordance with the applicable OPSD for the type of underground utility installed. The use of 19 millimetre clear stone is not recommended as bedding or cover.

The native silty sand and silty clay deposits below the groundwater level are sensitive to disturbance. Allowance should be made for a subbedding composed of at least 300 millimetres of OPSS Granular B Type II where these materials are encountered at subgrade level below the pipe.

Bedding, subbedding and cover materials should be placed in lifts not exceeding 200 millimetres thick and compacted to at least 95 percent of standard Proctor density (ASTM D698).

5.4.5 Trench Backfill

In areas where the service trench will be located below or in close proximity to existing or future areas of hard surfacing (i.e., access roadways and parking), acceptable native materials should be used as backfill between the roadway subgrade level and the depth of seasonal frost penetration in order to reduce the potential for differential frost heaving between the area over the trench and the adjacent hard surfaced area. The depth of frost penetration in exposed areas can normally be taken as 1.8 metres below finished grade. Where native backfill is used, it should match the native materials exposed on the trench walls. Backfill below the zone of seasonal frost penetration could consist of either acceptable native material or imported granular material conforming to OPSS Granular B Type I.

It is anticipated that most of the inorganic overburden materials encountered during the subsurface investigation will be acceptable for reuse as trench backfill. Topsoil or other organic material should be wasted from the trench. If on-site blast rock is used as backfill within the service trench, it should be mostly 300 millimetres, or smaller, in size and should be well graded. To prevent ingress of fine material into voids in the blast rock, the upper surface of the blast rock should be covered with a thin layer of compacted, well graded crushed stone, such as OPSS Granular B Type II.

To minimize future settlement of the backfill and achieve an acceptable subgrade for the roadways, curbs, driveways, etc., the trench backfill should be compacted in maximum 300 millimetre thick lifts to at least 95 percent of the standard Proctor dry density value. Rock fill should be placed in maximum 500 millimetre thick lifts and compacted with a large drum roller, the haulage and spreading equipment, or a combination of both. The specified density for compaction of the backfill materials may be reduced where the trench backfill is not located below or in close proximity to existing or future areas of hard surfacing and/or structures, provided that some settlement above the trench is acceptable.

The silty sand and silty clay deposits may have water contents that are too high for adequate compaction. Furthermore, depending on the weather conditions at the time of construction, some wetting of materials could occur. As such, the specified densities may not be possible to achieve and, as a consequence, some settlement of these backfill materials should be expected. Consideration could be given to implementing one or a combination of the following measures to reduce post construction settlement above the trenches, depending on the weather conditions encountered during the construction:

- Allow the overburden materials to dry prior to compaction;
- Reuse any wet materials in the lower part of the trenches and make provision to defer final paving of surface course (i.e., the Superpave 12.5 asphaltic concrete) in the roadways for 3 months, or longer, to allow the trench backfill settlement to occur and thereby improve the final roadway appearance.

5.4.6 Seepage Barriers

The granular bedding in the service trench could act as a “French Drain”, which could promote groundwater lowering. As such, we suggest that seepage barriers be installed along the service trenches at strategic locations at a horizontal spacing of about 100 metres. The seepage barriers should begin at subgrade level and extend vertically through the granular pipe bedding and granular surround to within the native backfill materials, and horizontally across the full width of the service trench excavation. The seepage barriers could consist of 1.5 metre wide dykes of compacted weathered silty clay. The weathered silty clay should be compacted in maximum 300 millimetre thick lifts to at least 95 percent of the standard Proctor dry density value. The locations of the seepage barriers could be provided as the design progresses.

5.5 Internal Roadways

5.5.1 Subgrade Preparation

In preparation for roadway construction at this site, all surficial topsoil, fill material, and any soft, wet, disturbed, or deleterious materials should be removed from the proposed roadways. Any subexcavated areas could be filled with compacted earth borrow. Similarly, should it be necessary to raise the roadway grades at this site, material which meets OPSS specifications for Select Subgrade Material or Earth Borrow may be used. The select subgrade material or earth borrow should be placed in maximum 300 millimetre thick lifts and compacted to at least 95 percent of the standard Proctor maximum dry density value using vibratory compaction equipment. Prior to placing granular material for the roadways, the exposed subgrade should be heavily proof rolled under suitable (dry) conditions, and inspected and approved by geotechnical personnel. Any soft areas evident from the proof rolling should be subexcavated and replaced with suitable earth borrow approved by the geotechnical engineer.

The subgrade should be shaped and crowned to promote drainage of the roadway granular materials.

It is understood that the roadways within Phase 9 of the development have been stripped of topsoil and peat, and backfilled with blast rock fill.

5.5.2 Pavement Design

The following minimum pavement structure is suggested for local roadways at this site, assuming that the roadways will not be used as collector roads or bus routes:

- 90 millimetre thick layer of asphaltic concrete (40 millimetres of Superpave 12.5 Traffic Level B over 50 millimetres of Superpave 12.5 Traffic Level B); over
- 150 millimetre thick layer of base (OPSS Granular A); over
- 400 millimetre thick layer of subbase (OPSS Granular B Type II);

In the absence of detailed traffic data, the thickness of asphaltic concrete and OPSS Granular B Type II subbase should be increased for collector/arterial roadways and bus routes, as follows:

- 120 millimetre thick layer of asphaltic concrete (50 millimetres of Superpave 12.5 Traffic Level D over 70 millimetres of Superpave 19.0 Traffic Level D); over
- 150 millimetre thick layer of base (OPSS Granular A); over
- 600 millimetre thick layer of subbase (OPSS Granular B Type II);

If the rock fill is open graded, and a significant amount of voids are present at the surface of the rock fill, a non-woven geotextile should be placed between the rock fill and the Granular B Type II subbase layer to prevent loss of material into the rock fill.

5.5.3 Effects of Soil Disturbance

The above pavement structures assume that the roadway subgrade surface is prepared as described in this report. If the roadway subgrade surface is disturbed or wetted due to construction operations or precipitation, the granular thickness given above may not be adequate and it may be necessary to increase the thickness of the Granular B Type II subbase and/or to incorporate a woven geotextile separator between the roadway subgrade surface and the granular subbase material. The adequacy of the design pavement thickness should be assessed by geotechnical personnel at the time of construction. In our experience, a geotextile will likely be required in most cases where the subgrade consists of overburden, if the roadway construction is planned during the wet period of the year (such as the spring or fall).

Similarly, if the granular pavement materials are to be used by construction traffic, it may be necessary to increase the thickness of the Granular B Type II, install a woven geotextile separator between the roadway subgrade surface and the granular subbase material, or a combination of both, to prevent pumping and disturbance to the subbase material. The contractor should be made responsible for their construction access.

5.5.4 Granular Material Compaction

The pavement granular materials should be compacted in maximum 300 millimetre thick lifts to at least 99 percent of standard Proctor maximum dry density using suitable vibratory compaction equipment.

5.5.5 Asphaltic Cement

Performance graded PG 58-34 asphaltic cement is recommended for local roadways while performance graded PG 64-34 asphalt is recommended for collector/arterial roadways and bus routes.

5.5.6 Transition Treatments

In areas where the new pavement structure will abut existing pavements, the depths of the granular materials should taper up or down at 5 horizontal to 1 vertical, or flatter, to match the depths of the granular material(s) exposed in the existing pavement.

5.5.7 Pavement Drainage

Adequate drainage of the pavement granular materials and subgrade is important for the long term performance of the pavement at this site. It is suggested that storm sewer catch basins be equipped with 3 metre stub drains extending in at least 2 directions. The stub drains should be installed at the subgrade level. In any areas where ditches are used, it is suggested that the pavement granular material extend to the ditches. The bottom of the OPSS Granular B Type II should be at least 0.3 metres above the bottom of the ditch.

Further details on pavement drainage can be provided as the design progresses.

5.6 Corrosion of Buried Concrete and Steel

According to Canadian Standards Association (CSA) "Concrete Materials and Methods of Concrete Construction", the concentration of sulphate in the soil samples recovered from boreholes 22-212 and 22-226 can be classified as low. For low exposure conditions, any concrete that will be in contact with the native soil or groundwater could be batched with General Use (GU) type cement. The effects of freeze thaw in the presence of de-icing chemical (sodium chloride) near the buildings should be considered in selecting the air entrainment and the concrete mix proportions for any exposed concrete.

Based on the resistivity and pH of the soil samples tested the soil can be generally classified as non aggressive toward unprotected steel. It is noted that the corrosivity of the soil could vary throughout the year due to the application sodium chloride for de-icing.

6.0 ADDITIONAL CONSIDERATIONS

6.1 Winter Construction

Provision must be made to prevent freezing of any soil below the level of any footings, slabs or services. Freezing of the soil could result in heaving related damage.

Any service trenches should be opened for as short a time as practicable and the excavations should be carried out only in lengths which allow all of the construction operations, including backfilling, to be fully completed in one working day. The materials on the sides of the trenches should not be allowed to freeze. In addition, the backfill should be excavated, stored and replaced without being disturbed by frost or contaminated by snow or ice.

6.2 Effects of Construction Induced Vibration

Some of the construction operations (such as granular material compaction, excavation, hoe ramming, foundation construction etc.) will cause ground vibration on and off of the site. The vibrations will attenuate with distance from the source, but may be felt at nearby structures. Comments on preconstruction surveys are provided in Section 5.4.2.

6.3 Disposal of Excess Soil

It is noted that the professional services retained for this project include only the geotechnical aspects of the subsurface conditions at this site. The presence or implications of possible surface and/or subsurface contamination, including naturally occurring source of contamination, are outside the terms of reference for this report. A Phase One and Two Environmental Site Assessment will be provided in a separate report.

6.4 Design Review and Construction Observation

The details for the proposed construction were not available to us at the time of preparation of this report. It is recommended that the final design drawings be reviewed by the geotechnical engineer as the design progresses to ensure that the guidelines provided in this report have been interpreted as intended.

The engagement of the services of the geotechnical consultant during construction is recommended to confirm that the subsurface conditions throughout the proposed excavations do not materially differ from those given in the report and that the construction activities do not adversely affect the intent of the design. The subgrade surfaces the individual houses, residential buildings, site services and roadways should be inspected by experienced geotechnical personnel to ensure that suitable materials have been reached and properly prepared. The placing and compaction of earth fill and imported granular materials should be inspected to ensure that the materials used conform to the grading and compaction specifications. In accordance with Ontario Building Code requirements, full time compaction testing is required for engineered fill below buildings.

7.0 CLOSURE



We trust this report provides sufficient information for your present purposes. If you have any questions concerning this report, please do not hesitate to contact our office.



Alex Meacoe, P.Eng.
Senior Geotechnical Engineer



Brent Wiebe, P.Eng.
VP Operations - Ontario




LEGEND

BH/ PH/ HA # BOREHOLE/ PROBEHOLE/ HAND AUGERHOLE ID
 XX.XX GROUND SURFACE ELEVATION, IN METRES
 GEODETIC DATUM

- BOREHOLE (current investigation by GEMTEC)
- BOREHOLE (previous investigation by GEMTEC)
- PROBEHOLE (current investigation by GEMTEC)
- PROBEHOLE (previous investigation by GEMTEC)
- HAND AUGERHOLE (previous investigation by GEMTEC)
- HAND AUGER HOLE (previous investigation by GEMTEC, 2018)
- HAND AUGER HOLE (current investigation by GEMTEC)
- HAND AUGER HOLE (current investigation by GEMTEC, elevations are based on DEM (not surveyed data))
- MONITORING WELL (current investigation by GEMTEC)
- BEDROCK OUTCROPS OBSERVED

APPROXIMATE DEVELOPMENT BOUNDARY
 APPROXIMATE DEVELOPMENT BOUNDARY



DRAWING		BEDROCK CONTOUR PLAN	
CLIENT		CAIVAN (PERTH GC) LIMITED	
PROJECT		PROPOSED DEVELOPMENT PERTH GOLF COURSE 151 PETER STREET PERTH, ONTARIO	
DRAWN BY	S.L.	CHECKED BY	W.A.M.
PROJECT NO.	100737.002	REVISION NO.	3
DATE	FEBRUARY 2023	FIGURE NO.	FIGURE 1



N:\PROJECTS\100737\100737_002\DRAWING\1.DRAWING\100737_002_CONTOUR_R3_2023-02.DWG

GEMTEC
CONSULTING ENGINEERS
AND SCIENTISTS

32 Steacie Drive
Ottawa, ON, K2K 2A9
Tel: (613) 836-1422
www.gemtec.ca
ottawa@gemtec.ca




LEGEND

BH/ PH/ HA # — BOREHOLE/ PROBEHOLE/ HAND AUGERHOLE ID
 XX.XX — GROUND SURFACE ELEVATION, IN METRES GEODETIC DATUM

- BOREHOLE (current investigation by GEMTEC)
- BOREHOLE (previous investigation by GEMTEC)
- PROBEHOLE (current investigation by GEMTEC)
- PROBEHOLE (previous investigation by GEMTEC)
- HAND AUGERHOLE (previous investigation by GEMTEC)
- HAND AUGER HOLE (previous investigation by GEMTEC, 2018)
- HAND AUGER HOLE (current investigation by GEMTEC)
- HAND AUGER HOLE (current investigation by GEMTEC, elevations are based on DEM (not surveyed data))
- MONITORING WELL (current investigation by GEMTEC)
- BEDROCK OUTCROPS OBSERVED

APPROXIMATE DEVELOPMENT BOUNDARY
 BEDROCK CONTOUR (METRES, m)



DRAWING		BEDROCK CONTOUR PLAN	
CLIENT		CAIVAN (PERTH GC) LIMITED	
PROJECT		PROPOSED DEVELOPMENT PERTH GOLF COURSE 151 PETER STREET PERTH, ONTARIO	
DRAWN BY	S.L.	CHECKED BY	W.A.M.
PROJECT NO.	100737.002	REVISION NO.	3
DATE	FEBRUARY 2023	FIGURE NO.	FIGURE 2



N:\PROJECTS\100737\100737_002\DRAWING\1.DRAWING\100737_002_CONTOUR_R3_2023-02.DWG

GEMTEC
CONSULTING ENGINEERS AND SCIENTISTS

32 Steacie Drive
Ottawa, ON, K2K 2A9
Tel: (613) 836-1422
www.gemtec.ca
ottawa@gemtec.ca



LEGEND


BH/ PH/ HA # BOREHOLE/ PROBEHOLE/ HAND AUGERHOLE ID
 XX.XX GROUND SURFACE ELEVATION, IN METRES
 GEODEIC DATUM

- BOREHOLE (current investigation by GEMTEC)
- BOREHOLE (previous investigation by GEMTEC)
- PROBEHOLE (current investigation by GEMTEC)
- PROBEHOLE (previous investigation by GEMTEC)
- HAND AUGERHOLE (previous investigation by GEMTEC)
- HAND AUGER HOLE (previous investigation by GEMTEC, 2018)
- HAND AUGER HOLE (current investigation by GEMTEC)
- HAND AUGER HOLE (current investigation by GEMTEC, elevations are based on DEM (not surveyed data))
- MONITORING WELL (current investigation by GEMTEC)
- BEDROCK OUTCROPS OBSERVED

APPROXIMATE DEVELOPMENT BOUNDARY

WATER LEVEL CONTOUR (masl)

DRAWING		GROUNDWATER ELEVATION CONTOUR PLAN	
CLIENT		CAIVAN (PERTH GC) LIMITED	
PROJECT		PROPOSED DEVELOPMENT PERTH GOLF COURSE 151 PETER STREET PERTH, ONTARIO	
DRAWN BY	S.L.	CHECKED BY	W.A.M.
PROJECT NO.	100737.002	REVISION NO.	3
DATE	FEBRUARY 2023	FIGURE NO.	FIGURE 3



N:\PROJECTS\100737\100737_002\DRAWING\1.DRAWING\100737_002_CONTOUR_R3_2023-02.DWG

GEMTEC
CONSULTING ENGINEERS AND SCIENTISTS

32 Steacie Drive
Ottawa, ON, K2K 2A9
Tel: (613) 836-1422
www.gemtec.ca
ottawa@gemtec.ca



APPENDIX A

Record of Borehole Logs – Current Investigation
List of Abbreviations and Symbols
22-201 to 22-203, 22-205 to 22-216, and 22-218 to 22-230

RECORD OF BOREHOLE 22-201

CLIENT: Caivan Communities
 PROJECT: Proposed Residential Development, Perth Golf, 141 Peter Street, Perth, Ontario
 JOB#: 100737.002
 LOCATION: See Site Plan, Figure 1

SHEET: 1 OF 1
 DATUM: CGVD28
 BORING DATE: Jan 18 2022

DEPTH SCALE METRES	BORING METHOD	SOIL PROFILE		SAMPLES				PENETRATION RESISTANCE (N), BLOWS/0.3m		SHEAR STRENGTH (Cu), kPA		ADDITIONAL LAB. TESTING	PIEZOMETER OR STANDPIPE INSTALLATION	
		DESCRIPTION	STRATA PLOT	ELEV. DEPTH (m)	NUMBER	TYPE	RECOVERY, mm	BLOWS/0.3m	▲ DYNAMIC PENETRATION RESISTANCE, BLOWS/0.3m	● PENETRATION RESISTANCE (N), BLOWS/0.3m	+ NATURAL ⊕ REMOULDED			WATER CONTENT, % Wp — W — Wl
0	Power Auger Hollow Stem Auger (210mm OD)	Ground Surface		136.00										
		TOPSOIL		0.10										
		Loose, brown SILTY SAND			1	SS	150	5		●	○			
1		Very loose to compact, grey brown SILTY SAND, some gravel, with cobbles and boulders (GLACIAL TILL)		135.24 0.76										
					2	SS	305	2		●	○			
2					3	SS	280	18		○	●			
					4	SS	255	16		○	●			
3		Compact to very dense, grey brown to grey SILTY SAND, some gravel, with cobbles and boulders (GLACIAL TILL)		133.10 2.90										
4	Diamond Rotary Core HQ (89mm OD)													
5				5	SS	150	>50 for 100mm							
6				6	SS	125	>50 for 100mm							
7				7	SS	230	>50 for 180mm							
7		Slightly weathered to fresh, fine grained, medium strong, greenish grey to pinkish grey Precambrian BEDROCK												
			8	RC			TCR = 98%; SCR = 89%; RQD = 89%							
8		End of Borehole												
9														
10														

GROUNDWATER OBSERVATIONS		
DATE	DEPTH (m)	ELEV. (m)
22/02/09	0.9	▽ 135.1

GEO - BOREHOLE LOG 100737.002 GINT - BOREHOLE LOGS.GPJ GEMTEC 2018.GDT 12/14/22





LOGGED: CS
 CHECKED: WAM

RECORD OF BOREHOLE 22-202

CLIENT: Caivan Communities
 PROJECT: Proposed Residential Development, Perth Golf, 141 Peter Street, Perth, Ontario
 JOB#: 100737.002
 LOCATION: See Site Plan, Figure 1

SHEET: 1 OF 1
 DATUM: CGVD28
 BORING DATE: Jan 14 2022



DEPTH SCALE METRES	BORING METHOD	SOIL PROFILE		SAMPLES				PENETRATION RESISTANCE (N), BLOWS/0.3m		SHEAR STRENGTH (Cu), kPA		ADDITIONAL LAB. TESTING	PIEZOMETER OR STANDPIPE INSTALLATION
		DESCRIPTION	STRATA PLOT	ELEV. DEPTH (m)	NUMBER	TYPE	RECOVERY, mm	BLOWS/0.3m	▲ DYNAMIC PENETRATION RESISTANCE, BLOWS/0.3m	● PENETRATION RESISTANCE (N), BLOWS/0.3m	+ NATURAL ⊕ REMOULDED		
0		Ground Surface TOPSOIL		135.65									
0.10		Very loose, brown SILTY SAND, some gravel, with cobbles and boulders (GLACIAL TILL)			1	SS	150	2	●				
1					2	SS	255	2	●	○			
1.52		Compact to very dense, grey SILTY SAND, some clay, trace gravel, with cobbles and boulders (GLACIAL TILL)		134.13									
2					3	SS	455	18	○	●			
2.5					4	SS	75	>50 for 130 mm					
3					5	SS	255	>50 for 130 mm					
4	Power Auger Hollow Stem Auger (210mm OD)				6	SS	280	>50 for 100 mm					
5					7	SS	150	>50 for 100 mm					
6					8	SS	75	>50 for 150 mm					
7					9	SS	205	>50 for 75 mm					
7.49				128.16	10	SS	180	>50 for 75 mm					
8		End of Borehole Auger Refusal		7.49									

GEO - BOREHOLE LOG, 100737.002, GINT - BOREHOLE LOGS.GPJ, GEMTEC, 2018, GDT, 12/14/22


RECORD OF BOREHOLE 22-203

CLIENT: Caivan Communities
 PROJECT: Proposed Residential Development, Perth Golf, 141 Peter Street, Perth, Ontario
 JOB#: 100737.002
 LOCATION: See Site Plan, Figure 1

SHEET: 1 OF 1
 DATUM: CGVD28
 BORING DATE: Jan 18 2022

DEPTH SCALE METRES	BORING METHOD	SOIL PROFILE			SAMPLES				PENETRATION RESISTANCE (N), BLOWS/0.3m		SHEAR STRENGTH (Cu), kPA		ADDITIONAL LAB. TESTING	PIEZOMETER OR STANDPIPE INSTALLATION
		DESCRIPTION	STRATA PLOT	ELEV.	NUMBER	TYPE	RECOVERY, mm	BLOWS/0.3m	DYNAMIC PENETRATION RESISTANCE, BLOWS/0.3m		WATER CONTENT, %			
				DEPTH (m)					▲	●	W _p	W		
0	Power Auger Auger (210mm OD)	Ground Surface		135.91										
		TOPSOIL		0.08										
		Loose to very dense, brown SILTY SAND, some gravel, with cobbles and boulders (GLACIAL TILL)			1	SS	330	7	●					
1	Hollow Stem Auger Refusal	End of Borehole Auger Refusal		134.92 0.99										
						2	SS	75	>50 for 75 mm.					
2														
3														
4														
5														
6														
7														
8														
9														
10														

Native backfill




GEO - BOREHOLE LOG 100737.002_GINT_BOREHOLE LOGS.GPJ GEMTEC 2018.GDT 12/14/22

RECORD OF BOREHOLE 22-203A

CLIENT: Caivan Communities
 PROJECT: Proposed Residential Development, Perth Golf, 141 Peter Street, Perth, Ontario
 JOB#: 100737.002
 LOCATION: See Site Plan, Figure 1

SHEET: 1 OF 1
 DATUM: CGVD28
 BORING DATE: Jan 20 2022

DEPTH SCALE METRES	BORING METHOD	SOIL PROFILE		SAMPLES				PENETRATION RESISTANCE (N), BLOWS/0.3m		SHEAR STRENGTH (Cu), kPA		ADDITIONAL LAB. TESTING	PIEZOMETER OR STANDPIPE INSTALLATION
		DESCRIPTION	STRATA PLOT	ELEV. DEPTH (m)	NUMBER	TYPE	RECOVERY, mm	BLOWS/0.3m	▲ DYNAMIC PENETRATION RESISTANCE, BLOWS/0.3m	● PENETRATION RESISTANCE (N), BLOWS/0.3m	+ NATURAL ⊕ REMOULDED		
0	Wash Casing H/W (114mm OD)	Ground Surface		135.91									
		TOPSOIL		0.08									
		Brown SILTY SAND, some gravel, with cobbles and boulders (GLACIAL TILL)											
1	Diamond Rotary Core HQ (89mm OD)	Slightly weathered to fresh, fine grained, very strong, greenish grey to pink Precambrian BEDROCK		135.15	1	RC		TCR = 100%; SCR = 37%; RQD = 0%					
2					2	RC		TCR = 100%; SCR = 91%; RQD = 91%					
3					3	RC		TCR = 100%; SCR = 87%; RQD = 95%					
4					4	RC		TCR = 98%; SCR = 60%; RQD = 60%					
5					5	RC		TCR = 100%; SCR = 100%; RQD = 88%					
6		End of Borehole		129.69									
				6.22									
7													
8													
9													
10													



GROUNDWATER OBSERVATIONS		
DATE	DEPTH (m)	ELEV. (m)
22/02/09	1.2	▼ 134.7

GEO - BOREHOLE LOG - 100737.002 - GINT - BOREHOLE LOGS.GPJ - GEMTEC 2018.GDT - 12/14/22




LOGGED: BWW
 CHECKED: WAM

RECORD OF BOREHOLE 22-205

CLIENT: Caivan Communities
 PROJECT: Proposed Residential Development, Perth Golf, 141 Peter Street, Perth, Ontario
 JOB#: 100737.002
 LOCATION: See Site Plan, Figure 1

SHEET: 1 OF 1
 DATUM: CGVD28
 BORING DATE: Jan 10 2022

DEPTH SCALE METRES	BORING METHOD	SOIL PROFILE		SAMPLES				PENETRATION RESISTANCE (N), BLOWS/0.3m		SHEAR STRENGTH (Cu), kPA		ADDITIONAL LAB. TESTING	PIEZOMETER OR STANDPIPE INSTALLATION
		DESCRIPTION	STRATA PLOT	ELEV. DEPTH (m)	NUMBER	TYPE	RECOVERY, mm	BLOWS/0.3m	▲ DYNAMIC PENETRATION RESISTANCE, BLOWS/0.3m	● PENETRATION RESISTANCE (N), BLOWS/0.3m	+ NATURAL ⊕ REMOULDED		
0	Power Auger Hollow Stem Auger (210mm OD)	Ground Surface		135.32									
		TOPSOIL		0.10									
		Stiff to very stiff, grey brown SILTY CLAY (WEATHERED CRUST)			1	SS	355	4	●				
1		Compact to very dense, grey SILTY SAND, some gravel, with cobbles and boulders (GLACIAL TILL)		134.56									
				0.76									
					2	SS	100	20	●				
					3	SS	510	20	●				
					4	SS	405	26	●				
					5	SS	455	81				●	
2				6	SS	455	84				●		
3				7	SS	455	77				●		
4				8	SS	510	82				●		
5				9	SS	50	>50 for 50 mm						
6		End of Borehole Auger Refusal		129.17									
				6.15									
7													
8													
9													
10													



GROUNDWATER OBSERVATIONS		
DATE	DEPTH (m)	ELEV. (m)
22/02/09	0.5	134.9

GEO - BOREHOLE LOG - 100737.002 - GINT - BOREHOLE LOGS.GPJ - GEMTEC 2018.GDT - 12/14/22

RECORD OF BOREHOLE 22-206

CLIENT: Caivan Communities
 PROJECT: Proposed Residential Development, Perth Golf, 141 Peter Street, Perth, Ontario
 JOB#: 100737.002
 LOCATION: See Site Plan, Figure 1

SHEET: 1 OF 1
 DATUM: CGVD28
 BORING DATE: Jan 20 2022

DEPTH SCALE METRES	BORING METHOD	SOIL PROFILE		SAMPLES				PENETRATION RESISTANCE (N), BLOWS/0.3m		SHEAR STRENGTH (Cu), kPA		ADDITIONAL LAB. TESTING	PIEZOMETER OR STANDPIPE INSTALLATION	
		DESCRIPTION	STRATA PLOT	ELEV. DEPTH (m)	NUMBER	TYPE	RECOVERY, mm	BLOWS/0.3m	▲ DYNAMIC PENETRATION RESISTANCE, BLOWS/0.3m	● PENETRATION RESISTANCE (N), BLOWS/0.3m	⊕ NATURAL ⊕ REMOULDED			WATER CONTENT, % W _p W W _L
0	Power Auger Hollow Stem Auger (210mm OD)	Ground Surface		136.26										
		Very loose to loose, dark brown to brown silty sand, some gravel (FILL MATERIAL)		1	SS	330	4	●						
1		Loose to compact, grey brown SILTY SAND, trace to some gravel, with cobbles and boulders (GLACIAL TILL)		2	SS	455	5	●						
2				3	SS	355	10	●						
3	Wash Casing HW (114mm OD)	Very dense, grey brown to grey SILTY SAND, some gravel, with cobbles and boulders (GLACIAL TILL)		133.97 2.29	4	SS	610	57	●					
4			5	SS	405	>50 for 130 mm								
5			6	RC	150	DD								
			7	SS	50	>50 for 75 mm								
			8	RC	255	DD								
			9	RC	150	DD								
			10	RC	75	DD								
6			11	SS	125	>50 for 50 mm								
7			12	RC	75	DD								
8			13	SS	150	>50 for 75 mm								
8		End of Borehole Sampler Refusal		128.28 7.98										
9														
10														

Native backfill

GEO - BOREHOLE LOG - 100737.002 - GINT - BOREHOLE LOGS.GPJ - GEMTEC 2018.GDT - 12/14/22



LOGGED: BWW/CS
 CHECKED: WAM

RECORD OF BOREHOLE 22-207

CLIENT: Caivan Communities
 PROJECT: Proposed Residential Development, Perth Golf, 141 Peter Street, Perth, Ontario
 JOB#: 100737.002
 LOCATION: See Site Plan, Figure 1

SHEET: 1 OF 1
 DATUM: CGVD28
 BORING DATE: Jan 12 2022

DEPTH SCALE METRES	BORING METHOD	SOIL PROFILE			SAMPLES				PENETRATION RESISTANCE (N), BLOWS/0.3m		SHEAR STRENGTH (Cu), kPA		ADDITIONAL LAB. TESTING	PIEZOMETER OR STANDPIPE INSTALLATION
		DESCRIPTION	STRATA PLOT	ELEV. DEPTH (m)	NUMBER	TYPE	RECOVERY, mm	BLOWS/0.3m	●	▲	+	⊕		
WATER CONTENT, %														
								10 20 30 40 50 60 70 80 90		Wp W Wl				
0	Power Auger Hollow Stem Auger (210mm OD)	Ground Surface		135.04									MH	Native backfill
		TOPSOIL		134.91										
		Stiff to very stiff, grey brown SILTY CLAY (WEATHERED CRUST)		0.13	1	SS	100	9	●					
1		Loose to very dense, brown SILTY SAND, some clay and gravel, with cobbles and boulders (GLACIAL TILL)		0.76	2	SS	510	8	●	○				
2					3	SS	455	13	●					
3				4	SS	50	10	●	○					
3				5	SS	180	>50 for 50 mm	○						
3.35		End of Borehole Auger Refusal		131.69										
4				3.35										
5														
6														
7														
8														
9														
10														


GEO - BOREHOLE LOG, 100737.002, GINT, BOREHOLE LOGS.GPJ, GEMTEC, 2018, GDT, 12/14/22

RECORD OF BOREHOLE 22-208

CLIENT: Caivan Communities
 PROJECT: Proposed Residential Development, Perth Golf, 141 Peter Street, Perth, Ontario
 JOB#: 100737.002
 LOCATION: See Site Plan, Figure 1

SHEET: 1 OF 1
 DATUM: CGVD28
 BORING DATE: Jan 12 2022

DEPTH SCALE METRES	BORING METHOD	SOIL PROFILE		SAMPLES				PENETRATION RESISTANCE (N), BLOWS/0.3m		SHEAR STRENGTH (Cu), kPA		ADDITIONAL LAB. TESTING	PIEZOMETER OR STANDPIPE INSTALLATION
		DESCRIPTION	STRATA PLOT	ELEV. DEPTH (m)	NUMBER	TYPE	RECOVERY, mm	BLOWS/0.3m	▲ DYNAMIC PENETRATION RESISTANCE, BLOWS/0.3m	●	WATER CONTENT, % W _p — W — W _L		
0	Power/Auger Hollow Stem Auger (210mm OD)	Ground Surface		137.48									
		TOPSOIL		0.08	1	SS	100	>50					
	Diamond Rotary Core HQ (89mm OD)	Very dense, brown SILTY SAND, with organics		137.18									
		Slightly weathered to fresh, fine grained, very strong, pinkish grey Precambrian BEDROCK		0.30									
1					2	RC		TCR = 100%; SCR = 63%; RQD = 67%					
2					3	RC		TCR = 95%; SCR = 43%; RQD = 59%					
3					4	RC		TCR = 100%; SCR = 86%; RQD = 86%					
4				5	RC		TCR = 100%; SCR = 96%; RQD = 96%						
5													
6		End of Borehole		131.41									
				6.07									
7													
8													
9													
10													





GROUNDWATER OBSERVATIONS		
DATE	DEPTH (m)	ELEV. (m)
22/02/09	2.7	134.8

GEO - BOREHOLE LOG 100737.002 GINT - BOREHOLE LOGS.GPJ GEMTEC 2018.GDT 12/14/22


RECORD OF BOREHOLE 22-209

CLIENT: Caivan Communities
 PROJECT: Proposed Residential Development, Perth Golf, 141 Peter Street, Perth, Ontario
 JOB#: 100737.002
 LOCATION: See Site Plan, Figure 1

SHEET: 1 OF 1
 DATUM: CGVD28
 BORING DATE: Jan 14 2022

DEPTH SCALE METRES	BORING METHOD	SOIL PROFILE			SAMPLES				PENETRATION RESISTANCE (N), BLOWS/0.3m		SHEAR STRENGTH (Cu), kPA		ADDITIONAL LAB. TESTING	PIEZOMETER OR STANDPIPE INSTALLATION
		DESCRIPTION	STRATA PLOT	ELEV. DEPTH (m)	NUMBER	TYPE	RECOVERY, mm	BLOWS/0.3m	●	▲	+	⊕		
				WATER CONTENT, %										
				W _p W W _L										
0	Power Auger Hollow Stem Auger (210mm OD)	Ground Surface		137.24										
		TOPSOIL			137.09									
		Loose to compact, brown SILTY SAND, trace to some gravel, with cobbles and boulders (GLACIAL TILL)		0.15	1	SS	355	8	●					
1					2	SS	330	12	●					
		End of Borehole Auger Refusal		135.97										
				1.27										
2														
3														
4														
5														
6														
7														
8														
9														
10														

Native backfill




GEO - BOREHOLE LOG 100737.002 GINT - BOREHOLE LOGS.GPJ GEMTEC 2018.GDT 12/14/22


RECORD OF BOREHOLE 22-210

CLIENT: Caivan Communities
 PROJECT: Proposed Residential Development, Perth Golf, 141 Peter Street, Perth, Ontario
 JOB#: 100737.002
 LOCATION: See Site Plan, Figure 1

SHEET: 1 OF 1
 DATUM: CGVD28
 BORING DATE: Jan 14 2022

DEPTH SCALE METRES	BORING METHOD	SOIL PROFILE			SAMPLES				● PENETRATION RESISTANCE (N), BLOWS/0.3m ▲ DYNAMIC PENETRATION RESISTANCE, BLOWS/0.3m	SHEAR STRENGTH (Cu), kPA		ADDITIONAL LAB. TESTING	PIEZOMETER OR STANDPIPE INSTALLATION	
		DESCRIPTION	STRATA PLOT	ELEV. DEPTH (m)	NUMBER	TYPE	RECOVERY, mm	BLOWS/0.3m		WATER CONTENT, %				
				W _p					W _L					
0	Power Auger Hollow Stem Auger (210mm OD)	Ground Surface		135.67										
		TOPSOIL		0.10										
		Very loose, brown SILTY SAND, trace to some gravel, with cobbles and boulders (GLACIAL TILL)				1	SS	150	3	●				
1						2	SS	125	3	●				
2						3	SS	355	2	●				
3					4	SS	405	1	●					
				132.47	5	SS	50	>50 for 100 mm						
		End of Borehole Auger Refusal		3.20										
4														
5														
6														
7														
8														
9														
10														

Native backfill





GEO - BOREHOLE LOG - 100737.002_GINT - BOREHOLE LOGS.GPJ_GEMTEC.2018.GDT_12/14/22

RECORD OF BOREHOLE 22-211

CLIENT: Caivan Communities
 PROJECT: Proposed Residential Development, Perth Golf, 141 Peter Street, Perth, Ontario
 JOB#: 100737.002
 LOCATION: See Site Plan, Figure 1

SHEET: 1 OF 1
 DATUM: CGVD28
 BORING DATE: Jan 12 2022




DEPTH SCALE METRES	BORING METHOD	SOIL PROFILE			SAMPLES				● PENETRATION RESISTANCE (N), BLOWS/0.3m ▲ DYNAMIC PENETRATION RESISTANCE, BLOWS/0.3m	SHEAR STRENGTH (Cu), kPA + NATURAL ⊕ REMOULDED WATER CONTENT, % W _p — W — W _L	ADDITIONAL LAB. TESTING	PIEZOMETER OR STANDPIPE INSTALLATION
		DESCRIPTION	STRATA PLOT	ELEV. DEPTH (m)	NUMBER	TYPE	RECOVERY, mm	BLOWS/0.3m				
0	Power Auger	Ground Surface		134.84								
		TOPSOIL		134.71 0.13								
	Hollow Stem Auger (210mm OD)	Very loose to very dense, brown SILTY SAND, some gravel, with cobbles and boulders (GLACIAL TILL)			1	SS	125	2	●			
1		End of Borehole Auger Refusal		133.93 0.91		2	SS	100	>50 for 150 mm			
2												
3												
4												
5												
6												
7												
8												
9												
10												

GEO - BOREHOLE LOG 100737.002_GINT_BOREHOLE LOGS.GPJ GEMTEC 2018.GDT 12/14/22


RECORD OF BOREHOLE 22-212

CLIENT: Caivan Communities
 PROJECT: Proposed Residential Development, Perth Golf, 141 Peter Street, Perth, Ontario
 JOB#: 100737.002
 LOCATION: See Site Plan, Figure 1

SHEET: 1 OF 1
 DATUM: CGVD28
 BORING DATE: Jan 11 2022

DEPTH SCALE METRES	BORING METHOD	SOIL PROFILE			SAMPLES				PENETRATION RESISTANCE (N), BLOWS/0.3m		SHEAR STRENGTH (Cu), kPA		ADDITIONAL LAB. TESTING	PIEZOMETER OR STANDPIPE INSTALLATION		
		DESCRIPTION	STRATA PLOT	ELEV. DEPTH (m)	NUMBER	TYPE	RECOVERY, mm	BLOWS/0.3m	▲ DYNAMIC PENETRATION RESISTANCE, BLOWS/0.3m	● PENETRATION RESISTANCE (N), BLOWS/0.3m	+ NATURAL ⊕ REMOULDED	WATER CONTENT, % W _p W W _L				
0	Power Auger Hollow Stem Auger (210mm OD)	Ground Surface		136.57												
		TOPSOIL		0.08												
		Very loose, brown SILTY SAND, some gravel, with cobbles and boulders (GLACIAL TILL)		135.96	1	SS	430	3	●							
1		Dense, brown to grey SILTY SAND, some gravel, with cobbles and boulders (GLACIAL TILL)		135.96 0.61												
					2	SS	535	34		●						
2					3	SS	510	45		●						
		End of Borehole Auger Refusal		134.61 1.96												
3																
4																
5																
6																
7																
8																
9																
10																

Native backfill





GEO - BOREHOLE LOG 100737.002_GINT_BOREHOLE LOGS.GPJ GEMTEC 2018.GDT 12/14/22


RECORD OF BOREHOLE 22-213

CLIENT: Caivan Communities
 PROJECT: Proposed Residential Development, Perth Golf, 141 Peter Street, Perth, Ontario
 JOB#: 100737.002
 LOCATION: See Site Plan, Figure 1

SHEET: 1 OF 1
 DATUM: CGVD28
 BORING DATE: Jan 11 2022

DEPTH SCALE METRES	BORING METHOD	SOIL PROFILE			SAMPLES				● PENETRATION RESISTANCE (N), BLOWS/0.3m ▲ DYNAMIC PENETRATION RESISTANCE, BLOWS/0.3m	SHEAR STRENGTH (Cu), kPA		ADDITIONAL LAB. TESTING	PIEZOMETER OR STANDPIPE INSTALLATION
		DESCRIPTION	STRATA PLOT	ELEV. DEPTH (m)	NUMBER	TYPE	RECOVERY, mm	BLOWS/0.3m		+ NATURAL ⊕ REMOULDED	WATER CONTENT, % W _p — W — W _L		
0	Power Auger Hollow Stem Auger (210mm OD)	Ground Surface		137.20									
		TOPSOIL		0.10									
		Loose to very dense, brown SILTY SAND, some gravel, with cobbles and boulders (GLACIAL TILL)											
1					1	SS	305	8	●				
2					2	SS	50	6	●				
3					3	SS	330	>50 for 75 mm					
2		End of Borehole Auger Refusal		134.99 2.21									
3													
4													
5													
6													
7													
8													
9													
10													

Native backfill




GEO - BOREHOLE LOG, 100737.002, GINT - BOREHOLE LOGS.GPJ, GEMTEC, 2018, GDT, 12/14/22

RECORD OF BOREHOLE 22-214

CLIENT: Caivan Communities
 PROJECT: Proposed Residential Development, Perth Golf, 141 Peter Street, Perth, Ontario
 JOB#: 100737.002
 LOCATION: See Site Plan, Figure 1

SHEET: 1 OF 1
 DATUM: CGVD28
 BORING DATE: Jan 5 2022

DEPTH SCALE METRES	BORING METHOD	SOIL PROFILE		SAMPLES				PENETRATION RESISTANCE (N), BLOWS/0.3m		SHEAR STRENGTH (Cu), kPA		ADDITIONAL LAB. TESTING	PIEZOMETER OR STANDPIPE INSTALLATION
		DESCRIPTION	STRATA PLOT	ELEV. DEPTH (m)	NUMBER	TYPE	RECOVERY, mm	BLOWS/0.3m	▲ DYNAMIC PENETRATION RESISTANCE, BLOWS/0.3m	● PENETRATION RESISTANCE (N), BLOWS/0.3m	⊕ NATURAL ⊕ REMOULDED		
0	Power Auger Hollow Stem Auger (210mm OD)	Ground Surface		137.92									
		TOPSOIL		0.08									
		Brown SILTY SAND			1	SS	480	8	●				
1		Loose, grey brown to grey SILTY SAND, some gravel, with cobbles and boulders (GLACIAL TILL)		0.76	2	SS	305	7	● ○				
					3	SS	430	9	●				
2		Compact to very dense, grey brown to grey SILTY SAND, some gravel, with cobbles and boulders (GLACIAL TILL)		2.29	4	SS	455	29	○ ●				
					5	SS	280	59		●			
3	Diamond Rotary Core HQ (89mm OD)	Slightly weathered to fresh, fine grained, very strong, red to grey Precambrian BEDROCK		4.65	6	SS	535	68	○ ●				
					7	SS	180	>50 for 50 mm					
5					8	SS	TCR = 100%; SCR = 84%; RQD = 68%						
6					9	SS	TCR = 84%; SCR = 64%; RQD = 75%						
7		End of Borehole		6.96									



GROUNDWATER OBSERVATIONS		
DATE	DEPTH (m)	ELEV. (m)
22/02/09	2.0	▽ 136.0

GEO - BOREHOLE LOG 100737.002_GINT_BOREHOLE LOGS.GPJ GEMTEC 2018.GDT 12/14/22




LOGGED: CS
 CHECKED: WAM

RECORD OF BOREHOLE 22-214A

CLIENT: Caivan Communities
 PROJECT: Proposed Residential Development, Perth Golf, 141 Peter Street, Perth, Ontario
 JOB#: 100737.002
 LOCATION: See Site Plan, Figure 1

SHEET: 1 OF 1
 DATUM: CGVD28
 BORING DATE: Jan 6 2022

DEPTH SCALE METRES	BORING METHOD	SOIL PROFILE			SAMPLES				PENETRATION RESISTANCE (N), BLOWS/0.3m		SHEAR STRENGTH (Cu), kPA		ADDITIONAL LAB. TESTING	PIEZOMETER OR STANDPIPE INSTALLATION
		DESCRIPTION	STRATA PLOT	ELEV.	NUMBER	TYPE	RECOVERY, mm	BLOWS/0.3m	DYNAMIC PENETRATION RESISTANCE, BLOWS/0.3m		WATER CONTENT, %			
				DEPTH (m)					10	20	30	40		
0	Power Auger Hollow Stem Auger (210mm OD)	Ground Surface		137.80										
		TOPSOIL		0.08										
		Brown SILTY SAND			137.04	1	SS	150	-					
1		Grey brown to grey SILTY SAND, some gravel, with cobbles and boulders (GLACIAL TILL)			135.59	2	SS	455	-					
2				2.21	3	SS	305	-						
3		End of Borehole Auger Refusal												
4														
5														
6														
7														
8														
9														
10														



Native backfill

GEO - BOREHOLE LOG - 100737.002 - GINT - BOREHOLE LOGS.GPJ - GEMTEC, 2018.GDT - 12/14/22


RECORD OF BOREHOLE 22-215

CLIENT: Caivan Communities
 PROJECT: Proposed Residential Development, Perth Golf, 141 Peter Street, Perth, Ontario
 JOB#: 100737.002
 LOCATION: See Site Plan, Figure 1

SHEET: 1 OF 1
 DATUM: CGVD28
 BORING DATE: Jan 6 2022

DEPTH SCALE METRES	BORING METHOD	SOIL PROFILE			SAMPLES				PENETRATION RESISTANCE (N), BLOWS/0.3m		SHEAR STRENGTH (Cu), kPA		ADDITIONAL LAB. TESTING	PIEZOMETER OR STANDPIPE INSTALLATION
		DESCRIPTION	STRATA PLOT	ELEV. DEPTH (m)	NUMBER	TYPE	RECOVERY, mm	BLOWS/0.3m	▲ DYNAMIC PENETRATION RESISTANCE, BLOWS/0.3m	● PENETRATION RESISTANCE (N), BLOWS/0.3m	+ NATURAL ⊕ REMOULDED	WATER CONTENT, % W _p — W — W _L		
0	Power Auger Hollow Stem Auger (108mm OD)	Ground Surface		135.25										
		TOPSOIL		0.05										
		Stiff to very stiff, grey brown SILTY CLAY (WEATHERED CRUST)		134.64	1	SS	230	4	●					
		Very loose, brown SILTY SAND, some gravel, with cobbles and boulders (GLACIAL TILL)		0.61	2	SS	405	3	●					
1		Dense to very dense, some gravel, with cobbles and boulders (GLACIAL TILL)		133.88										
			1.37	3	SS	455	35	●						
2		End of Borehole Auger Refusal		132.81	4	SS	75	>50 for 150 mm						
			2.44											
3														
4														
5														
6														
7														
8														
9														
10														

Native backfill






GEO - BOREHOLE LOG - 100737.002 - GINT - BOREHOLE LOGS.GPJ - GEMTEC 2018.GDT - 12/14/22


RECORD OF BOREHOLE 22-216

CLIENT: Caivan Communities
 PROJECT: Proposed Residential Development, Perth Golf, 141 Peter Street, Perth, Ontario
 JOB#: 100737.002
 LOCATION: See Site Plan, Figure 1

SHEET: 1 OF 1
 DATUM: CGVD28
 BORING DATE: Jan 6 2022

DEPTH SCALE METRES	BORING METHOD	SOIL PROFILE			SAMPLES				PENETRATION RESISTANCE (N), BLOWS/0.3m		SHEAR STRENGTH (Cu), kPA		ADDITIONAL LAB. TESTING	PIEZOMETER OR STANDPIPE INSTALLATION	
		DESCRIPTION	STRATA PLOT	ELEV. DEPTH (m)	NUMBER	TYPE	RECOVERY, mm	BLOWS/0.3m	▲ DYNAMIC PENETRATION RESISTANCE, BLOWS/0.3m	●	WATER CONTENT, % W _p — W — W _L				
0	Power Auger (210mm OD)	Ground Surface		134.58											
		TOPSOIL		0.03											
		Stiff to very stiff, grey brown SILTY CLAY (WEATHERED CRUST)		133.97	1	SS	405	3	●						
		Very loose, brown SILTY SAND, some gravel, with cobbles and boulders (GLACIAL TILL)		133.56	2	SS	50	1	●						
1	Diamond Rotary Core HQ (89mm OD)	Slightly weathered to fresh, fine grained, very strong, greenish grey to pink Precambrian BEDROCK		1.02	3	RC									
					5.79	4	RC								
						5	RC								
						6	RC								
6		End of Borehole		128.79											

GROUNDWATER OBSERVATIONS		
DATE	DEPTH (m)	ELEV. (m)
22/02/09	0.7	▽ 133.9




GEO - BOREHOLE LOG - 100737.002 - GINT - BOREHOLE LOGS.GPJ - GEMTEC.2018.GDT - 12/14/22


RECORD OF BOREHOLE 22-219

CLIENT: Caivan Communities
 PROJECT: Proposed Residential Development, Perth Golf, 141 Peter Street, Perth, Ontario
 JOB#: 100737.002
 LOCATION: See Site Plan, Figure 1

SHEET: 1 OF 1
 DATUM: CGVD28
 BORING DATE: Jan 5 2022

DEPTH SCALE METRES	BORING METHOD	SOIL PROFILE		SAMPLES				PENETRATION RESISTANCE (N), BLOWS/0.3m		SHEAR STRENGTH (Cu), kPA		ADDITIONAL LAB. TESTING	PIEZOMETER OR STANDPIPE INSTALLATION	
		DESCRIPTION	STRATA PLOT	ELEV. DEPTH (m)	NUMBER	TYPE	RECOVERY, mm	BLOWS/0.3m	▲ DYNAMIC PENETRATION RESISTANCE, BLOWS/0.3m	● PENETRATION RESISTANCE (N), BLOWS/0.3m	⊕ NATURAL ⊖ REMOULDED			WATER CONTENT, % W _p — W — W _L
0	Power Auger Hollow Stem Auger (210mm OD)	Ground Surface		136.84										
		TOPSOIL		0.08	1	SS	180	5	●					
1		Loose to compact, grey brown SILTY SAND, some gravel, with cobbles and boulders (GLACIAL TILL)			2	SS	230	20	●					
2		Compact to very dense, grey SILTY SAND, some gravel, with cobbles and boulders (GLACIAL TILL)		135.32 1.52	3	SS	280	19	●					
3					4	SS	455	65	●					
4		End of Borehole Auger Refusal		133.31 3.53										
5														
6														
7														
8														
9														
10														

Native backfill





GEO - BOREHOLE LOG 100737.002_GINT_BOREHOLE LOGS.GPJ_GEMTEC 2018.GDT 12/14/22

RECORD OF BOREHOLE 22-220


CLIENT: Caivan Communities
 PROJECT: Proposed Residential Development, Perth Golf, 141 Peter Street, Perth, Ontario
 JOB#: 100737.002
 LOCATION: See Site Plan, Figure 1

SHEET: 1 OF 1
 DATUM: CGVD28
 BORING DATE: Jan 7 2022

DEPTH SCALE METRES	BORING METHOD	SOIL PROFILE			SAMPLES				PENETRATION RESISTANCE (N), BLOWS/0.3m		SHEAR STRENGTH (Cu), kPA		ADDITIONAL LAB. TESTING	PIEZOMETER OR STANDPIPE INSTALLATION
		DESCRIPTION	STRATA PLOT	ELEV. DEPTH (m)	NUMBER	TYPE	RECOVERY, mm	BLOWS/0.3m	▲ DYNAMIC PENETRATION RESISTANCE, BLOWS/0.3m	●	⊕ NATURAL	⊖ REMOULDED		
0	Power Auger Hollow Stem Auger (210mm OD)	Ground Surface		137.53										
		TOPSOIL		0.10										
		Loose, brown SILTY SAND, trace gravel, with cobbles and boulders (GLACIAL TILL)			1	SS	455	9	●					
1					2	SS	480	9	●	○				
		Loose to very dense, brown SILTY CLAYEY SAND, trace gravel, with cobbles and boulders (GLACIAL TILL)		136.01 1.52										
2				3	SS	405	5	●		○				
				4	SS	100	>50 for 100 mm			○				
3		End of Borehole Auger Refusal		134.96 2.57										
4														
5														
6														
7														
8														
9														
10														

Native backfill

MH




GEO - BOREHOLE LOG 100737.002_GINT_BOREHOLE LOGS.GPJ_GEMTEC 2018.GDT 12/14/22

RECORD OF BOREHOLE 22-221

CLIENT: Caivan Communities
 PROJECT: Proposed Residential Development, Perth Golf, 141 Peter Street, Perth, Ontario
 JOB#: 100737.002
 LOCATION: See Site Plan, Figure 1

SHEET: 1 OF 1
 DATUM: CGVD28
 BORING DATE: Jan 12 2022

DEPTH SCALE METRES	BORING METHOD	SOIL PROFILE		SAMPLES				PENETRATION RESISTANCE (N), BLOWS/0.3m ▲ DYNAMIC PENETRATION RESISTANCE, BLOWS/0.3m	SHEAR STRENGTH (Cu), kPA + NATURAL ⊕ REMOULDED		ADDITIONAL LAB. TESTING	PIEZOMETER OR STANDPIPE INSTALLATION
		DESCRIPTION	STRATA PLOT	ELEV. DEPTH (m)	NUMBER	TYPE	RECOVERY, mm		BLOWS/0.3m	WATER CONTENT, % W _p — W — W _L		
0	Power Auger (210mm OD)	Ground Surface		134.63								
		TOPSOIL		134.50								
		Stiff to very stiff, grey brown SILTY CLAY (WEATHERED CRUST)		0.13	1	SS	255	2				
		Very dense, brown SILTY SAND, some gravel, with cobbles and boulders (GLACIAL TILL)		0.61	2	SS	75	>50				
1	Hollow Stem Auger (210mm OD) Diamond Rotary Core (HQ (89mm OD))	Slightly weathered to fresh, fine grained, medium to very strong, pinkish grey Precambrian BEDROCK		1.19	3	RC			TCR = 50%; SCR = 50%; RQD = 50%			
					4	RC			TCR = 97%; SCR = 85%; RQD = 88%			
					5	RC			TCR = 100%; SCR = 93%; RQD = 35%			
					6	RC			TCR = 100%; SCR = 95%; RQD = 91%			
					7	RC			TCR = 100%; SCR = 100%; RQD = 100%			
6		End of Borehole		128.33 6.30								



GROUNDWATER OBSERVATIONS		
DATE	DEPTH (m)	ELEV. (m)
22/02/09	0.5	134.2


GEO - BOREHOLE LOG, 100737.002, GINT, BOREHOLE LOGS.GPJ, GEMTEC, 2018, GDT, 12/14/22

RECORD OF BOREHOLE 22-221A

CLIENT: Caivan Communities
 PROJECT: Proposed Residential Development, Perth Golf, 141 Peter Street, Perth, Ontario
 JOB#: 100737.002
 LOCATION: See Site Plan, Figure 1

SHEET: 1 OF 1
 DATUM: CGVD28
 BORING DATE: Jan 12 2022

DEPTH SCALE METRES	BORING METHOD	SOIL PROFILE			SAMPLES				PENETRATION RESISTANCE (N), BLOWS/0.3m		SHEAR STRENGTH (Cu), kPA		ADDITIONAL LAB. TESTING	PIEZOMETER OR STANDPIPE INSTALLATION	
		DESCRIPTION	STRATA PLOT	ELEV. DEPTH (m)	NUMBER	TYPE	RECOVERY, mm	BLOWS/0.3m	●	▲	+	⊕			
				WATER CONTENT, %											
				W _p — W — W _L											
				10 20 30 40 50 60 70 80 90											
0	Power Auger Hollow Stem Auger (210mm OD)	Ground Surface		134.72											
		TOPSOIL		134.59											
		Stiff to very stiff, grey brown SILTY CLAY (WEATHERED CRUST)		0.13											
		Very dense, brown SILTY SAND, some gravel, with cobbles and boulders (GLACIAL TILL)		134.11 0.61											
1		End of Borehole		133.30 1.42											
		Soil stratigraphy from 0.00 to 1.42 metres inferred from Borehole 22-221													
2															
3															
4															
5															
6															
7															
8															
9															
10															



GROUNDWATER OBSERVATIONS		
DATE	DEPTH (m)	ELEV. (m)
22/02/09	0.6	▽ 134.1

GEO - BOREHOLE LOG 100737.002 GINT - BOREHOLE LOGS.GPJ GEMTEC 2018.GDT 12/14/22

RECORD OF BOREHOLE 22-222

CLIENT: Caivan Communities
 PROJECT: Proposed Residential Development, Perth Golf, 141 Peter Street, Perth, Ontario
 JOB#: 100737.002
 LOCATION: See Site Plan, Figure 1

SHEET: 1 OF 1
 DATUM: CGVD28
 BORING DATE: Jan 13 2022

DEPTH SCALE METRES	BORING METHOD	SOIL PROFILE		SAMPLES				PENETRATION RESISTANCE (N), BLOWS/0.3m		SHEAR STRENGTH (Cu), kPA		ADDITIONAL LAB. TESTING	PIEZOMETER OR STANDPIPE INSTALLATION	
		DESCRIPTION	STRATA PLOT	ELEV. DEPTH (m)	NUMBER	TYPE	RECOVERY, mm	BLOWS/0.3m	▲ DYNAMIC PENETRATION RESISTANCE, BLOWS/0.3m	● PENETRATION RESISTANCE (N), BLOWS/0.3m	+ NATURAL ⊕ REMOULDED			WATER CONTENT, % W _p W W _L
0	Power Auger Stem Auger (210mm OD)	Ground Surface		135.63										
		TOPSOIL		0.10	1	SS	150	9	●					
1	Hollow Stem Auger (210mm OD)	Loose to very loose, brown SILTY SAND, some gravel, with cobbles and boulders (GLACIAL TILL)			2	SS	380	3	●	○				
		Slightly weathered to fresh, fine grained, very strong, light grey to pinkish grey Precambrian BEDROCK		1.17	3	RC								
2	Diamond Rotary Core HQ (89mm OD)	Slightly weathered to fresh, fine grained, very strong, greyish pink to light pink Precambrian BEDROCK		132.05	4	RC								
3				3.58	5	RC								
4					6	RC								
5					7	RC								
6		End of Borehole		129.53										
				6.10										
7														
8														
9														
10														



GROUNDWATER OBSERVATIONS		
DATE	DEPTH (m)	ELEV. (m)
22/02/09	1.1	134.5

GEO - BOREHOLE LOG, 100737.002, GINT, BOREHOLE LOGS.GPJ, GEMTEC, 2018, GDT, 12/14/22




LOGGED: CS
 CHECKED: WAM

RECORD OF BOREHOLE 22-222A

CLIENT: Caivan Communities
 PROJECT: Proposed Residential Development, Perth Golf, 141 Peter Street, Perth, Ontario
 JOB#: 100737.002
 LOCATION: See Site Plan, Figure 1

SHEET: 1 OF 1
 DATUM: CGVD28
 BORING DATE: Jan 13 2022

DEPTH SCALE METRES	BORING METHOD	SOIL PROFILE		SAMPLES				PENETRATION RESISTANCE (N), BLOWS/0.3m		SHEAR STRENGTH (Cu), kPA		ADDITIONAL LAB. TESTING	PIEZOMETER OR STANDPIPE INSTALLATION
		DESCRIPTION	STRATA PLOT	ELEV. DEPTH (m)	NUMBER	TYPE	RECOVERY, mm	BLOWS/0.3m	▲ DYNAMIC PENETRATION RESISTANCE, BLOWS/0.3m	+ NATURAL ⊕ REMOULDED	WATER CONTENT, % W _p — W — W _L		
0	Power Auger Stem Auger (210mm OD)	Ground Surface		135.73									
		TOPSOIL		0.10									
		Loose to very loose, brown SILTY SAND, some gravel, with cobbles and boulders (GLACIAL TILL)											
1	Hollow Stem Auger (210mm OD)	Slightly weathered to fresh, fine grained, very strong, light grey to pinkish grey Precambrian BEDROCK		134.56									
		1.17											
2	Diamond Rotary Core HQ (89mm OD)	Slightly weathered to fresh, fine grained, very strong, greyish pink to light pink Precambrian BEDROCK		132.15									
		3.58											
4		3.73	End of Borehole Soil and bedrock stratigraphy from 0.00 to 3.73 metres inferred from Borehole 22-222										
5													
6													
7													
8													
9													
10													






GROUNDWATER OBSERVATIONS		
DATE	DEPTH (m)	ELEV. (m)
22/02/09	1.3	134.4

GEO - BOREHOLE LOG_100737.002_GINT_BOREHOLE LOGS.GPJ_GEMTEC 2018.GDT_12/14/22

RECORD OF BOREHOLE 22-223

CLIENT: Caivan Communities
 PROJECT: Proposed Residential Development, Perth Golf, 141 Peter Street, Perth, Ontario
 JOB#: 100737.002
 LOCATION: See Site Plan, Figure 1

SHEET: 1 OF 2
 DATUM: CGVD28
 BORING DATE: Jan 25 2022

DEPTH SCALE METRES	BORING METHOD	SOIL PROFILE		SAMPLES				PENETRATION RESISTANCE (N), BLOWS/0.3m		SHEAR STRENGTH (Cu), kPA		ADDITIONAL LAB. TESTING	PIEZOMETER OR STANDPIPE INSTALLATION
		DESCRIPTION	STRATA PLOT	ELEV. DEPTH (m)	NUMBER	TYPE	RECOVERY, mm	BLOWS/0.3m	▲ DYNAMIC PENETRATION RESISTANCE, BLOWS/0.3m	● PENETRATION RESISTANCE (N), BLOWS/0.3m	+ NATURAL ⊕ REMOULDED		
0	Power Auger Stem Auger (210mm OD)	Ground Surface		134.62									
		TOPSOIL		134.47									
		Stiff to very stiff, grey brown SILTY CLAY (WEATHERED CRUST)		0.15	1	SS	405	8	●				
1					2	SS	355	8	●				
	Hollow Stem Auger Diamond Rotary Core HQ (89mm OD)	Slightly weathered to fresh, fine grained, pink and grey Precambrian BEDROCK		1.29	3	RC				TCR = 83%; SCR = 83%; RQD = 0%			
2					4	RC				TCR = 100%; SCR = 100%; RQD = 100%			
3						5	RC				TCR = 100%; SCR = 93%; RQD = 90%		
4						6	RC				TCR = 97%; SCR = 97%; RQD = 97%		
5						7	RC				TCR = 100%; SCR = 97%; RQD = 97%		
6						8	RC				TCR = 85%; SCR = 14%; RQD = 14%		
7						9	RC				TCR = 90%; SCR = 67%; RQD = 73%		
8					126.67	10	RC				TCR = 97%; SCR = 78%; RQD = 78%		
			Fresh, fine grained, pink and greenish grey Precambrian BEDROCK		7.95								
9													
10				124.62	11	RC				TCR = 100%; SCR = 90%; RQD = 90%			

GEO - BOREHOLE LOG 100737.002 GINT BOREHOLE LOGS.GPJ GEMTEC 2018.GDT 12/14/22



LOGGED: CS
 CHECKED: WAM




RECORD OF BOREHOLE 22-223

CLIENT: Caivan Communities
 PROJECT: Proposed Residential Development, Perth Golf, 141 Peter Street, Perth, Ontario
 JOB#: 100737.002
 LOCATION: See Site Plan, Figure 1

SHEET: 2 OF 2
 DATUM: CGVD28
 BORING DATE: Jan 25 2022

DEPTH SCALE METRES	BORING METHOD	SOIL PROFILE			SAMPLES				PENETRATION RESISTANCE (N), BLOWS/0.3m		SHEAR STRENGTH (Cu), kPA		ADDITIONAL LAB. TESTING	PIEZOMETER OR STANDPIPE INSTALLATION
		DESCRIPTION	STRATA PLOT	ELEV. DEPTH (m)	NUMBER	TYPE	RECOVERY, mm	BLOWS/0.3m	DYNAMIC PENETRATION RESISTANCE, BLOWS/0.3m		WATER CONTENT, %			
10	20			30					40	50	60	70	80	90
10		Fresh, fine grained, pink and greenish grey Precambrian BEDROCK		10.00										
11				12	RC	TCR = 97%; SCR = 86%; RQD = 80%								
12				122.53 12.09	13	RC	TCR = 100%; SCR = 22%; RQD = 0%							
13		End of Borehole												
14														
15														
16														
17														
18														
19														
20														

50 millimetre well screen



GROUNDWATER OBSERVATIONS		
DATE	DEPTH (m)	ELEV. (m)
22/02/09	0.3 ▽	134.3

GEO - BOREHOLE LOG - 100737.002 - GINT - BOREHOLE LOGS.GPJ - GEMTEC.2018.GDT - 12/14/22

RECORD OF BOREHOLE 22-224

CLIENT: Caivan Communities
 PROJECT: Proposed Residential Development, Perth Golf, 141 Peter Street, Perth, Ontario
 JOB#: 100737.002
 LOCATION: See Site Plan, Figure 1

SHEET: 1 OF 1
 DATUM: CGVD28
 BORING DATE: Jan 5 2022

DEPTH SCALE METRES	BORING METHOD	SOIL PROFILE		SAMPLES				PENETRATION RESISTANCE (N), BLOWS/0.3m ▲ DYNAMIC PENETRATION RESISTANCE, BLOWS/0.3m	SHEAR STRENGTH (Cu), kPA + NATURAL ⊕ REMOULDED	WATER CONTENT, % W _p — W — W _L	ADDITIONAL LAB. TESTING	PIEZOMETER OR STANDPIPE INSTALLATION	
		DESCRIPTION	STRATA PLOT	ELEV. DEPTH (m)	NUMBER	TYPE	RECOVERY, mm						BLOWS/0.3m
0	Power Auger Hollow Stem Auger (210mm OD)	Ground Surface		135.64								Filter sand Native backfill Bentonite seal Filter sand 50 millimetre well screen Bentonite backfill	
		TOPSOIL		0.08	1	SS	255	4	●				
		Very loose, grey brown SILTY SAND, some gravel, with cobbles and boulders (GLACIAL TILL)											
1					2	SS	150	4	●	○			
		Compact to very dense, grey brown to grey SILTY SAND, some gravel, with cobbles and boulders (GLACIAL TILL)											
2					3	SS	150	13	●				
	Diamond Rotary Core HQ (89mm OD)	Slightly weathered to fresh, fine grained, very strong, pinkish grey Precambrian BEDROCK		134.12									
			4.45	7	RC								
2				131.19									
				4.45	8	RC							
4				129.47									
		End of Borehole		6.17									
5													
6													
7													
8													
9													
10													

GROUNDWATER OBSERVATIONS		
DATE	DEPTH (m)	ELEV. (m)
22/02/09	0.5	135.1


GEO - BOREHOLE LOG - 100737.002 - GINT - BOREHOLE LOGS.GPJ - GEMTEC 2018.GDT - 12/14/22

RECORD OF BOREHOLE 22-225

CLIENT: Caivan Communities
 PROJECT: Proposed Residential Development, Perth Golf, 141 Peter Street, Perth, Ontario
 JOB#: 100737.002
 LOCATION: See Site Plan, Figure 1

SHEET: 1 OF 1
 DATUM: CGVD28
 BORING DATE: Jan 4 2022

DEPTH SCALE METRES	BORING METHOD	SOIL PROFILE		SAMPLES				PENETRATION RESISTANCE (N), BLOWS/0.3m ▲ DYNAMIC PENETRATION RESISTANCE, BLOWS/0.3m	SHEAR STRENGTH (Cu), kPA + NATURAL ⊕ REMOULDED		ADDITIONAL LAB. TESTING	PIEZOMETER OR STANDPIPE INSTALLATION
		DESCRIPTION	STRATA PLOT	ELEV. DEPTH (m)	NUMBER	TYPE	RECOVERY, mm		BLOWS/0.3m	WATER CONTENT, % Wp — W — Wl		
0	Power Auger Stem Auger (210mm OD)	Ground Surface		134.94								
		TOPSOIL		134.79								
		Loose, grey brown SILTY SAND, some gravel, with cobbles and boulders (GLACIAL TILL)		0.15	1	SS	205	6				
1	Hollow Stem Auger Diamond Rotary Core HQ (89mm OD)	Slightly weathered to fresh, fine grained, very strong, pinkish grey Precambrian BEDROCK		133.72	2	SS	150	5				
				1.22	3	RC			TCR = 95%; SCR = 82%; RQD = 45%			
2					4	RC			TCR = 98%; SCR = 96%; RQD = 86%			
3					5	RC			TCR = 100%; SCR = 88%; RQD = 66%			
4					6	RC			TCR = 98%; SCR = 85%; RQD = 66%			
5												
6		End of Borehole		128.92								
				6.02								
7												
8												
9												
10												



GROUNDWATER OBSERVATIONS		
DATE	DEPTH (m)	ELEV. (m)
22/02/09	0.8	134.1


GEO - BOREHOLE LOG 100737.002_GINT - BOREHOLE LOGS.GPJ GEMTEC 2018.GDT 12/14/22

RECORD OF BOREHOLE 22-225A

CLIENT: Caivan Communities
 PROJECT: Proposed Residential Development, Perth Golf, 141 Peter Street, Perth, Ontario
 JOB#: 100737.002
 LOCATION: See Site Plan, Figure 1

SHEET: 1 OF 1
 DATUM: CGVD28
 BORING DATE: Jan 4 2022

DEPTH SCALE METRES	BORING METHOD	SOIL PROFILE			SAMPLES				PENETRATION RESISTANCE (N), BLOWS/0.3m		SHEAR STRENGTH (Cu), kPA		ADDITIONAL LAB. TESTING	PIEZOMETER OR STANDPIPE INSTALLATION
		DESCRIPTION	STRATA PLOT	ELEV.	NUMBER	TYPE	RECOVERY, mm	BLOWS/0.3m	DYNAMIC PENETRATION RESISTANCE, BLOWS/0.3m		WATER CONTENT, %			
				DEPTH (m)					10	20	30	40		
0	Power Auger	Ground Surface		134.97										
		TOPSOIL		134.82										
	Hollow Stem Auger (210mm OD)	Loose, grey brown SILTY SAND, some gravel, with cobbles and boulders (GLACIAL TILL)		0.15										
1		End of Borehole Auger Refusal Soil and bedrock stratigraphy from 0.00 to 1.37 metres inferred from Borehole 22-225		133.60										
2				1.37										
3														
4														
5														
6														
7														
8														
9														
10														



GROUNDWATER OBSERVATIONS		
DATE	DEPTH (m)	ELEV. (m)
22/02/09	0.9	▽ 134.1

GEO - BOREHOLE LOG, 100737.002, GINT, BOREHOLE LOGS.GPJ, GEMTEC, 2018, GDT, 12/14/22


RECORD OF BOREHOLE 22-226

CLIENT: Caivan Communities
 PROJECT: Proposed Residential Development, Perth Golf, 141 Peter Street, Perth, Ontario
 JOB#: 100737.002
 LOCATION: See Site Plan, Figure 1

SHEET: 1 OF 1
 DATUM: CGVD28
 BORING DATE: Jan 5 2022

DEPTH SCALE METRES	BORING METHOD	SOIL PROFILE			SAMPLES				● PENETRATION RESISTANCE (N), BLOWS/0.3m ▲ DYNAMIC PENETRATION RESISTANCE, BLOWS/0.3m	SHEAR STRENGTH (Cu), kPA		ADDITIONAL LAB. TESTING	PIEZOMETER OR STANDPIPE INSTALLATION	
		DESCRIPTION	STRATA PLOT	ELEV. DEPTH (m)	NUMBER	TYPE	RECOVERY, mm	BLOWS/0.3m		+ NATURAL ⊕ REMOULDED	WATER CONTENT, % W _p ——— W ——— W _L			
0	Power Auger Hollow Stem Auger (210mm OD)	Ground Surface		135.59										
		TOPSOIL		0.08										
		Stiff to very stiff, grey brown SILTY CLAY (WEATHERED CRUST)				1	SS	305	5	●				
1						2	SS	610	10	●				
2						3	SS	610	3	●				
		Compact to very dense, brown SILTY SAND, some gravel, with cobbles and boulders (GLACIAL TILL)		133.30 2.29										
					4	SS	25	21	●					
3					5	SS	75	>50 for 75 mm						
		End of Borehole Auger Refusal		132.24 3.35										
4														
5														
6														
7														
8														
9														
10														

Native backfill





GEO - BOREHOLE LOG - 100737.002 - GINT - BOREHOLE LOGS.GPJ - GEMTEC 2018.GDT - 12/14/22


RECORD OF BOREHOLE 22-227

CLIENT: Caivan Communities
 PROJECT: Proposed Residential Development, Perth Golf, 141 Peter Street, Perth, Ontario
 JOB#: 100737.002
 LOCATION: See Site Plan, Figure 1

SHEET: 1 OF 1
 DATUM: CGVD28
 BORING DATE: Jan 26 2022

DEPTH SCALE METRES	BORING METHOD	SOIL PROFILE			SAMPLES				PENETRATION RESISTANCE (N), BLOWS/0.3m		SHEAR STRENGTH (Cu), kPA		ADDITIONAL LAB. TESTING	PIEZOMETER OR STANDPIPE INSTALLATION
		DESCRIPTION	STRATA PLOT	ELEV. DEPTH (m)	NUMBER	TYPE	RECOVERY, mm	BLOWS/0.3m	●	▲	+	⊕		
				WATER CONTENT, %										
				W _p W W _L										
				10 20 30 40 50 60 70 80 90										
0	Power Auger Auger (210mm OD)	Ground Surface		137.56										
		TOPSOIL			137.38 0.18									
		Compact to very dense, brown SILTY SAND, some gravel, with cobbles and boulders (GLACIAL TILL)			1	SS	355	14		●				
1	Hollow Stem Auger Refusal	End of Borehole		136.59 0.97										
		Auger Refusal				2	SS	150	>50 for 100 mm					
2														
3														
4														
5														
6														
7														
8														
9														
10														

Native backfill



GEO - BOREHOLE LOG 100737.002 GINT - BOREHOLE LOGS.GPJ GEMTEC 2018.GDT 12/14/22

RECORD OF BOREHOLE 22-228

CLIENT: Caivan Communities
 PROJECT: Proposed Residential Development, Perth Golf, 141 Peter Street, Perth, Ontario
 JOB#: 100737.002
 LOCATION: See Site Plan, Figure 1

SHEET: 1 OF 2
 DATUM: CGVD28
 BORING DATE: Jan 28 2022

DEPTH SCALE METRES	BORING METHOD	SOIL PROFILE			SAMPLES				PENETRATION RESISTANCE (N), BLOWS/0.3m		SHEAR STRENGTH (Cu), kPA		ADDITIONAL LAB. TESTING	PIEZOMETER OR STANDPIPE INSTALLATION	
		DESCRIPTION	STRATA PLOT	ELEV. DEPTH (m)	NUMBER	TYPE	RECOVERY, mm	BLOWS/0.3m	DYNAMIC PENETRATION RESISTANCE, BLOWS/0.3m		WATER CONTENT, %				
									10	20	W _p	W _L			
0	Power Auger Auger (210mm OD)	Ground Surface		138.48											
		TOPSOIL	0.10	1	SS	255	16		●						Native backfill
1	Hollow Stem Auger (99mm OD)	Compact to very dense, brown SILTY SAND, some gravel, with cobbles and boulders (GLACIAL TILL)		137.54	2	SS	100	>50 for 75 mm		●					
		Slightly weathered to fresh, fine grained, very strong, pinkish grey Precambrian BEDROCK	0.94	3	RC			TCR = 100%; SCR = 77%; RQD = 69%							
			4	RC			TCR = 100%; SCR = 19%; RQD = 0%								
			5	RC			TCR = 94%; SCR = 17%; RQD = 0%								
2			6	RC			TCR = 100%; SCR = 53%; RQD = 67%								
			7	RC			TCR = 92%; SCR = 61%; RQD = 61%								
3			8	RC			TCR = 100%; SCR = 74%; RQD = 54%								
			9	RC			TCR = 80%; SCR = 70%; RQD = 70%								
4			10	RC			TCR = 100%; SCR = 65%; RQD = 65%								▽ Bentonite seal
			11	RC			TCR = 97%; SCR = 69%; RQD = 38%								
5			12	RC			TCR = 100%; SCR = 95%; RQD = 95%								
			13	RC			TCR = 100%; SCR = 68%; RQD = 65%								
6		Diamond Rotary Core HQ (89mm OD)	14	RC			TCR = 100%; SCR = 17%; RQD = 0%								
			15	RC			TCR = 100%; SCR = 100%; RQD = 100%								
7			16	RC			TCR = 96%; SCR = 94%; RQD = 94%								
			17	RC			TCR = 97%; SCR = 43%; RQD = 37%								
8			18	RC			TCR = 100%; SCR = 63%; RQD = 41%								
			19	RC			TCR = 100%; SCR = 0%; RQD = 0%								
9				20	RC			TCR = 100%; SCR = 0%; RQD = 0%							
10					128.48									50 millimetre well screen	

GEO - BOREHOLE LOG, 100737.002, GINT, BOREHOLE LOGS.GPJ, GEMTEC, 2018, GDT, 12/14/22



LOGGED: CS
 CHECKED: WAM

RECORD OF BOREHOLE 22-228

CLIENT: Caivan Communities
 PROJECT: Proposed Residential Development, Perth Golf, 141 Peter Street, Perth, Ontario
 JOB#: 100737.002
 LOCATION: See Site Plan, Figure 1

SHEET: 2 OF 2
 DATUM: CGVD28
 BORING DATE: Jan 28 2022

DEPTH SCALE METRES	BORING METHOD	SOIL PROFILE			SAMPLES				PENETRATION RESISTANCE (N), BLOWS/0.3m		SHEAR STRENGTH (Cu), kPA		ADDITIONAL LAB. TESTING	PIEZOMETER OR STANDPIPE INSTALLATION	
		DESCRIPTION	STRATA PLOT	ELEV. DEPTH (m)	NUMBER	TYPE	RECOVERY, mm	BLOWS/0.3m	DYNAMIC PENETRATION RESISTANCE, BLOWS/0.3m		WATER CONTENT, %				
10	20								30	40	50	60	70	80	90
10		Slightly weathered to fresh, fine grained, very strong, pinkish grey Precambrian BEDROCK		10.00	20	RC		100	55	61				50 millimetre well screen	
11				21	RC		100	57	33						
12				22	RC		100	36	36						
12				23	RC	126.14 12.34	100	38	50						
13		End of Borehole													
14															
15															
16															
17															
18															
19															
20															






GROUNDWATER OBSERVATIONS		
DATE	DEPTH (m)	ELEV. (m)
22/02/09	4.1	134.3

GEO - BOREHOLE LOG - 100737.002 - GINT - BOREHOLE LOGS.GPJ - GEMTEC 2018.GDT - 12/14/22

RECORD OF BOREHOLE 22-228A

CLIENT: Caivan Communities
 PROJECT: Proposed Residential Development, Perth Golf, 141 Peter Street, Perth, Ontario
 JOB#: 100737.002
 LOCATION: See Site Plan, Figure 1

SHEET: 1 OF 1
 DATUM: CGVD28
 BORING DATE: Feb 2 2022

DEPTH SCALE METRES	BORING METHOD	SOIL PROFILE		SAMPLES				PENETRATION RESISTANCE (N), BLOWS/0.3m		SHEAR STRENGTH (Cu), kPA		ADDITIONAL LAB. TESTING	PIEZOMETER OR STANDPIPE INSTALLATION		
		DESCRIPTION	STRATA PLOT	ELEV. DEPTH (m)	NUMBER	TYPE	RECOVERY, mm	BLOWS/0.3m	▲ DYNAMIC PENETRATION RESISTANCE, BLOWS/0.3m	+	WATER CONTENT, % W _p — W — W _L				
0	Power Auger Auger (210mm OD)	Ground Surface		138.45									Native backfill 		
		TOPSOIL		0.10											
1	Hollow Stem Auger	Compact to very dense, brown SILTY SAND, some gravel, with cobbles and boulders (GLACIAL TILL)		137.51									Bentonite seal		
		Slightly weathered to fresh, fine grained, very strong, pinkish grey Precambrian BEDROCK		0.94											
2	Diamond Rotary Core HQ (89mm OD)												Filter sand  50 millimetre well screen		
3															
4															
5															
6															
7															
8															
9															
10		End of Borehole Soil and bedrock stratigraphy from 0.00 to 7.65 metres inferred from Borehole 22-228		130.80 7.65											

GROUNDWATER OBSERVATIONS		
DATE	DEPTH (m)	ELEV. (m)
22/02/09	4.0	134.4

GEO - BOREHOLE LOG, 100737.002, GINT - BOREHOLE LOGS.GPJ, GEMTEC, 2018, GDT, 12/14/22



LOGGED: CS
 CHECKED: WAM

RECORD OF BOREHOLE 22-229

CLIENT: Caivan Communities
 PROJECT: Proposed Residential Development, Perth Golf, 141 Peter Street, Perth, Ontario
 JOB#: 100737.002
 LOCATION: See Site Plan, Figure 1

SHEET: 1 OF 1
 DATUM: CGVD28
 BORING DATE: Jan 4 2022

DEPTH SCALE METRES	BORING METHOD	SOIL PROFILE			SAMPLES				● PENETRATION RESISTANCE (N), BLOWS/0.3m ▲ DYNAMIC PENETRATION RESISTANCE, BLOWS/0.3m	SHEAR STRENGTH (Cu), kPA		ADDITIONAL LAB. TESTING	PIEZOMETER OR STANDPIPE INSTALLATION	
		DESCRIPTION	STRATA PLOT	ELEV.	NUMBER	TYPE	RECOVERY, mm	BLOWS/0.3m		+ NATURAL ⊕ REMOULDED				WATER CONTENT, %
DEPTH (m)	W _p			W					W _L					
0	Power Auger Hollow Stem Auger (210mm OD)	Ground Surface		135.59										
		TOPSOIL		0.05	1	SS	50	6	●					
		Loose, brown silty sand, some gravel (FILL MATERIAL)			2	SS	405	5	●					Native backfill
1				3	SS	355	>50 for 150 mm							
2		End of Borehole Auger Refusal		133.48										
				2.11										
3														
4														
5														
6														
7														
8														
9														
10														

GEO - BOREHOLE LOG - 100737.002 - GINT - BOREHOLE LOGS.GPJ - GEMTEC 2018.GDT - 12/14/22

RECORD OF BOREHOLE 22-230

CLIENT: Caivan Communities
 PROJECT: Proposed Residential Development, Perth Golf, 141 Peter Street, Perth, Ontario
 JOB#: 100737.002
 LOCATION: See Site Plan, Figure 1

SHEET: 1 OF 1
 DATUM: CGVD28
 BORING DATE: Jan 4 2022

DEPTH SCALE METRES	BORING METHOD	SOIL PROFILE			SAMPLES				PENETRATION RESISTANCE (N), BLOWS/0.3m		SHEAR STRENGTH (Cu), kPA		ADDITIONAL LAB. TESTING	PIEZOMETER OR STANDPIPE INSTALLATION	
		DESCRIPTION	STRATA PLOT	ELEV. DEPTH (m)	NUMBER	TYPE	RECOVERY, mm	BLOWS/0.3m	DYNAMIC PENETRATION RESISTANCE, BLOWS/0.3m	WATER CONTENT, % W _p W W _L	+ NATURAL	⊕ REMOULDED			
0	Power Auger Hollow Stem Auger (210mm OD)												Ground Surface		134.95
		TOPSOIL		0.08											
		Compact, brown silty sand, some gravel (FILL MATERIAL)		134.34	1	SS	230	18	●						
		Loose, dark brown silty sand, with organics (FILL MATERIAL)		0.61											
1		Loose, grey brown silty sand (FILL MATERIAL)		134.04	2	SS	455	5	●	○					
				0.91											
2			132.66	3	SS	150	5	●	○						
		Loose to very dense, grey brown SILTY SAND, some clay, trace gravel, with cobbles and boulders (GLACIAL TILL)		2.29	4	SS	455	10	●						
3				5	SS	610	16	○	●						
4			130.91	6	SS	255	>50 for 150 mm								
		End of Borehole Auger Refusal		4.04											
5															
6															
7															
8															
9															
10															

Native backfill

MH


GEO - BOREHOLE LOG - 100737.002 - GINT - BOREHOLE LOGS.GPJ - GEMTEC 2018.GDT - 12/14/22

RECORD OF BOREHOLE 22-231

CLIENT: Caivan Communities
 PROJECT: Geotechnical and Hydrological Investigation, Proposed Residential Development, Perth golf Course
 JOB#: 100737.002
 LOCATION: 141 Peter Street, Perth

SHEET: 1 OF 1
 DATUM: CGVD28
 BORING DATE: Mar 15 2022

DEPTH SCALE METRES	BORING METHOD	SOIL PROFILE			SAMPLES				PENETRATION RESISTANCE (N), BLOWS/0.3m		SHEAR STRENGTH (Cu), kPA		ADDITIONAL LAB. TESTING	PIEZOMETER OR STANDPIPE INSTALLATION	
		DESCRIPTION	STRATA PLOT	ELEV. DEPTH (m)	NUMBER	TYPE	RECOVERY, mm	BLOWS/0.3m	▲ DYNAMIC PENETRATION RESISTANCE, BLOWS/0.3m	● PENETRATION RESISTANCE (N), BLOWS/0.3m	+ NATURAL ⊕ REMOULDED	WATER CONTENT, % Wp — W — Wl			
0	Portable Drill Rig Open Borehole			Ground Surface		136.54									
		Loose, black to dark brown fibrous PEAT		136.26	1	SS	430	3	●						
		Stiff to very stiff, grey brown SILTY CLAY, trace sand (WEATHERED CRUST)		136.28	2	SS	610	6	●						
1					3	SS	560	9	●						
					4	SS	455	10	●						
2					5	SS	355	41	●						
		Dense, grey SILTY SAND, some gravel, with cobbles and boulders (GLACIAL TILL)		134.18	6	SS	0	>50 for 125mm							
				2.36	7	RC	5	DD							
3				8	RC	0	DD								
		End of Borehole		133.19											
				3.35											
4															
5															
6															
7															
8															
9															
10															



GROUNDWATER OBSERVATIONS		
DATE	DEPTH (m)	ELEV. (m)
22/10/15	0.7	135.8

GEO - BOREHOLE LOG, 100737.002, GINT_V01_2022-03-28.GPJ, GEMTEC, 2018.GDT, 12/14/22

RECORD OF BOREHOLE 22-231A

CLIENT: Caivan Communities
 PROJECT: Geotechnical and Hydrological Investigation, Proposed Residential Development, Perth golf Course
 JOB#: 100737.002
 LOCATION: 141 Peter Street, Perth

SHEET: 1 OF 2
 DATUM: CGVD28
 BORING DATE: Mar 16 2022

DEPTH SCALE METRES	BORING METHOD	SOIL PROFILE		SAMPLES				PENETRATION RESISTANCE (N), BLOWS/0.3m		SHEAR STRENGTH (Cu), kPA		ADDITIONAL LAB. TESTING	PIEZOMETER OR STANDPIPE INSTALLATION
		DESCRIPTION	STRATA PLOT	ELEV. DEPTH (m)	NUMBER	TYPE	RECOVERY, mm	BLOWS/0.3m	▲ DYNAMIC PENETRATION RESISTANCE, BLOWS/0.3m	●	± NATURAL ⊕ REMOULDED		
0		Ground Surface		136.03									
		Black to dark brown, fibrous PEAT		135.75									
		Grey to brown, SILTY CLAY, trace sand (WEATHERED CRUST)		0.28									
1													
2													
		Grey SILTY SAND, some gravel, with cobbles and boulders (GLACIAL TILL)		133.67									
				2.36									
3		Probable SILTY SAND, some gravel, with cobbles and boulders (GLACIAL TILL)		133.18	1	RC	205	DD					
				2.85	2	RC	75	DD					
					3	RC	155	DD					
4	Wash Casing NQ (70mm OD)				4	RC	0	DD					
					5	RC	75	DD					
					6	SS	0	>50 for 25mm					
5					7	RC	815	DD					
6					8	RC	155	DD					
7					9	SS	0	>50 for 100mm					
		Slightly weathered to fresh, fine grained pink to grey Precambrian BEDROCK		128.95	10	RC		TCR 76%, SCR 35%, RQD 11%					
				7.08	11	RC		TCR 89%, SCR 44%, RQD 0%					
8					12	RC	915	TCR 57%, SCR 16%, RQD 0%					
9	Diamond Rotary Core NQ (70mm OD)	Slightly weathered to fresh, fine grained pink to grey Precambrian BEDROCK		127.03									
				9.00									
10													


GEO - BOREHOLE LOG 100737.002_GINT_V01_2022-03-28.GPJ GEMTEC 2018.GDT 12/14/22

RECORD OF BOREHOLE 22-231A

CLIENT: Caivan Communities
 PROJECT: Geotechnical and Hydrological Investigation, Proposed Residential Development, Perth golf Course
 JOB#: 100737.002
 LOCATION: 141 Peter Street, Perth

SHEET: 2 OF 2
 DATUM: CGVD28
 BORING DATE: Mar 16 2022

DEPTH SCALE METRES	BORING METHOD	SOIL PROFILE			SAMPLES				● PENETRATION RESISTANCE (N), BLOWS/0.3m ▲ DYNAMIC PENETRATION RESISTANCE, BLOWS/0.3m ○ WATER CONTENT, % W_p — W — W_L	SHEAR STRENGTH (Cu), kPA + NATURAL ⊕ REMOULDED	ADDITIONAL LAB. TESTING	PIEZOMETER OR STANDPIPE INSTALLATION
		DESCRIPTION	STRATA PLOT	ELEV. DEPTH (m)	NUMBER	TYPE	RECOVERY, mm	BLOWS/0.3m				
10			125.62	13	RC	75	TCR	37%	SCR 25%	ROD 0%		
11		End of Borehole	10.41									
12												
13												
14												
15												
16												
17												
18												
19												
20												



GROUNDWATER OBSERVATIONS		
DATE	DEPTH (m)	ELEV. (m)
22/10/15	0.8	135.3

GEO - BOREHOLE LOG - 100737.002_GINT_V01_2022-03-28.GPJ GEMTEC 2018.GDT 12/14/22




LOGGED: PS
 CHECKED: WAM

RECORD OF BOREHOLE 22-232

CLIENT: Caivan Communities
 PROJECT: Geotechnical and Hydrological Investigation, Proposed Residential Development, Perth golf Course
 JOB#: 100737.002
 LOCATION: 141 Peter Street, Perth

SHEET: 1 OF 1
 DATUM: CGVD28
 BORING DATE: Mar 25 2022

DEPTH SCALE METRES	BORING METHOD	SOIL PROFILE			SAMPLES				PENETRATION RESISTANCE (N), BLOWS/0.3m		SHEAR STRENGTH (Cu), kPA		ADDITIONAL LAB. TESTING	PIEZOMETER OR STANDPIPE INSTALLATION	
		DESCRIPTION	STRATA PLOT	ELEV. DEPTH (m)	NUMBER	TYPE	RECOVERY, mm	BLOWS/0.3m	●	▲	+ NATURAL ⊕ REMOULDED	WATER CONTENT, %			
										10 20 30 40 50 60 70 80 90		Wp — W — Wl			
0	Portable Drill Rig Open Borehole	Ground Surface		138.44											
		Black fibrous PEAT	[Hatched Box]	0.07	1	SS	280	3	●						
		Stiff to very stiff, grey brown SILTY CLAY (WEATHERED CRUST)	[Hatched Box]		2	SS	460	9	●						
1		End of Borehole Sampler Refusal		136.84 1.60	3	SS	460	23	●						
2															
3															
4															
5															
6															
7															
8															
9															
10															



GROUNDWATER OBSERVATIONS		
DATE	DEPTH (m)	ELEV. (m)
22/10/17	1.4	▽ 137.1

GEO - BOREHOLE LOG - 100737.002 - GINT_V01_2022-03-28.GPJ - GEMTEC 2018.GDT - 12/14/22

RECORD OF BOREHOLE 22-232A

CLIENT: Caivan Communities
 PROJECT: Geotechnical and Hydrological Investigation, Proposed Residential Development, Perth golf Course
 JOB#: 100737.002
 LOCATION: 141 Peter Street, Perth

SHEET: 1 OF 1
 DATUM: CGVD28
 BORING DATE: Mar 23 2022

DEPTH SCALE METRES	BORING METHOD	SOIL PROFILE		SAMPLES				PENETRATION RESISTANCE (N), BLOWS/0.3m DYNAMIC PENETRATION RESISTANCE, BLOWS/0.3m	SHEAR STRENGTH (Cu), kPA		WATER CONTENT, % W_p — W — W_L	ADDITIONAL LAB. TESTING	PIEZOMETER OR STANDPIPE INSTALLATION	
		DESCRIPTION	STRATA PLOT	ELEV. DEPTH (m)	NUMBER	TYPE	RECOVERY, mm		BLOWS/0.3m	+				⊕
0	Portable Drill Rig Open Borehole	Ground Surface		139.33										
		Black fibrous PEAT		138.77	1	SS	205	4	●					
1		Stiff to very stiff, grey to brown SILTY CLAY, some sand (WEATHERED CRUST)		137.71	2	SS	610	12	●					
2	Diamond Rotary Core NQ (70mm OD)	Slightly weathered to fresh, fine grained pink to grey Precambrian BEDROCK		137.71	3	SS	355	23	●					
				4	RC		TCR	97%	SCR 92%	RQD 92%				
				5	RC		TCR	97%	SCR 93%	RQD 93%				
3				6	RC		TCR	100%	SCR 75%	RQD 67%				
				7	RC		TCR	100%	SCR 97%	RQD 97%				
				8	RC		TCR	100%	SCR 96%	RQD 75%				
4				9	RC		TCR	98%	SCR 91%	RQD 84%				
5		End of Borehole		134.66										
6				4.67										
7														
8														
9														
10														



GROUNDWATER OBSERVATIONS		
DATE	DEPTH (m)	ELEV. (m)
22/10/17	1.3	138.1


GEO - BOREHOLE LOG - 100737.002 - GINT_V01_2022-03-28.GPJ - GEMTEC 2018.GDT - 12/14/22

RECORD OF BOREHOLE 22-233B

CLIENT: Caivan (Perth G.C.) Limited
 PROJECT: Proposed Residential Development, Perth Golf, 141 Peter Street, Perth, Ontario
 JOB#: 100737.002
 LOCATION: See Site Plan, Figure 1

SHEET: 1 OF 1
 DATUM: CGVD28
 BORING DATE: Oct 6 2022

DEPTH SCALE METRES	BORING METHOD	SOIL PROFILE		SAMPLES				PENETRATION RESISTANCE (N), BLOWS/0.3m		SHEAR STRENGTH (Cu), kPA		ADDITIONAL LAB. TESTING	PIEZOMETER OR STANDPIPE INSTALLATION
		DESCRIPTION	STRATA PLOT	ELEV. DEPTH (m)	NUMBER	TYPE	RECOVERY, mm	BLOWS/0.3m	▲ DYNAMIC PENETRATION RESISTANCE, BLOWS/0.3m	WATER CONTENT, %			
	W _p			W						W _L			
0		Ground Surface		134.94									
		Unsampled Overburden											
1	Power Auger Hollow Stem Auger (210mm OD)												
2													
3													
4													
5													
6													
6		End of Borehole, Auger Refusal		129.07 5.87									
7													
8													
9													
10													



GROUNDWATER OBSERVATIONS		
DATE	DEPTH (m)	ELEV. (m)
22/10/14	1.0 ▽	133.9

GEO - BOREHOLE LOG 100737.002_GINT_2022-10-13.GPJ_GEMTEC 2018.GDT_12/14/22

RECORD OF BOREHOLE 22-234

CLIENT: Caivan (Perth G.C.) Limited
 PROJECT: Proposed Residential Development, Perth Golf, 141 Peter Street, Perth, Ontario
 JOB#: 100737.002
 LOCATION: See Site Plan, Figure 1

SHEET: 1 OF 1
 DATUM: CGVD28
 BORING DATE: Oct 5 2022

DEPTH SCALE METRES	BORING METHOD	SOIL PROFILE		SAMPLES				PENETRATION RESISTANCE (N), BLOWS/0.3m		SHEAR STRENGTH (Cu), kPA		ADDITIONAL LAB. TESTING	PIEZOMETER OR STANDPIPE INSTALLATION	
		DESCRIPTION	STRATA PLOT	ELEV. DEPTH (m)	NUMBER	TYPE	RECOVERY, mm	BLOWS/0.3m	▲ DYNAMIC PENETRATION RESISTANCE, BLOWS/0.3m	● NATURAL ⊕ REMOULDED	WATER CONTENT, % Wp — W — Wl			
0	Power Auger Hollow Stem Auger (260mm OD)	Ground Surface		134.43								Flush Mount		
1		Unsampled Overburden												Bentonite seal
2	Air Rotary 98.4 mm diameter	Probable Bedrock		132.14								Native backfill		
3				2.29									Bentonite seal	
4														Filter Sand
5														50 mm well screen
6														
7		End of Borehole		127.57										
8				6.86										
9														
10														

GROUNDWATER OBSERVATIONS		
DATE	DEPTH (m)	ELEV (m)
22/10/14	1.1	133.3

GEO - BOREHOLE LOG, 100737.002, GINT, 2022-10-13, GPJ, GEMTEC 2018, GDT, 12/14/22



LOGGED: A.N.
 CHECKED: W.A.M.

RECORD OF BOREHOLE 22-235

CLIENT: Caivan (Perth G.C.) Limited
 PROJECT: Proposed Residential Development, Perth Golf, 141 Peter Street, Perth, Ontario
 JOB#: 100737.002
 LOCATION: See Site Plan, Figure 1

SHEET: 1 OF 1
 DATUM: CGVD28
 BORING DATE: Oct 6 2022

DEPTH SCALE METRES	BORING METHOD	SOIL PROFILE		SAMPLES				PENETRATION RESISTANCE (N), BLOWS/0.3m		SHEAR STRENGTH (Cu), kPA		ADDITIONAL LAB. TESTING	PIEZOMETER OR STANDPIPE INSTALLATION	
		DESCRIPTION	STRATA PLOT	ELEV. DEPTH (m)	NUMBER	TYPE	RECOVERY, mm	BLOWS/0.3m	▲ DYNAMIC PENETRATION RESISTANCE, BLOWS/0.3m	●	WATER CONTENT, %			⊕ REMOULDED
0	Power Auger Hollow Stem Auger (210mm OD)	Ground Surface		134.25								Flush Mount	Bentonite seal	
		Unsampled Overburden												
1	Air Rotary 98.4 mm diameter	Probable Bedrock		132.93 1.32								50 mm well screen	Native cave	
2														
3														
4														
5														
6														
6		End of Borehole		128.15 6.10										
7														
8														
9														
10														

GROUNDWATER OBSERVATIONS		
DATE	DEPTH (m)	ELEV. (m)
22/10/14	1.0	133.3

GEO - BOREHOLE LOG, 100737.002, GINT, 2022-10-13, GP J, GEMTEC 2018, GDT, 12/14/22



LOGGED: A.N.
 CHECKED: W.A.M.


RECORD OF BOREHOLE 22-108

CLIENT: Caivan (Perth G.C.) Limited
 PROJECT: Proposed Residential Development, Perth Golf, 141 Peter Street, Perth, Ontario
 JOB#: 100737.002
 LOCATION: See Site Plan, Figure 1

SHEET: 1 OF 1
 DATUM: CGVD28
 BORING DATE: Oct 5 2022

DEPTH SCALE METRES	BORING METHOD	SOIL PROFILE		SAMPLES				PENETRATION RESISTANCE (N), BLOWS/0.3m		SHEAR STRENGTH (Cu), kPA		ADDITIONAL LAB. TESTING	PIEZOMETER OR STANDPIPE INSTALLATION
		DESCRIPTION	STRATA PLOT	ELEV. DEPTH (m)	NUMBER	TYPE	RECOVERY, mm	BLOWS/0.3m	▲ DYNAMIC PENETRATION RESISTANCE, BLOWS/0.3m	● NATURAL ⊕ REMOULDED	WATER CONTENT, % Wp — W — Wl		
0	Power Auger Hollow Stem Auger (210mm OD)	Ground Surface		137.40									
1		Unsamed Overburden											
2													
3													
3				134.22									
4		End of Borehole, Auger Refusal		3.18									
5													
6													
7													
8													
9													
10													

Native backfill




GEO - BOREHOLE LOG - 100737.002_GINT_2022-10-13.GPJ_GEMTEC 2018.GDT_12/14/22



APPENDIX B

Laboratory Test Results Grain Size Distribution Testing



Line Symbol	Sample	Borehole/ Test Pit	Sample Number	Depth	% Cob.+ Gravel	% Sand	% Silt	% Clay
—●—	GLACIAL TILL	22-202	SS 5	3.05-3.48	5.0	56.6	27.7	10.7
—■—	GLACIAL TILL	22-207	SS 3	1.52-2.13	10.2	53.4	25.0	11.5
—○—	GLACIAL TILL	22-220	SS 3	1.52-2.13	8.0	38.0	27.5	26.5
—□—	GLACIAL TILL	22-224	SS 4	2.29-2.90	17.5	50.6	21.7	10.2

Line Symbol	CanFEM Classification	USCS Symbol	D ₁₀	D ₁₅	D ₃₀	D ₅₀	D ₆₀	D ₈₅	% 5-75µm
—●—	Silty sand , some clay , trace gravel	N/A	0.00	0.01	0.06	0.13	0.20	1.36	27.7
—■—	Silty sand , some gravel, some clay	N/A	0.00	0.01	0.05	0.14	0.21	1.77	25.0
—○—	Silty clayey sand , trace gravel	N/A	---	---	0.01	0.06	0.11	0.56	27.5
—□—	Silty sand , some gravel, some clay	N/A	0.00	0.01	0.07	0.19	0.30	7.89	21.7



APPENDIX C

Bedrock Core Photographs
Figures C1 to C12
Unconfined Compressive Strength Results

BOREHOLE 22-201
BORING DATE: JANUARY 19, 2022
DEPTH: 6.43 to 7.47 mbgs



32 Steacie Drive, Ottawa, ON K2K 2A9
T: (613) 836-1422 | www.gemtec.ca | ottawa@gemtec.ca


Project
PROPOSED DEVELOPMENT
PERTH GOLF, 151 PETER STREET
PERTH, ONTARIO

FIGURE C1

File No.
100737.002

ROCKCORE PHOTOGRAPH
BH22-201

BOREHOLE 22-203A
BORING DATE: JANUARY 20, 2022
DEPTH: 0.76 to 6.22 mbgs



32 Steacie Drive, Ottawa, ON K2K 2A9
T: (613) 836-1422 | www.gemtec.ca | ottawa@gemtec.ca

Project
PROPOSED DEVELOPMENT
PERTH GOLF, 151 PETER STREET
PERTH, ONTARIO

FIGURE C2

File No.
100737.002

ROCKCORE PHOTOGRAPH
BH22-203A

BOREHOLE 22-206
BORING DATE: JANUARY 25, 2022
DEPTH: 3.81 to 7.59 mbgs



Note:

The material in the core box from 3.81 to 7.59 metres depth is gravel and cobbles from within the glacial till



32 Steacie Drive, Ottawa, ON K2K 2A9
T: (613) 836-1422 | www.gemtec.ca | ottawa@gemtec.ca

Project

PROPOSED DEVELOPMENT
PERTH GOLF, 151 PETER STREET
PERTH, ONTARIO

FIGURE C3

File No.

100737.002

ROCKCORE PHOTOGRAPH
BH22-206

BOREHOLE 22-208
BORING DATE: JANUARY 13, 2022
DEPTH: 0.30 to 6.07 mbgs



32 Steacie Drive, Ottawa, ON K2K 2A9
T: (613) 836-1422 | www.gemtec.ca | ottawa@gemtec.ca

Project
PROPOSED DEVELOPMENT
PERTH GOLF, 151 PETER STREET
PERTH, ONTARIO

FIGURE C4

File No.
100737.002

ROCKCORE PHOTOGRAPH
BH22-208

BOREHOLE 22-214
BORING DATE: JANUARY 6, 2022
DEPTH: 4.65 to 6.96 mbgs



32 Steacie Drive, Ottawa, ON K2K 2A9
T: (613) 836-1422 | www.gemtec.ca | ottawa@gemtec.ca

Project
PROPOSED DEVELOPMENT
PERTH GOLF, 151 PETER STREET
PERTH, ONTARIO

FIGURE C5

File No.
100737.002

ROCKCORE PHOTOGRAPH
BH22-214

BOREHOLE 22-216
BORING DATE: JANUARY 10, 2022
DEPTH: 1.02 to 5.79 mbgs



32 Steacie Drive, Ottawa, ON K2K 2A9
T: (613) 836-1422 | www.gemtec.ca | ottawa@gemtec.ca

Project
PROPOSED DEVELOPMENT
PERTH GOLF, 151 PETER STREET
PERTH, ONTARIO

FIGURE C6

File No.
100737.002

ROCKCORE PHOTOGRAPH
BH22-216

BOREHOLE 22-221
BORING DATE: JANUARY 12, 2022
DEPTH: 1.19 to 6.30 mbgs



32 Steacie Drive, Ottawa, ON K2K 2A9
T: (613) 836-1422 | www.gemtec.ca | ottawa@gemtec.ca

Project
PROPOSED DEVELOPMENT
PERTH GOLF, 151 PETER STREET
PERTH, ONTARIO

FIGURE C7

File No.
100737.002

ROCKCORE PHOTOGRAPH
BH22-221

BOREHOLE 22-222
BORING DATE: JANUARY 13, 2022
DEPTH: 1.17 to 6.10 mbgs



32 Steacie Drive, Ottawa, ON K2K 2A9
T: (613) 836-1422 | www.gemtec.ca | ottawa@gemtec.ca

Project
PROPOSED DEVELOPMENT
PERTH GOLF, 151 PETER STREET
PERTH, ONTARIO

FIGURE C8

File No.
100737.002

ROCKCORE PHOTOGRAPH
BH22-222

BOREHOLE 22-223
BORING DATE: JANUARY 27, 2022
DEPTH: 1.29 to 12.09 mbgs



32 Steacie Drive, Ottawa, ON K2K 2A9
T: (613) 836-1422 | www.gemtec.ca | ottawa@gemtec.ca


Project
PROPOSED DEVELOPMENT
PERTH GOLF, 151 PETER STREET
PERTH, ONTARIO

FIGURE C9

File No.
100737.002

ROCKCORE PHOTOGRAPH
BH22-223

BOREHOLE 22-224
BORING DATE: JANUARY 5, 2022
DEPTH: 4.45 to 6.17 mbgs



32 Steacie Drive, Ottawa, ON K2K 2A9
T: (613) 836-1422 | www.gemtec.ca | ottawa@gemtec.ca

Project
PROPOSED DEVELOPMENT
PERTH GOLF, 151 PETER STREET
PERTH, ONTARIO

FIGURE C10

File No.
100737.002

ROCKCORE PHOTOGRAPH
BH22-224

BOREHOLE 22-225
BORING DATE: JANUARY 4, 2022
DEPTH: 1.22 to 6.02 mbgs



32 Steacie Drive, Ottawa, ON K2K 2A9
T: (613) 836-1422 | www.gemtec.ca | ottawa@gemtec.ca

Project
PROPOSED DEVELOPMENT
PERTH GOLF, 151 PETER STREET
PERTH, ONTARIO

FIGURE C11

File No.
100737.002

ROCKCORE PHOTOGRAPH
BH22-225

BOREHOLE 22-228
BORING DATE: JANUARY 28, 2022
DEPTH: 0.94 to 12.34 mbgs



32 Steacie Drive, Ottawa, ON K2K 2A9
 T: (613) 836-1422 | www.gemtec.ca | ottawa@gemtec.ca

Project
**PROPOSED DEVELOPMENT
 PERTH GOLF, 151 PETER STREET
 PERTH, ONTARIO**

FIGURE C12

File No.
 100737.002

**ROCKCORE PHOTOGRAPH
 BH22-228**


**COMPRESSIVE STRENGTH
of ROCK CORE**

CLIENT: Caivan **PROJECT No.:** 100737.002
Project: Perth Golf Course **REPORT NO.:**
Date Received: 28-Jan-22 **Date Tested:** 31-Jan-22


Lab no.						
Cylinder ID	BH 22-201	BH 22-203	BH 22-208	BH 22-216	BH 22-221	BH 22-222
Depth (m)	6.55-6.75	2.44-2.73	0.81-1.04	3.02-3.43	2.97-3.28	5.18-5.51
Cut length (mm)						
Ground length (mm)	125.21	126.08	126.03	125.91	125.27	125.01
Diameter (mm)	63.24	63.37	63.23	63.17	63.35	63.25
Ground Mass (kg)	1097.00	1089.00	1078.00	1.07	1.13	1035.00
Length:Diameter ratio	1.98	1.99	1.99	1.99	1.98	1.98
Correction factor	1.00	1.00	1.00	1.00	1.00	1.00
Failure load (kN)	103.63	510.74	468.84	511.48	131.17	724.21
Uncorrected Strength (MPa)	33.00	161.90	149.30	163.20	41.60	230.50
Corrected Strength (MPa)	33.00	161.90	149.30	163.20	41.60	230.50

Remarks The Core from BH22-201 had cracking before being broken.

Checked by:


Krystle Smith, Laboratory Manager

Reviewed by:


Steve Goodman, Ph.D., P.Eng.


**COMPRESSIVE STRENGTH
 of ROCK CORE**

CLIENT: Caivan **PROJECT No.:** 100737.002
Project: Perth Golf Course **REPORT NO.:**
Date Received: Jan 28,2022 **Date Tested:** 31-Jan-22


Lab no.						
Cylinder ID	BH 22-223	BH 22-224	BH 22-225			
Depth (m)	4.39-4.80	4.67-5.05	5.31-5.54			
Cut length (mm)						
Ground length (mm)	125.82	125.92	125.97			
Diameter (mm)	63.18	63.14	63.16			
Ground Mass (kg)	1069.00	1079.00	1088.00			
Length:Diameter ratio	1.99	1.99	1.99			
Correction factor	1.00	1.00	1.00			
Failure load (kN)	362.71	408.55	442.73			
Uncorrected Strength (MPa)	115.70	130.50	141.30			
Corrected Strength (MPa)	115.70	130.50	141.30			

Remarks

Checked by:


 Krystle Smith, Laboratory Manager

Reviewed by:


 Steve Goodman, Ph.D., P.Eng.



APPENDIX D

Borehole Records – Previous Investigation
Boreholes 21-01 to 21-04, Proboholes 21-101 to 21-104,
and Hand Augerholes 21-201 and 21-202

RECORD OF BOREHOLE 21-01

CLIENT: Caivan Communities
 PROJECT: Preliminary Geotechnical Investigation, Perth Golf Course, Perth, Ontario
 JOB#: 100737.001
 LOCATION: See Site Plan, Figure 1

SHEET: 1 OF 1
 DATUM: CGVD28
 BORING DATE: May 4 2021

DEPTH SCALE METRES	BORING METHOD	SOIL PROFILE		SAMPLES				● PENETRATION RESISTANCE (N), BLOWS/0.3m ▲ DYNAMIC PENETRATION RESISTANCE, BLOWS/0.3m	SHEAR STRENGTH (Cu), kPA		ADDITIONAL LAB. TESTING	PIEZOMETER OR STANDPIPE INSTALLATION	
		DESCRIPTION	STRATA PLOT	ELEV. DEPTH (m)	NUMBER	TYPE	RECOVERY, mm		BLOWS/0.3m	+ NATURAL			⊕ REMOULDED
0	Power Auger Hollow Stem Auger (210mm OD)	Ground Surface		135.07									
		Grey brown silty sand and gravel (BASE MATERIAL)		134.97	1	SS	405	6	●				
		Loose, brown silty sand, trace gravel (FILL MATERIAL)		0.10									
1	Loose to compact, grey brown SILTY SAND, some gravel, with cobbles and gravel (GLACIAL TILL)	134.31		2	SS	455	10	●					
2	Wash Casing HW (114mm OD)				3	SS	455	6	●	○			
3		Very dense, grey SILTY SAND, some gravel, with cobbles and boulders (GLACIAL TILL)	132.63	4	RC	250							
4			2.44										
5				5	RC	305							
6				6	SS	255	>50 for 51 mm						
7			7	RC									
7		End of Borehole		128.39									
				6.68									
8													
9													
10													

GEO - BOREHOLE LOG - 100737.001 GINT LOGS.GPJ - GEMTEC 2018.GDT - 21/5/21

RECORD OF BOREHOLE 21-02

CLIENT: Caivan Communities
 PROJECT: Preliminary Geotechnical Investigation, Perth Golf Course, Perth, Ontario
 JOB#: 100737.001
 LOCATION: See Site Plan, Figure 1

SHEET: 1 OF 1
 DATUM: CGVD28
 BORING DATE: May 4 2021





DEPTH SCALE METRES	BORING METHOD	SOIL PROFILE			SAMPLES				PENETRATION RESISTANCE (N), BLOWS/0.3m ▲ DYNAMIC PENETRATION RESISTANCE, BLOWS/0.3m	SHEAR STRENGTH (Cu), kPA + NATURAL ⊕ REMOULDED		ADDITIONAL LAB. TESTING	PIEZOMETER OR STANDPIPE INSTALLATION
		DESCRIPTION	STRATA PLOT	ELEV. DEPTH (m)	NUMBER	TYPE	RECOVERY, mm	BLOWS/0.3m		WATER CONTENT, % W _p — W — W _L			
0		Ground Surface		136.30									
		Grey brown silty sand and gravel (BASE MATERIAL) Loose to very loose, dark brown silty sand, with organics (FILL MATERIAL)		136.10 0.20	1	SS	255	5	●				
1	Power Auger												
		Compact, grey brown SILTY SAND, some gravel, with cobbles and boulders (GLACIAL TILL)		134.93 1.37	2	SS	255	2	●				
2	Hollow Stem Auger (210mm OD)												
					3	SS	455	28	○	●			
3													
					4	SS	305	34		●			
4	Diamond Rotary Core HQ (89mm OD)												
		Slightly weathered to fresh, grey and pink, fine grained, strong Precambrian BEDROCK		132.97 3.33	5	SS	205	>50 for 75 cm					
5					6	RC							
					7	RC							
6													
7													
8													
9													
10		End of Borehole		131.19 5.11									

GEO - BOREHOLE LOG - 100737.001 GINT LOGS.GPJ - GEMTEC 2018.GDT 5-18-21

RECORD OF BOREHOLE 21-03

CLIENT: Caivan Communities
 PROJECT: Preliminary Geotechnical Investigation, Perth Golf Course, Perth, Ontario
 JOB#: 100737.001
 LOCATION: See Site Plan, Figure 1

SHEET: 1 OF 1
 DATUM: CGVD28
 BORING DATE: May 4 2021




DEPTH SCALE METRES	BORING METHOD	SOIL PROFILE			SAMPLES				PENETRATION RESISTANCE (N), BLOWS/0.3m		SHEAR STRENGTH (Cu), kPA		ADDITIONAL LAB. TESTING	PIEZOMETER OR STANDPIPE INSTALLATION		
		DESCRIPTION	STRATA PLOT	ELEV. DEPTH (m)	NUMBER	TYPE	RECOVERY, mm	BLOWS/0.3m	●	▲	+ NATURAL ⊕ REMOULDED	WATER CONTENT, % W _p — W — W _L				
0	Diamond Rotary Core HQ (89mm OD)	Ground Surface		138.51												
		Grey brown silty sand and gravel (BASE MATERIAL)		138.43 0.08												Gravel
		Grey brown, SILTY SAND and gravel (GLACIAL TILL)		138.10												
		Highly fractured pink, fine grained Precambrian BEDROCK		0.41	1	RC			TCR = 100%, SCR = 20%, RQD = 20%							
2		Slightly weathered to fresh, pink, fine grained, strong Precambrian BEDROCK		136.78 1.73	2	RC		TCR = 100%, SCR = 90%, RQD = 50%								Bentonite
3					3	RC		TCR = 100%, SCR = 87%, RQD = 87%								
4		End of Borehole		135.18 3.33												
5																
6																
7																
8																
9																
10																

GEO - BOREHOLE LOG, 100737.001 GINT LOGS.GPJ, GEMTEC 2018.GDT, 5-18-21

RECORD OF BOREHOLE 21-04

CLIENT: Caivan Communities
 PROJECT: Preliminary Geotechnical Investigation, Perth Golf Course, Perth, Ontario
 JOB#: 100737.001
 LOCATION: See Site Plan, Figure 1

SHEET: 1 OF 1
 DATUM: CGVD28
 BORING DATE: May 3 2021




DEPTH SCALE METRES	BORING METHOD	SOIL PROFILE			SAMPLES				● PENETRATION RESISTANCE (N), BLOWS/0.3m ▲ DYNAMIC PENETRATION RESISTANCE, BLOWS/0.3m	SHEAR STRENGTH (Cu), kPA + NATURAL ⊕ REMOULDED WATER CONTENT, % W_p — W — W_L	ADDITIONAL LAB. TESTING	PIEZOMETER OR STANDPIPE INSTALLATION
		DESCRIPTION	STRATA PLOT	ELEV. DEPTH (m)	NUMBER	TYPE	RECOVERY, mm	BLOWS/0.3m				
0	Power Auger Hollow Stem Auger (210mm OD)	Ground Surface		134.66								
		Grey brown silty sand and gravel (BASE MATERIAL) Loose, brown SILTY SAND, trace gravel (GLACIAL TILL)		134.51 0.15	1	SS	305	6	●			
1	Hollow Stem Auger (210mm OD)	Weathered Bedrock		133.59 1.07	2	SS	355	45	●			
		Slightly weathered to fresh, dark grey, fine grained, strong Precambrian BEDROCK		133.22 1.44	3	RC			TCR = 56%, SCR = 56%, RQD = 80%			
2	Diamond Rotary Core HQ (89mm OD)										UCS	
3				131.18 3.48								
4		End of Borehole										
5												
6												
7												
8												
9												
10												


GEO - BOREHOLE LOG - 100737.001 GINT LOGS.GPJ - GEMTEC 2018.GDT - 5-18-21

RECORD OF HAND AUGERHOLE 21-201

CLIENT: Caivan Communities
 PROJECT: Preliminary Geotechnical Investigation, Perth Golf Course, Perth, Ontario
 JOB#: 100737.001
 LOCATION: See Site Plan, Figure 1

SHEET: 1 OF 1
 DATUM: CGVD28
 BORING DATE: May 5 2021

DEPTH SCALE METRES	BORING METHOD	SOIL PROFILE			SAMPLES				PENETRATION RESISTANCE (N), BLOWS/0.3m		SHEAR STRENGTH (Cu), kPA		ADDITIONAL LAB. TESTING	PIEZOMETER OR STANDPIPE INSTALLATION	
		DESCRIPTION	STRATA PLOT	ELEV. DEPTH (m)	NUMBER	TYPE	RECOVERY, mm	BLOWS/0.3m	DYNAMIC PENETRATION RESISTANCE, BLOWS/0.3m		WATER CONTENT, %				
10	20			30					40	50	60	70	80	90	
0	Hand Auger Open hole	Ground Surface		134.70											
		TOPSOIL		134.55											
		Brown SILTY CLAY (WEATHERED CRUST)		0.15	1	AS									
1		Brown SILTY SAND, some gravel (GLACIAL TILL)		133.73	2	AS									
		End of Hand Auger hole Hand Auger Refusal		133.58											
				1.12											
2															
3															
4															
5															
6															
7															
8															
9															
10															



GEO - BOREHOLE LOG - 100737.001 GINT LOGS.GPJ - GEMTEC 2018.GDT 21/5/21

RECORD OF HAND AUGERHOLE 21-202

CLIENT: Caivan Communities
 PROJECT: Preliminary Geotechnical Investigation, Perth Golf Course, Perth, Ontario
 JOB#: 100737.001
 LOCATION: See Site Plan, Figure 1

SHEET: 1 OF 1
 DATUM: CGVD28
 BORING DATE: May 5 2021

DEPTH SCALE METRES	BORING METHOD	SOIL PROFILE			SAMPLES				TESTING									
		DESCRIPTION	STRATA PLOT	ELEV. DEPTH (m)	NUMBER	TYPE	RECOVERY, mm	BLOWS/0.3m	PENETRATION RESISTANCE (N), BLOWS/0.3m	SHEAR STRENGTH (Cu), kPA	WATER CONTENT, %		ADDITIONAL LAB. TESTING	PIEZOMETER OR STANDPIPE INSTALLATION				
										W_p — W — W_L								
										10 20 30 40 50 60 70 80 90								
0	Hand Auger Open hole	Ground Surface	[Symbol]	135.35														
		TOPSOIL	[Symbol]	135.20														
		Brown SILTY SAND, trace gravel (GLACIAL TILL)	[Symbol]	0.15	1	AS												Native backfill
1		End of Hand Auger hole Hand Auger Refusal		134.44 0.91														
2																		
3																		
4																		
5																		
6																		
7																		
8																		
9																		
10																		

GEO - BOREHOLE LOG 100737.001 GINT LOGS.GPJ GEMTEC 2018.GDT 5-18-21



APPENDIX E

Chemical Analysis of Soil Samples
Samples Relating to Corrosion
(Paracel Laboratories Ltd. Order No. 2205579)

Certificate of Analysis

Report Date: 03-Feb-2022

Client: GEMTEC Consulting Engineers and Scientists Limited

Order Date: 28-Jan-2022

Client PO:

Project Description: 100737.002

Client ID:	22-226 SS-3	22-212 SS-3	-	-
Sample Date:	28-Jan-22 12:10	28-Jan-22 13:15	-	-
Sample ID:	2205579-01	2205579-02	-	-
MDL/Units	Soil	Soil	-	-

Physical Characteristics

% Solids	0.1 % by Wt.	67.7	94.7	-	-
----------	--------------	------	------	---	---


General Inorganics

Conductivity	5 uS/cm	201	104	-	-
pH	0.05 pH Units	7.53	7.26	-	-
Resistivity	0.10 Ohm.m	49.7	96.4	-	-

Anions

Chloride	5 ug/g dry	<5	<5	-	-
Sulphate	5 ug/g dry	16	<5	-	-

experience • knowledge • integrity



civil
geotechnical
environmental
field services
materials testing


civil
géotechnique
environnementale
surveillance de chantier
service de laboratoire des matériaux

expérience • connaissance • intégrité



APPENDIX E

LAND USE	LOT/BLOCK	AREA (sq.m/acs.)
DETACHED HOMES	LOT 1 TO 632 BOTH INCLUSIVE	177247.3 / 43.8
TOWNHOUSE	BLOCK 633 TO 696 BOTH INCLUSIVE	49832.4 / 12.3
MULTI-USE PATH	BLOCKS 697, 698, 699 AND 709	916.7 / 0.2
TRAMP STATION	BLOCK 706	502.3 / 0.1
PARK/OPEN SPACE	BLOCKS 700, 701 AND 702	22474.2 / 5.6
AFFORDABLE HOUSING	BLOCK 707	6099.9 / 1.5
SWM	BLOCKS 703, 704, 705 AND 710	40397.3 / 9.9
WETLAND	BLOCK 708	32793.8 / 81.0
STREETS	STREETS A TO STREET X	152142.2 / 37.8
TOTAL		777242.2 / 192.0



ADDITIONAL INFORMATION REQUIRED UNDER SECTION 51 OF THE PLANNING ACT.

- (A)-(B)(C)(E)(G) AND (L)-AS SHOWN ON DRAFT PLAN
- (C)-AS SHOWN ON DRAFT AND KEY PLANS
- (D)-LAND TO BE USED IN ACCORDANCE WITH SCHEDULE OF LAND USE (BY-TOWN MUNICIPAL SERVICES)
- (I)-OFFSHORE MARINE DEPOSITS OF CLAY, SILTY CLAY AND SILT, BEDROCK

SHEET 1 OF 3

DRAFT PLAN OF SUBDIVISION OF
PART OF LOT 26 AND 27 CONVESSION 1
 AND
PART OF LOT 25 AND 26 CONVESSION 2
 AND
PART OF PARK LOT 1 IN LOT 27 CONVESSION 2
 AND
PART OF THE ROAD ALLOWANCE BETWEEN CONCESSIONS 1 & 2 CLOSED BY BY-LAW LC204235
 ALL IN THE GEOGRAPHIC TOWNSHIP OF BATHURST

AND
SOUTH EAST PART OF LOT 1 CONVESSION 1 AS SHOWN ON COMPILED PLAN No. 8828
 IN THE GEOGRAPHIC TOWNSHIP OF DRUMMOND TOWN OF PERTH

AND
PART OF THE ROAD ALLOWANCE BETWEEN GEOGRAPHIC TOWNSHIPS OF BATHURST AND DRUMMOND
 COUNTY OF LANARK
 J.D. BARNES LIMITED

REGISTRARS COMPILED PLAN No. 8828
 TOWN OF PERTH
 LOT 2 IN S.W. HALF LOT 1
 CONVESSION 2

IN THE GEOGRAPHIC TOWNSHIPS OF BATHURST AND DRUMMOND
 COUNTY OF LANARK
 J.D. BARNES LIMITED

METRIC DISTANCES AND/OR COORDINATES SHOWN ON THIS PLAN ARE IN METRES AND CAN BE CONVERTED TO FEET BY DIVIDING BY 0.3048.

SCALE 1 : 1750

NOTES
 BEARINGS ARE UTM GRID, DERIVED FROM SPECIFIED CONTROL POINTS (SCP) 08872055011 AND 01019802271, UTM ZONE 18, NAD83 (CSRS).

ELEVATIONS
 ELEVATIONS SHOWN ON THIS PLAN ARE RELATED TO GEODETIC DATUM CGVD08/78
 CONTOUR INTERVALS ARE SHOWN AS 1m FOR MAJOR AND 0.25m FOR MINOR
 --- DENOTES MAJOR CONTOUR
 - - - - DENOTES MINOR CONTOUR

OWNER'S CERTIFICATE
 CAIVAN (PERTH) INC. BEING THE REGISTERED OWNER OF THE SUBJECT LANDS HEREBY AUTHORIZES J.D. BARNES LIMITED TO PREPARE AND SUBMIT THIS DRAFT PLAN OF SUBDIVISION FOR APPROVAL.

DATE _____
 FRANK CARO
 PRESIDENT
 (I HAVE THE AUTHORITY TO BIND THE CORPORATION)
 CAIVAN (PERTH) INC.


SURVEYOR'S CERTIFICATE
 I HEREBY CERTIFY THAT THE BOUNDARIES OF THE LAND TO BE SUBDIVIDED ARE CORRECTLY SHOWN.

DATE MAY 31, 2024
 C.M. FOX
 ONTARIO LAND SURVEYOR

DATA SOURCE
 DATA SHOWN HEREON IS COMPILED FROM VARIOUS SOURCES:
 - 1:100 FLOOD PLAN - PERTH GOLF COURSE FLOODPLAIN MAPPING AMENDMENT MAY 31, 2024, FSA
 - 2024 GRANTS OVER PROPOSED SIGNIFICANT WETLAND BOUNDARY AS PER METHURP AND ASSOCIATES
 - 2022 THE EROSION AND EROSION ACCESS ALLOWANCE AS PER KENNEDY CONSULTING ENGINEERS AND SCIENTISTS
 - 2024 MENDERSHIEF AS PER GEO MAPPING LTD.
 - HYDROGRAPHIC INFORMATION SHOWN HEREON AS PER FIRST BASE MAPPING 2022
 - SECOND BRIDGE OPTION AS PER CGH TRANSPORTATION


J.D. BARNES LIMITED
 SURVEYING & MAPPING GIS
 LAND INFORMATION SPECIALISTS
 62 STRAITS DRIVE, SUITE 101, LANARK, ON N3B 2W9
 T: (613) 731-7254 F: (613) 254-8609 www.jdbarnes.com

DRAWN BY: CE CHECKED BY: CF
 PLOTTED: 5/23/24 REFERENCE NO: 22-10-008-00-07
 SHEET 1 OF 3 DATE: 05/23/2024



FILE: G:\22-10-008\00\Drawings\Draft Plan\G:\22-10-008-00\Draft Plan v7.2_25 1.dwg

SCHEDULE OF LAND USE		
LAND USE	LOT/BLOCK	AREA (sqm/acs.)
DETACHED HOMES	LOT 1 TO 632 BOTH INCLUSIVE	177247.4 / 43.8
TOWNHOUSE	BLOCK 633 TO 696 BOTH INCLUSIVE	49832.4 / 12.3
MULTI-USE PATH	BLOCKS 697, 698, 699 AND 709	916.7 / 0.2
TRAMP STATION	BLOCK 706	502.3 / 0.1
PARK/OPEN SPACE	BLOCKS 700, 701 AND 702	22474.2 / 5.6
AFFORDABLE HOUSING	BLOCK 707	6099.9 / 1.5
SWM	BLOCKS 703, 704, 705 AND 710	40397.3 / 9.9
WETLAND	BLOCK 708	32793.8 / 81.0
STREETS	STREETS A TO STREET X	152142.2 / 37.8
TOTAL		777242.2 / 192.0



ADDITIONAL INFORMATION REQUIRED UNDER SECTION 51 OF THE PLANNING ACT.

- (A)(B)(C)(E)(G) AND (L)-AS SHOWN ON DRAFT PLAN
- (C)-AS SHOWN ON DRAFT AND KEY PLANS
- (D)-LAND TO BE USED IN ACCORDANCE WITH SCHEDULE OF LAND USE
- (F)-FULL MUNICIPAL SERVICES
- (I)-OFFSHORE MARINE DEPOSITS OF CLAY, SILTY CLAY AND SILT, BEDROCK

SHEET 2 OF 2

DRAFT PLAN OF SUBDIVISION OF
**PART OF LOT 26 AND 27
 CONCESSION 1**
 AND
**PART OF LOT 25 AND 26
 CONCESSION 2**
 AND
**PART OF PARK LOT 1
 IN LOT 27
 CONCESSION 2**

AND
**PART OF THE ROAD ALLOWANCE
 BETWEEN CONCESSIONS 1 & 2
 CLOSED BY BY-LAW LC204235**
 ALL IN THE GEOGRAPHIC TOWNSHIP OF BATHURST

AND
**SOUTH EAST PART OF LOT 1
 CONCESSION 1 AS SHOWN ON
 COMPILED PLAN No. 8828**
 IN THE GEOGRAPHIC TOWNSHIP OF DRUMMOND
 TOWN OF PERTH

AND
**PART OF THE ROAD ALLOWANCE
 BETWEEN GEOGRAPHIC TOWNSHIPS
 OF BATHURST AND DRUMMOND**
 COUNTY OF LANARK
 J.D. BARNES LIMITED

METRIC DISTANCES AND/OR COORDINATES SHOWN ON THIS PLAN ARE IN METRES AND CAN BE CONVERTED TO FEET BY DIVIDING BY 0.3048.

SCALE 1 : 1750

NOTES
 BEARINGS ARE UTM GRID, DERIVED FROM SPECIFIED CONTROL POINTS (SCP) 008205051 AND 01019502271, UTM ZONE 18, NAD83 (CSRS).

ELEVATIONS
 ELEVATIONS SHOWN ON THIS PLAN ARE RELATED TO GEODETIC DATUM CGVD08 78
 CONTOUR INTERVALS ARE SHOWN AS 1m
 FOR MAJOR AND 0.25m FOR MINOR
 --- DENOTES MIRROR CONTOUR

OWNER'S CERTIFICATE
 CAIVAN (PERTH) INC. BEING THE REGISTERED OWNER OF THE SUBJECT LANDS HEREBY AUTHORIZES J.D. BARNES LIMITED TO PREPARE AND SUBMIT THIS DRAFT PLAN OF SUBDIVISION FOR APPROVAL.



SURVEYOR'S CERTIFICATE
 I HEREBY CERTIFY THAT THE BOUNDARIES OF THE LAND TO BE SUBDIVIDED ARE CORRECTLY SHOWN.

MAY 31, 2024
 DATE


DATA SOURCE
 DATA SHOWN HEREON IS COMPILED FROM VARIOUS SOURCES:
 - 1:100 FLOOD PLAN - PERTH SOUP COURSE FLOODPLAIN MAPPING AMENDMENT MAY 31, 2024 - FSA
 - 2024 GRANTS OPEN PROSPECTOR SIGNIFICANT WETLAND BOUNDARY AS PER WETLUP AND ASSOCIATES
 - 2024 THE EROSION AND EROSION ACCESS ALLOWANCE AS PER GRANTS CONSULTING ENGINEERS AND GEOTECHNISTS
 - 2024 MEMBERSHIP AS PER GEO MAPPING LTD
 - TOPOGRAPHIC INFORMATION SHOWN HEREON AS PER PER BASE MAPPING 2022 - SECOND BRIDGE OPTION AS PER CGH TRANSPORTATION

J.D. BARNES LIMITED
 SURVEYING & MAPPING GIS
 LAND INFORMATION SPECIALISTS
 10 ZEPHYRUS DRIVE, SUITE 101, LANARK, ON L9B 3W9
 T: (416) 731-7241 F: (416) 254-8609 www.jdbarnes.com

DRAWN BY: CE CHECKED BY: CF
 PLOTTED: 6/12/24 REFERENCE NO: 22-10-008-00 37
 SHEET 2 OF 3 DATE: 06/12/2024



LAND USE	LOT/BLOCK	AREA (sqm/acs)
DETACHED HOMES	LOT 1 TO 632 BOTH INCLUSIVE	177247.3 / 43.8
TOWNHOUSE	BLOCK 633 TO 696 BOTH INCLUSIVE	49832.4 / 12.3
MULTI-USE PATH	BLOCKS 697, 698, 699 AND 709	916.7 / 0.2
TRAMP STATION	BLOCK 706	502.3 / 0.1
PARK/OPEN SPACE	BLOCKS 700, 701 AND 702	22474.2 / 5.6
AFFORDABLE HOUSING	BLOCK 707	6099.9 / 1.5
SWM	BLOCKS 703, 704, 705 AND 710	40397.3 / 9.9
WETLAND	BLOCK 708	32793.8 / 81.0
STREETS	STREETS A TO STREET X	152142.2 / 37.8
TOTAL		777242.2 / 192.0



ADDITIONAL INFORMATION REQUIRED UNDER SECTION 51 OF THE PLANNING ACT.

- (A)(B)(C)(E)(G) AND (L)-AS SHOWN ON DRAFT PLAN
- (C)-AS SHOWN ON DRAFT AND KEY PLANS
- (D)-LAND TO BE USED IN ACCORDANCE WITH SCHEDULE OF LAND USE (BY-TOWN MUNICIPAL SERVICES)
- (I)-OFFSHORE MARINE DEPOSITS OF CLAY, SILTY CLAY AND SILT, BEDROCK

SHEET 3 OF 3

DRAFT PLAN OF SUBDIVISION OF
PART OF LOT 26 AND 27 CONCESSION 1
 AND
PART OF LOT 25 AND 26 CONCESSION 2
 AND
PART OF PARK LOT 1 IN LOT 27 CONCESSION 2

AND
PART OF THE ROAD ALLOWANCE BETWEEN CONCESSIONS 1 & 2 CLOSED BY BY-LAW LC204235
 ALL IN THE GEOGRAPHIC TOWNSHIP OF BATHURST

AND
SOUTH EAST PART OF LOT 1 CONCESSION 1 AS SHOWN ON COMPILED PLAN No. 8828

IN THE GEOGRAPHIC TOWNSHIP OF DRUMMOND TOWN OF PERTH

AND
PART OF THE ROAD ALLOWANCE BETWEEN GEOGRAPHIC TOWNSHIPS OF BATHURST AND DRUMMOND

COUNTY OF LANARK
 J.D. BARNES LIMITED

METRIC DISTANCES AND/OR COORDINATES SHOWN ON THIS PLAN ARE IN METRES AND CAN BE CONVERTED TO FEET BY DIVIDING BY 0.3048

SCALE 1 : 1750

NOTES
 BEARINGS ARE UTM GRID, DERIVED FROM SPECIFIED CONTROL POINTS (SCP) 00872050511 AND 01019902271, UTM ZONE 18, NAD83 (CSRS).

- LEGEND**
- DENOTES FLOODPLAIN
 - - - DENOTES 30m SETBACK FROM RIVER
 - DENOTES WETLAND/ECOSITES
 - DENOTES 30m SETBACK BUFFER WETLAND/ECOSITE

OWNER'S CERTIFICATE
 CAIVAN (PERTH) INC. BEING THE REGISTERED OWNER OF THE SUBJECT LANDS HEREBY AUTHORIZES J.D. BARNES LIMITED TO PREPARE AND SUBMIT THIS DRAFT PLAN OF SUBDIVISION FOR APPROVAL.

DATE: _____
 FRANK CARO
 PRESIDENT
 (I HAVE THE AUTHORITY TO BIND THE CORPORATION)
CAIVAN (PERTH) INC.

SURVEYOR'S CERTIFICATE
 I HEREBY CERTIFY THAT THE BOUNDARIES OF THE LAND TO BE SUBDIVIDED ARE CORRECTLY SHOWN.

DATE: MAY 31, 2024
 DATE: _____
 J.D. BARNES LIMITED
 ONTARIO LAND SURVEYOR

DATA SOURCE
 DATA SHOWN HEREON IS COMPILED FROM VARIOUS SOURCES:
 - 1:100 FLOOD PLAN - PERTH SOUP COURSE FLOODPLAIN MAPPING AMENDMENT MAY 31, 2024 - FSA
 - 2024 GRANTS OPEN PROSPECTOR SIGNIFICANT WETLAND BOUNDARY AS PER WETLUM AND ASSOCIATES
 - 2022 THE EROSION AND EROSION ACCESS ALLOWANCE AS PER KIMBER CONSULTING ENGINEERS AND SCIENTISTS
 - 2024 MEMBERSHIP AS PER GEO MORPHO LTD
 - TOPOGRAPHIC INFORMATION SHOWN HEREON AS PER FIRST BASE MAPPING 2022 - SECOND BRIDGE OPTION AS PER CGH TRANSPORTATION

J.D. BARNES LIMITED
 SURVEYING & MAPPING GIS
 LAND INFORMATION SPECIALISTS
 62 TRITON DRIVE, SUITE 101, LANARK, ON L9K 2W9
 T: (613) 731-7241 F: (613) 254-8697 www.jdbarnes.com

DRAWN BY: CE CHECKED BY: CF
 PLOTTED: 6/12/24 DATE: 06/12/2024

REFERENCE No: 22-10-008-00 37
 SHEET 3 OF 3

